

8560
8562

8561
8563

103
60
50
00

02
60
50
00

Diag. Cht. No. 8864-2.

Form 504

U. S. COAST AND GEODETIC SURVEY

DEPARTMENT OF COMMERCE

DESCRIPTIVE REPORT

Type of Survey Topographic
Project 24050 T-8560 thru
Field No. (Ph-34) Office No. T-8563

LOCALITY

State Alaska

General locality Rat Islands of Aleutian Islands

Locality Semisopochnoi Island

1949-53

CHIEF OF PARTY

H.E. Finnegan, Chief of Field Party
L.W. Swanson, Div. of Photo. Wash, D.C.

LIBRARY & ARCHIVES

DATE May 23, 1958

B-1670-1 (1)

DATA RECORD

	8560	Semisophochnoi Is.	N.W.
T	8561	"	N.E.
	8562	"	S.W.
	8563	"	S.E.

Project No. (II): Ph 34(24050) Quadrangle Name (IV):

Field Office (II): USC&GSSPIONEER

Chief of Party: Henry E. Finnegan

Photogrammetric Office (III): Washington, D.C. Officer-in-Charge: L. W. Swanson

Instructions dated (II) (III): 3 February 1948

Copy filed in Division of
Photogrammetry (IV)

Supplemental instructions: 18 March 1944
10 February 1948
8 April 1948

Method of Compilation (III): Reading Plotters

Manuscript Scale (III): 1:20,000

Stereoscopic Plotting Instrument Scale (III): 1:20,000

Scale Factor (III): none

Date received in Washington Office (IV):

Date reported to Nautical Chart Branch (IV):

Applied to Chart No.

Date:

Date registered (IV): 29 Mar. 1958

Publication Scale (IV):

Publication date (IV):

Geographic Datum (III): NA 1927

Vertical Datum (III): MSL

Mean sea level except as follows:
Elevations shown as (25) refer to mean high water
Elevations shown as (5) refer to sounding datum
i.e., mean low water or mean lower low water

Reference Station (III):

Lat.:

Long.:

Adjusted
Unadjusted

Plane Coordinates (IV):

State: UTM

Zone: 60

Y=

X=

Roman numerals indicate whether the item is to be entered by (I) Field Party, (II) Photogrammetric Office, or (IV) Washington Office.

When entering names of personnel on this record give the surname and initials, not initials only.

DATA RECORD

Field Inspection by (II): Ernest B. Lewey

Date: June-Sept. 1949

Planetable contouring by (II): none

Date:

Completion Surveys by (II): none

Date:

Mean High Water Location (III) (State date and method of location):

September 1953 (photography) by stereocompilation

Projection and Grids ruled by (IV): A. Riley

Date: 8/31/54

Projection and Grids checked by (IV): A. Riley

Date: 9/1/54

Control plotted by (III): C. O. DeMarr

Date: Sept. 15, 1954

Control checked by (III): J. Amburn

Date: Sept. 16, 1954

Radial Plot or Stereoscopic

Date: Nov. 2, 1956

Control extension by (III): J. Battley, Jr.

Stereoscopic Instrument compilation (III):
 Planimetry } C. Misfeldt
 Contours } W. Heinbaugh

Date: Jan. 1957

Date: Jan. 1957

Manuscript delineated by (III): C. Misfeldt
 W. Heinbaugh

Date: Jan. 1957

Photogrammetric Office Review by (III): L. Levin

Date: Feb. 12, 1957

Elevations on Manuscript
 checked by (II) (III): L. Levin

Date: Feb. 12, 1957

Camera (kind or source) (III): Reading 9-lens

Number	Date	Time	Scale	Stage of Tide
41859-62	9/10/53	12:18	1:20,000	1.8 MLLW
41869-71	"	12:45		1.8
42211-13	9/26/53	15:05		3.0
42216-19	"	15:15		3.0
42222-26	"	15:30		3.1
42229-32	"	15:40		3.1
42235-37	"	15:50		3.2

(from appended tabulation
prepared by Div. of Tides)

Tide (III)

Reference Station: Sweeper Cove (observed)

Subordinate Station:

Subordinate Station:

Washington Office Review by (IV):

Final Drafting by (IV):

Drafting verified for reproduction by (IV): W.O. Hallinan

Proof Edit by (IV):

Land Area (Sq. Statute Miles) (II):

Shoreline (More than 200 meters to opposite shore) (III):

Shoreline (Less than 200 meters to opposite shore) (III):

Control Leveling - Miles (II):

Number of Triangulation Stations searched for (II):

Recovered:

Identified:

Number of BMs searched for (II):

Recovered:

Identified:

Number of Recoverable Photo Stations established (III):

Number of Temporary Photo Hydro Stations established (III):

Remarks:

Diurnal

Ratio of Ranges	Mean Range	Spring Range
		3.7

Date:

3/4/58 - 7-8560

Date: 3/5/58 - 7-8561

4/5/58 - 7-8562

Date: 4/4/58 - 7-8563

3-6-58

Date:

Aleutian Islands



Diurnal Range $GE\ 3.7'$ for this station

Form 869
Ed. May, 1929
DEPARTMENT OF COMMERCE
U. S. COAST AND GEODETIC SURVEY

TIDES: HOURLY HEIGHTS

Same diurnal range; same time.
Same height as Sweeper Cove.
These tides were observed at S.

Station: Semisopachnoi Island, Akutan Is.

Year: 1953 from conv.

Observer: _____

Lat. _____

Long. _____

Time Meridian: $165^{\circ}W$ Height datum is MLLW which is _____ ft. below B. M.

Month and Day	mo.	d.	d.	d.	d.	d.	d.	d.	d.	Horizontal Sum
Day of Series										
Hour	Feet	Feet	Feet	Feet	Feet	Feet	Feet	Feet	Feet	Feet
0	1.7	0.9						-1.0	-1.0	
1	1.6	0.8						-1.1	-1.5	
2	1.6	0.9						-0.8	-1.6	
3	1.9							-0.3	-1.4	
4	2.1							0.4	-0.7	
5	2.2							1.1		
6	2.3							1.8		
7	2.4							2.2		
8	2.2							2.5		
9	2.0							2.7		
10	1.9							2.7		
11	1.7							2.6		
Noon	1.8							2.6		
13	1.8							2.6		
14	1.9							2.8		
15	2.0							3.0		
16	2.2							3.2		
17	2.3							3.3		
18	2.2							3.3		
19	2.1							3.0		
20	2.0							2.4		
21	1.7							1.6		
22	1.3							0.6		
23	1.1							-0.2		
Sum										

Sum for

=

Divisor = (28d) 672; (29d) 696; (30d) 720; (31d) 744. Mean for month =

Tabulated by _____

Date _____

Summed by UEN

Date 11-20-55

FIELD INSPECTION REPORT FOR AIR PHOTOGRAPHS

South Side of Little Sitkin Island and Semisopochnoi Island

Rat Islands, Aleutian Islands

Project CS-218 Ship PIONEER H.E. Finnegan, Comdg.

Season of 1949

INSTRUCTIONS:

Original Instructions for this Project were dated 3 February 1938. Applicable Supplemental Instructions were dated 18 March 1944, 10 February 1948, and 8 April 1948. (Items 2, 9, 10, and 11 of the attached List of Instructions).

PHOTOGRAPHS USED:

Little Sitkin Island:

(Note: This report covers the field inspection of the southern part of Little Sitkin Island, which was done in 1949. The remainder of the island was field inspected in 1948).

Coverage of Little Sitkin Island is on U.S. Navy five lens photographs, flown in 1935, approximate scale 1-30,000; and U.S. Army single lens photographs, flown in 1943, approximate scale 1-40,000. Neither set of photographs give good coverage of the southern tip of the island, the Army photos did not extend far enough south and clouds obscured this part of the island on the Navy photos. The Army photos are quite clear, but their small scale made them very difficult to work with. The Navy photos are indistinct and it is difficult to delineate detail on them.

No further field work will be necessary on the southern tip of the island when better photographs are available, since sufficient notes were made on the photos which were field inspected this year.

The following photographs were field inspected: U.S. Army, 1943, FV43; and U.S. Navy, 1935, Nos. 895 and 898.

A section of TOPOGRAPHIC MANUSCRIPT T9134 (Advance Copy), which was field edited, is submitted with this report.

PHOTOGRAPHS USED: (Continued)

Semisopochnoi Island:

The only photographs available for field inspection on Semisopochnoi Island were U.S. Navy Photos flown in 1935 to an approximate scale of 1-30,000. These photos are indistinct and it was difficult to delineate detail on them. Also, the scale is smaller than is desired for field inspection.

The following photographs were field inspected: U.S. Navy, 1935, Nos. 739, 741, 742, 745, 748, 750, 752, 753, 757, 758, 759, 760, 761, 765, 766, 767, 771, 773, 779, 782, 785.

PERSONNEL:

All field inspection was done by LCDR. E. B. Lewey.

ABBREVIATIONS:

Abbreviation of descriptive notes used for field inspection were tabulated. A sheet of these abbreviations is included with this report.

FIELD INSPECTION:

Little Sitkin Island:

See AIR PHOTO REPORT of Field Inspection, Rat Islands, Ship PIONEER, 1948, for General Description, Streams, Lakes, and Lagoons.

Semisopochnoi Island:

General Description: Prominent features of Semisopochnoi Island are:

1. Two volcanic peaks topping the mountain on the northwest side of the island, the northeasterly of the two being the highest and most prominent peak on the island. It is 4005 feet high and is rather symmetrical in shape with steep slopes on all sides and has a large flat top to the northeast of the highest tip.
2. Three cones in the southwest center of the island, the highest of which (the northwesterly one) is 2669 feet. Actually, there are deep craters inside the cones, but from offshore they appear as conical shaped flat-topped peaks.
3. Two volcanoes on the south tip of the island; one 1620 feet high, and the other (northerly of the two) 2862 feet high. Both are conical shaped and have steep slopes, particularly to the east and south.

FIELD INSPECTION (Continued):

4. Two jagged peaks on the southeast side of the island. These peaks are quite sharp and ragged and are probably the most easily identified of any peaks on the island. They are slightly over 3000 feet in elevation.

5. A peak on the northeast side of the island which is 2928 feet high. It is on the north side of a deep valley and is not as symmetrical in shape as are most other peaks on the island. The high point is on the north end of a sharp ridge.

6. A deep valley extending inland from the prominent bight on the east side of the island. The valley is about 0.6 miles in width at its eastern end and rises gradually to the westward for a distance of approximately 1.5 miles, then rises rapidly to a saddle around 500 feet in height and drops off again into a crescent shaped valley in the center of the island. The inner valley is less than 300 feet in elevation.

There are two other rather prominent valleys reaching inland, one from the southeast side of the island, and one from the bight on the west side of the island; but neither are as prominent as the one discussed above.

Generally, the shoreline of the entire island is rocky and is backed by steep bluffs and cliffs from a few feet to several hundred feet high. The island is ragged and rough, being badly cut up with deep gullies. Due to the roughness of the terrain, travel over most of the island is difficult by foot and impossible by vehicle.

Shoreline: (Note: Names used in this report, other than charted names, are indicated on U.S. Army Quad. Maps and are for identification purposes only. They are not necessarily recommended for Geographic Names).

ESE Bight: There is a sand beach, 600-700 meters in length, in the north center of ESE Bight. The slope of the beach is gentle, the low waterline averages about 25 meters from the high waterline. A sand bar appears at times 10-25 meters offshore from the low waterline and hinders landing on the beach at such times. The bar comes and goes with the storms. Dry ramp landings may be made on the beach when the bar is not in evidence, but wet landings result when the bar is present. However, most vehicles may ford the intervening water from the bar to the beach. It is difficult to hold a landing craft on the bar when there is much swell and such operations are restricted to almost flat seas. Exit from the beach is hindered only by sand and dirt banks 20 to 50 feet high. The best landing spot is just south of the stream emptying into the approximate center of the bight and it can be identified (at present) by a hut that stands on the bank just north of the stream. The southern portion of the head of this bight has a boulder beach with some boulders 10-30 meters off the waterline in shoal water. These boulders make beaching of landing craft inadvisable, though landings by skiff or dory can usually be made. The north shore of the bight is formed by vertical rocky cliffs with large boulders at the waterline. The south shore has boulder beaches backed by steep rocky bluffs.

FIELD INSPECTION (Continued):

ESE Head is fringed with rocky ledges and foul areas to 200 meters offshore and has heavy kelp to approximately the same distance. The shoreline is backed by steep rocky bluffs.

Southwestward of ESE Head for a distance of two and one-half miles, the shoreline is at the foot of steep dirt, grass, and rocky bluffs with large boulders at the waterline. The only dangers along this stretch of shoreline are occasional boulders 10-30 meters offshore. The shore is fringed with kelp to about 100 meters offshore.

SSE Bay: This slight indentation is backed with a small low valley extending about a mile to the northwest and is marked with a sharp rocky point to the northeast. A perennial stream empties into the approximate center of the bay and at present a shack stands on the south bank near the shoreline. The bay has a sand beach approximately 800 meters in length, but it is quite flat and dry ramp landings are never possible. Landings are difficult at any time and impossible when there is much swell. The portion of the beach south of the stream is strewn with large boulders. South of SSE Bay to Sugarloaf Knob there are boulders beaches backed by moderately steep grass slopes with no offlying dangers. Sugarloaf Knob is fringed with kelp to 100 meters offshore.

Sugarloaf Head: The shoreline around Sugarloaf Head lies at the base of vertical rocky cliffs. There are boulders at the waterline with some rocky ledges, but there are no dangers more than 50 meters offshore. Back of the shoreline are steep slopes up to the two volcanoes. The slopes are lava flows and ash and are covered by tundra on the lower levels.

South Point to Southwest Knob: The shoreline is at the base of steep cliffs and bluffs, in general, and is ragged with many jutting rocky ledges, narrow rocky points, offlying rocks and pinnacles. However, there are no underwater dangers more than 100 meters offshore, except (1) off the rocky point 0.8 miles northwest of South Point and (2) off SSW Point. A cluster of sunken rocks lies approximately 200 meters off the first mentioned point and a sunken rock lies 150 meters off the center of SSW Point. These rocks do not show on the photographs, but are plotted on launch boat sheets of PI-2249 (H-7726).

Large landing craft may beach on the cobblestone and boulder beach which lies 0.6 miles northwest of South Point. However, landings must be made under almost perfect conditions, since swells of any size break heavily on the beach. Also, the cobblestones and boulders would damage the craft when there is surf. It is seldom possible to land on this beach with pulling boats, due to the surf. Exit from the beach is possible by laying a matting over the boulders.

Approximately 1200 meters west-northwest of the above mentioned beach, just east of a sharp rocky point, and at the mouth of a deep

FIELD INSPECTION (Continued):

ravine, lies a very small cobblestone and boulder beach. There are scattered huge boulders at the waterline which makes the beach unsuitable for landing craft. The swells do not break as heavily on this beach as on the one to the east and pulling boats may land in light swells.

There is a good landing spot for pulling boats just to the west of SSW Point. Landings may be made on large square boulders behind offlying rocks and kelp beds. Exit from the beach is thru a break in the bluff.

A short small boulder beach lies about midway between SSW Point and Southwest Knob, and a small sand beach lies at the bend in the shoreline northeast of Southwest Knob. These beaches are not suitable for landings at any time because breakers are present even in light swells.

Southwest Knob: Southwest Knob is a high-pointed peninsula on the southwest side of Semisopochnoi Island. The outer point is higher than the connecting land. The knob is surrounded with pinnacle rocks to 300 meters offshore, the highest of which is to the westward and is approximately 50 feet high. The waterline around the knob is among large boulders and at the base of vertical rocky cliffs.

There are patches of sand beach to the northwest of Southwest Knob, particularly just east of the stream emptying into SW Indent. This latter mentioned beach is 600 meters long and landing craft may beach on it in calm weather. Moderate swells break on the beach making any kind of landing hazardous in other than calm weather. Exit from the beach by vehicles would be difficult on account of the steep dirt and grass bluffs.

WSW Head: WSW Head is the bold and steep headland on the southwest side of Semisopochnoi Island. The shoreline along WSW Head is at the foot of steep rocky cliffs and is fringed with heavy kelp beds to 200 meters offshore. Waterline is among large boulders all along with occasional boulders 10-50 meters offshore. There are no other dangers.

WSW Bight: From this bight, on the west end of the island, a valley about 0.75 miles wide extends eastward 1.0 mile. The valley floor consists of large boulders covered with tundra which makes any kind of travel difficult.

There is 1100 meters of sand beach 10-20 meters wide in the center of the bight. However, there are boulders under and back of the sand giving this beach a doubtful value for use of landing craft. Also, there is a shoal off the center of the beach over which moderate swells break. At high tide, and with smooth seas, dry ramp landings would be possible. Under other conditions, landings would be wet

FIELD INSPECTION (Continued):

and hazardous. Heavy swells roll into the bight quite frequently.

The shoreline on the southeast and northeast sides of the bight is at the base of steep bluffs, is fringed with kelp, and has large boulders at the waterline.

Tuman Head: Tuman Head is the bold, steep, rocky headland on the west side of Semisopochnoi Island. The shoreline is at the base of steep rocky cliffs and slides and is fringed with kelp to 300 meters offshore. Waterline is formed by large boulders with occasional boulders 10-30 meters offshore. A foul area extends 150 meters off South Tuman Point, marked on the outer end by a rock 4 feet above high water. Otherwise, there are no dangers.

WNW Bight: WNW Bight is the indentation in the shoreline northeast of Tuman Head. Except at the three beaches discussed below, the shoreline is at foot of steep cliffs and is fringed with kelp. Boulders form the waterline in most places.

There are two offshore rocks in the bight: one baring 4 feet at high water 100 meters off the north shore of Tuman Head; and one baring 2 feet at MLLW 300 meters offshore from the gravel and small boulder beach on the east side of the bight. There are two small stretches of sand beach just northeast of the gravel and small boulder beach. Neither of the three beaches are suitable for landing craft, except under exceptionally good conditions. Besides, exits from the beaches are impractical. Several landings were made with a LCVF on the west end of the gravel and small boulder beach during the season of 1949, but good conditions had to be picked and it was necessary to build a ramp to get vehicles over the boulders.

WNW Point to Petrel Point: This stretch of shoreline is marked by steep dirt and grass cliffs with boulders at the waterline. Foul areas and high water rocks extend to 100 meters off the points, otherwise, there are no dangers. Heavy kelp beds extend to 300 meters offshore.

Dry ramp landings are possible on the small gravel beach at the bend in the shoreline south of Petrel Point (in NNW Bight) in good weather. There is no exit from the beach.

A waterfall on the west side of Petrel Point, and near its northern tip, is prominent to the westward.

Petrel Point to Northeast Point: Except in NNE Bight, the shoreline is at the base of high rocky slides, has large boulders at the waterline, and is fringed with scattered kelp 200-300 meters offshore.

A very small beach, composed of small boulders, at the bend in the shoreline on the east side of Petrel Point affords dry ramp landings in good weather. There is no exit from the beach.

FIELD INSPECTION (Continued):

NNE Bight has a gravel and small boulder beach approximately 1200 meters long and 10-20 meters wide. It is not suitable for landing craft, except under ideal conditions, because of surf and occasional large boulders. The bluffs back of the beach make an exit impractical. There is a thick and extensive kelp patch in this bight.

High water rocks and ledges extend 150 meters off Northeast Point. There are no other dangers along this stretch of shoreline.

Northeast Point to Pochnoi Point: The shoreline is at the base of steep bluffs and cliffs. In general, boulders mark the waterline, but there are stretches of gravel and cobblestone beaches. None of the beaches are suitable for landing craft, because of underwater boulders close inshore and lack of exits.

The only danger any distance offshore is a sunken rock, covered 1 foot at MLLW, 150 meters offshore of the north side of Pochnoi Point. This rock is off a deep ravine and is approximately 1.25 miles northwest of the center of Pochnoi Point.

Pochnoi Point is bounded by almost vertical rocky cliffs and has numerous rocks and pinnacles to 150 meters offshore.

STREAMS, LAKES, LAGOONS:

There are a total of seventeen perennial streams on Semisopochnoi Island that empty into the ocean, and numerous intermittent streams. The more prominent perennial streams are those emptying into ESE Bight, SSE Bay, WSW Bight, WNW Bight, at Petrel Point, and into NNE Bight. All of the perennial streams and the more prominent of the intermittent streams are marked on the photographs. There is a large lake in the center of the island which drains southward and into SSE Bay. Its elevation is approximately 250 feet.

A small lake exists 0.1 miles inland from the southeast side of WSW Bight. No drainage from this lake was noticed, but it probably drains under the boulders and into WSW Bight.

There are several intermittent ponds on Pochnoi Point.

HORIZONTAL CONTROL:

The following triangulation stations were identified on photographs and Control Station Identification Cards have been made for them:

Little Sitkin Island:

Waterfall, W. Side Little Sitkin I., 1948; Large Waterfall, W. Side Little Sitkin I., 1948. These are intersection stations, located in 1948 and identified on photographs in 1949.

HORIZONTAL CONTROL (Continued):

Semisopochnoi Island:

The following are for horizontal control only: RUG; *ARCH (sub.sta.); *POCHNOI; SHACK; *SUGAR (sub.sta.); KEM.

The following are for both horizontal and vertical control: *KNIFE; *DOWN (sub.sta.).

The following are primarily for vertical control, but it is thought that they may be pricked accurately enough for horizontal control also----if needed: Peak #6; *TUMAN; South Volcano; Semi. Volcano; Horn Peak; Anvil Peak; Rim Peak; Peak #4; N. Split Peak; and S. Split Peak. All were located in 1949.

* denotes main scheme stations. Others are intersection stations.

VERTICAL CONTROL:

Vertical control data is being submitted in a separate report.

HYDROGRAPHIC SIGNALS:

All signals necessary for the control of hydrography were located on graphic control sheets. Some were located by planetable; some by sextant cuts; and some by a combination of triangulation, planetable, and sextant cuts.

No photo plots were made in the field.

All signals that could be positively identified were marked on the photographs for future reference, if needed. Control Station Identification Cards are not being submitted for hydrographic signals.


LANDMARKS FOR CHARTS:

The waterfall on the west side of Petrel Point is sufficiently prominent to be charted as a landmark. It is pricked on Navy Photo. # 742, Control Station Identification Card and Form 567 have been prepared for it and are included with this report.

ABSTRACT:

- 1- List of Instructions and Supplemental Instructions for Project CS-218.
- 1- List of abbreviations.
- 20- Control Station Identification Cards of triangulation stations. ✓
- 1- Control Station Identification Card of Landmark. ✓
- 1- Form 567 (Landmarks for Charts).
- 1- Sketch (Photo Inspection Index).
- 1- Section of TOPOGRAPHIC MANUSCRIPT T9134.

Submitted by:


Ernest B. Lewey,
LCDR., USC&GS,
Ship PIONEER

Approved and forwarded:


Henry E. Finnegan
CDR., USC&GS
Comdg. Ship PIONEER

LEGEND
FIELD INSPECTION - AIR PHOTOS

SHORELINE:

rky - rocky
rl - rock ledge
sh - shelving
st - steep - to
rp - rocky point
hwl - high water line
lwl - low water line

BEACHES:

bb - boulder beach
cb - cobblestone beach
sb - sand beach
 above followed by (d) - dry ramp landing on steep beach
 above followed by (w) - wet ramp landing on gentle beach
gb - gravel beach

BLUFF, CLIFFS, SLIDES, ETC.

cl - cliff, rocky
ba - low earth bank
bl - bluff
sl - slide
rp - rocky point

INTERIOR:


bo - boulders
ga - grass and moss
lv - lava
lo - loose rock
pe - pond
rl - rock ledge outcrop
sw - swamp
tu - tundra

STREAMS:

is - intermittent stream
ps - perennial stream


OFFSHORE ROCKS, ETC.

ra - rock awash, give height and time if critical
rh - rock above high water, and approximate height
rs - sunken rock
fa - foul area
kp - kelp
tr - tide rips



1949 Field Inspection

The photos indicated around
Semisopochnoi Is. Nos. 739—785
are 1935 U.S. Navy Photos of
poor quality - see D.R. p. 2



Photogrammetric Plot Report
Project 24050
Semisopochnoi Island

21. Area Covered

This plot was laid on four topographic manuscripts, T-8560, 8561, 8562 and 8563 which cover Semisopochnoi Island entirely.

22. Method

The radial plot was laid on vinylite manuscripts on which the polyconic projection and the UTM grid with 1000 meter intervals, were ruled at 1:20,000 scale. The grid was used to junction the manuscripts.

The photographs were nine-lens metal mounts and were prepared in the conventional manner selecting shoreline pass points, where possible, at intervals of 4 inches and points in the interior at a density of about 7 inches.

Vinylite templet stock was used throughout and master calibration templet for photographs 40261 thru 43156 was used for radial adjustments.

The attached sketch shows the layout, photographs used and the density of control.

23. Adequacy of Control

Horizontal control was considered adequate. Eighteen field-identified control stations were furnished by the field party. Of these, ten stations were noted as primarily vertical control, but were thought accurately enough identified for horizontal control (See Field Inspection Report, page 8)

Thirteen of the eighteen stations identified were selected on the office photographs. The other five stations could not be accurately enough identified from the 1935 1:30,000 U.S. Navy photographs used for field inspection.

Of the thirteen control stations selected and used in the radial plot, nine held within 0.3 mm and four did not hold. These four are discussed below:

South
Semi Volcano 1949 (intersection station) ... this station was picked primarily for vertical control. It is believed to be accurately identified on the photographs; but as the radial plot position falls 7.7 mm W of the plotted position, an error in the listed position is indicated. ?

7.7 mm

Evidently a difference in identification of point on a rounded top egg same applies to station Juanan - next page. See also item 32.

Tuman 1949 (intersection station) ~~32.0~~ ^{33.2} mm N.E. of plotted position This station had a poor field description and office photo-identification was considered doubtful. Other nearby control held.

Pochnoi 1948 0.9 mm N of plotted position - ground measurements furnished by the field did not appear to conform to the description (high pt.). The highest point in the area was selected, but it was apparent upon laying the plot that the measured position would have held.

Peak 6 1949 0.4 mm W of plotted position. This was an intersection station primarily for vertical control and would not hold tight with other better identified control.

24. Supplemental Data

None

25. Photography

The photography was more than adequate as to coverage and overlap. There was, however, many photographs obscured by clouds and the abundance of photography was necessary to assure adequate stereoscopic coverage for contouring.

Submitted by:

Jeter P. Battley, Jr.
Cartographer

Approved by:

E. H. Ramey
Chief, Graphic Compilation

MAP T. 8560 PROJECT NO. 7931 SCALE OF MAP 1:20,000 SCALE FACTOR

STATION	SOURCE OF INFORMATION (INDEX)	DATUM	LATITUDE OR Y-COORDINATE LONGITUDE OR X-COORDINATE	DISTANCE FROM GRID IN FEET, OR PROJECTION LINE IN METERS		DATUM CORRECTION	N.A. 1927 - DATUM DISTANCE FROM GRID OR PROJECTION LINE IN METERS		FACTOR DISTANCE FROM GRID OR PROJECTION LINE IN METERS
				FORWARD	(BACK)		FORWARD	(BACK)	
✓ RUG 1949	Z-794 p5	1927	51 57 58.004 179 28 10.658				1792.8 (61.7)		
✓ TUMAN 1949	791 p1	"	51 57 58.539 179 30 58.016				776.2 (369.3)		
✓ ARCH 1949	791 p4	"	51 59 43.412 179 32 31.294				1809.2 (45.2)		
✓ HORN PK 1949	p7	"	51 58 41.977 179 35 15.282				1107.6 (38.0)		
✓ SLIP 1949	791 p1	"	51 58 58.030 179 29 02.253				1341.6 (512.7)		
BEACH 1949	793 p1	"	51 57 23.320 179 29 37.194				597.0 (547.7)		
✓ HEAD 1949	791 p4	"	52 00 46.516 179 31 21.901				1297.4 (557.0)		
✓ SCALE 1949	794 p4	"	52 00 07.993 179 31 10.227				291.8 (853.8)		
✓ CABLE 1949	794 p5	"	51 58 47.439 179 29 12.153				1793.5 (61.0)		
✓ FLAT PK 1949	794 p7	"	51 58 02.518 179 29 36.856				63.0 (1102.1)		
ARCH SUB. 1949			51 59 179 32				729.8 (1133.7)		
							720.3 (435.5)		
							1137.7 (116.8)		
							1171.8 (669.5)		
							217.0 (1607.6)		
							195.1 (919.5)		
							1166.1 (388.2)		
							232.0 (913.1)		
							77.9 (1776.4)		
							703.7 (111.8)		
							1313.9 (540.4)		
							611.9 (532.8)		

1 FT. = 3048006 METER

COMPUTED BY C. O. DeHann

DATE 10 September 1954

CHECKED BY J. C. Lunde

DATE 11 September 1954

M-2388-12

MAP T. 8561 PROJECT NO. Ph-34 SCALE OF MAP 1:20,000 SCALE FACTOR

STATION	SOURCE OF INFORMATION (INDEX)	DATUM	LATITUDE OR y -COORDINATE LONGITUDE OR x -COORDINATE	DISTANCE FROM GRID IN FEET, OR PROJECTION LINE IN METERS FORWARD (BACK)	DATUM CORRECTION	N.A. 1927 - DATUM DISTANCE FROM GRID OR PROJECTION LINE IN METERS FORWARD (BACK)	FACTOR DISTANCE FROM GRID OR PROJECTION LINE IN METERS FORWARD (BACK)
✓ RIM PK 1949	p6	1927	51 58 08.540 179 40 36.731			264.0 1590.5	
✓ DOWN 1949	p4	"	52 00 22.611 179 42 05.056			701.3 444.2	
✓ POCHNOI 1948	p3	"	51 57 37.123 179 45 53.821			698.9 1155.7	
SHORE 1949	p3	"	51 57 19.590 179 43 31.794			96.4 1048.0	
✓ INDENT 1949	p4	"	51 59 02.762 179 43 23.921			1156.7 697.8	
✓ VALVE (Shoran Sta) 1949	p5	"	51 57 43.699 179 45 54.425		9	1027.7 118.0	
RHINO 1949	p5	"	51 57 22.039 179 46 17.628			605.5 1249.0	
✓ ANVIL PK 1949	p6	"	51 59 12.983 179 36 11.864			607.2 538.6	
DOWN 1949			52 00 179 42			85.4 1769.1	
Sub Sta.						456.5 688.6	
						1350.6 503.8	
						1039.2 106.5	
						681.2 1173.3	
						336.6 809.1	
						401.3 1453.2	
						226.4 918.7	
						690.7 1163.9	
						82.2 1062.2	

1 FT. = 3048006 METER

COMPUTED BY: C. O. DeMarr

DATE 10 September 1954

CHECKED BY: L. C. Lande

DATE

11 Sept. 1954

M 2388.12

MAP T-8562 PROJECT NO. Ph-34 SCALE OF MAP 1:20,000 SCALE FACTOR

STATION	SOURCE OF INFORMATION (INDEX)	DATUM	LATITUDE OR Y-COORDINATE LONGITUDE OR X-COORDINATE	DISTANCE FROM GRID IN FEET, OR PROJECTION LINE IN METERS		DATUM CORRECTION	N.A. 1927 - DATUM DISTANCE FROM GRID OR PROJECTION LINE IN METERS		FACTOR DISTANCE FROM GRID OR PROJECTION LINE IN METERS
				FORWARD	(BACK)		FORWARD	(BACK)	
✓ PEAK No. 6, 1949	p 6	1927	51-55-49.296 179 30 20.873				1523.6	330.8	
✓ PEAK No. 4, 1949	p 6	"	51 56 08.059 179 35 15.515				249.1	1605.3	
✓ KEM 1949	p 5	"	51 53 45.552 179 31 14.406				296.4	849.9	
✓ KNIFE 1949	p 1	"	51 54 37.499 179 34 47.138				1407.9	446.5	
✓ POCH 1944	p 1	"	51 53 56.689 179 31 15.538				275.5	871.8	
✓ TRICK 1949	p 1	"	51 56 55.652 179 33 40.214				1159.0	695.4	
✓ MUTTON 1949	p 1	"	51 55 53.686 179 29 35.010				901.1	245.9	
✓ LOOK 1949	p 1	"	51 56 30.216 179 28 39.489				1752.1	102.3	
✓ JUMP 1949	p 4	"	51 53 32.778 179 35 17.883				297.1	850.1	
✓ RAD 1949	p 5	"	51 53 17.225 179 35 39.696				1720.0	134.4	
✓ MOS (ROCK) 1949	p 5	"	51 52 47.794 179 35 49.939				768.0	377.9	
✓ PEAK "B" 1949	p 6	"	51 56 01.661 179 30 42.582				1659.3	195.1	
							668.9	477.5	
							933.9	920.5	
							754.3	391.8	
							1013.0	841.3	
							342.0	805.6	
							532.4	1322.0	
							759.1	388.4	
							1477.0	377.3	
							955.2	192.4	
							51.3	1803.1	
							813.6	332.8	

1 FT. = 3048006 METER

COMPUTED BY: C. L. De Marr

DATE 10 September 1954

CHECKED BY: L.C. Lande

DATE

11 September 1954

M-2385-12

PROJECT NO. Ph-34

SCALE OF MAP 1:20,000.....

SCALE FACTOR

[illegible]

NY 100 - 4018008 MEYER

1 FT. = 3048008 MICRONS
COMPUTED BY: C. O. DeMarr

DATE 10 September 1954

CHECKED BY: **L. C. Lande**

DATE 11 September 1954
M-2388-12

M-2388-12

MAP T. 8563 PROJECT NO. Ph-34 SCALE OF MAP 1:20,000 SCALE FACTOR

MAP T. 8563 PROJECT NO. Ph-34 SCALE OF MAP 1:20,000 SCALE FACTOR

MAP T. 8563 PROJECT NO. Ph-34 SCALE OF MAP 1:20,000 SCALE FACTOR

[illegible]

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100	101	102	103	104	105	106	107	108	109	110	111	112	113	114	115	116	117	118	119	120	121	122	123	124	125	126	127	128	129	130	131	132	133	134	135	136	137	138	139	140	141	142	143	144	145	146	147	148	149	150	151	152	153	154	155	156	157	158	159	160	161	162	163	164	165	166	167	168	169	170	171	172	173	174	175	176	177	178	179	180	181	182	183	184	185	186	187	188	189	190	191	192	193	194	195	196	197	198	199	200	201	202	203	204	205	206	207	208	209	210	211	212	213	214	215	216	217	218	219	220	221	222	223	224	225	226	227	228	229	230	231	232	233	234	235	236	237	238	239	240	241	242	243	244	245	246	247	248	249	250	251	252	253	254	255	256	257	258	259	260	261	262	263	264	265	266	267	268	269	270	271	272	273	274	275	276	277	278	279	280	281	282	283	284	285	286	287	288	289	290	291	292	293	294	295	296	297	298	299	300	301	302	303	304	305	306	307	308	309	310	311	312	313	314	315	316	317	318	319	320	321	322	323	324	325	326	327	328	329	330	331	332	333	334	335	336	337	338	339	340	341	342	343	344	345	346	347	348	349	350	351	352	353	354	355	356	357	358	359	360	361	362	363	364	365	366	367	368	369	370	371	372	373	374	375	376	377	378	379	380	381	382	383	384	385	386	387	388	389	390	391	392	393	394	395	396	397	398	399	400	401	402	403	404	405	406	407	408	409	410	411	412	413	414	415	416	417	418	419	420	421	422	423	424	425	426	427	428	429	430	431	432	433	434	435	436	437	438	439	440	441	442	443	444	445	446	447	448	449	450	451	452	453	454	455	456	457	458	459	460	461	462	463	464	465	466
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

1 FT. = 3048006 METERS

COMPUTED BY: C. O. DeMarr	DATE: 10 September 1954
CHECKED BY: L. C. Lande	DATE: 11 September 1954

MAP T-8563 PROJECT NO. Ph-34 SCALE OF MAP 1:20,000 SCALE FACTOR

STATION	SOURCE OF INFORMATION (INDEX)	DATUM	LATITUDE OR y -COORDINATE LONGITUDE OR x -COORDINATE	DISTANCE FROM GRID IN FEET, OR PROJECTION LINE IN METERS FORWARD (BACK)	DATUM CORRECTION	N.A. 1927 - DATUM DISTANCE FROM GRID OR PROJECTION LINE IN METERS FORWARD (BACK)	FACTOR DISTANCE FROM GRID OR PROJECTION LINE IN METERS FORWARD (BACK)
SEMISOPOCHNOI ✓ VOLCANO 1949	p7	1927	51 53 06.522 179 38 06.781			201.6 1652.8 129.8 1017.9	
S. VOLCANO 1949	p6	"	51 53 41.871 179 38 22.559	<i>Revised</i>		1294.1 560.3 1431.5 716.1	
SUGAR ✓ 1949	p4	"	51 52 36.046 179 38 52.970			1114.0 740.3 1013.1 134.4	
N. SPLIT PK. 1949	p6	"	51 55 30.920 179 41 08.297			955.6 898.8 158.6 98.2	
S. SPLIT PK. 1949	p6	"	51 55 25.906 179 41 14.778	<i>Revised</i>		800.7 1053.7 282.1 861.3	
SHACK ✓ 1949	p5	"	51 56 30.885 179 44 00.430			954.3 900.0 8.2 1138.0	
1944 SEMISOPOCHNOI	p1	"	51 53 04.459 179 38 06.721			137.8 1716.6 128.6 1019.0	
TIER ✓ 1949	p3	"	51 56 48.741 179 40 19.867			1506.1 348.0 852.8 193.6	
DROP ✓ 1949	p2	"	51 52 24.070 179 36 55.216			743.9 1110.5 1056.3 91.5	
VIEW ✓ 1949	p3	"	51 56 19.988 179 41 17.968			617.8 1236.6 343.3 803.1	
UPPER ✓ 1949	p3	"	51 56 59.032 179 41 41.714			1824.5 29.9 797.0 349.4	
SEMISOPOCHNOI ✓ E. BASE 1949	p3	"	51 56 12.292 179 43 58.891			379.9 1474.5 1125.1 21.2	

1 FT. = 3048006 METER

COMPUTED BY: C. O. DeMart

DATE 10 September 1954

CHECKED BY: L. C. Lande

DATE 11 Sept. 1954

COMPILATION REPORT

T-8560, T-8561, T-8562, T-8563

31. Delineation

Reading Plotters A and B were used to delineate shoreline features and contours. Compilation directly upon the manuscripts was thought to reduce over-all time and free the draftsmen-compilers. The positive manuscripts, used in the radial plot, were therefore hand-rubbed on the back with an abrasive to produce a grain and details from the negative, nine-lens, rectified prints transferred thereon.

32. Control

Horizontal and vertical control were adequate and, in some areas, abundant.

T-8560 - TUMAN, 1949 (see 23) (See page 8 of Field Inspection Report, 1949). The southwestern end of the top of the peak, instead of the radial plot office's identification at the northeastern end, was held to in compilation.

FLAT PEAK, 1949 could not be held. Compiled position is 2.5mm (500m) westward. The observation from BEACH 1949 probably was on the military crest of the peak and, as the observed position is unchecked, the station was deleted. Elevation retained.

T-8562 - PEAK 6, 1949 (see 23). The southern end of the top of the peak, instead of the radial plot office's identification at the northern end, was held to in compilation.

RAD, 1949 - No tower was visible but the apparent base held the observed position in compilation. The listed elevations of 334 ft. (top) and 264 ft. (ground) could not be held. The 70 ft. tower, noted in description, is probably 20 or 30 ft. and the ground elevation would then be approximately the photogrammetric elevation of 305 ft.

T-8563 - SOUTH VOLCANO, 1949 (see 23) could not be held. Compiled position is 1.7mm (154m) westward. As the observed position is unchecked, the station was deleted. Elevation retained.

SOUTH SPLIT PEAK, 1949 could not be held. Compiled position is 1.35mm (270m) westward. Elevation by vertical angle from UPPER, 1949 is 95 feet too high but elevation obtained from POCHNOI was held. As the observed position is unchecked, the station was deleted.

33. Supplemental Data

C&GS single-lens photos Nos. 52 0 1189 - 1247

34. Contours and Drainage

Clouds and shadows caused considerable difficulty in delineating the contours and drainage. The Zeiss Stereotope was used with the photos listed in paragraph 33 to delineate areas which were covered by clouds on the nine-lens photos. All instrument elevations shown on the manuscript were from the Reading plotters.

35 and 36. Shoreline, Alongshore and Offshore Details

Shoreline inspection was scant but, in conjunction with details visible in the stereo models, was adequate.

37. Landmarks and Aids

Fall on western side of Petrel Point is a landmark described on the appended Form 567 (see Field Inspection Report, page 8). No aids to navigation are known in the area.

38. Control for Future Surveys

Hydrography was completed in 1949 (H-7726, H-7727). No topo stations were established. Hydro signals were located on graphic control sheets in the field.

39. Junctions

All junctions with contemporary surveys were made.

40. Horizontal and Vertical Accuracy

See radial report.

46. Comparison with existing maps

SEMISOPOCHNOI ISLAND, Sheets 1, 2, 3, 4, 1:25,000
20 ft. contour interval.
War Department, Corps of Engineers, U. S. Army, 1943
from T3-A (3-lens) aerial photography of 1934
RAT ISLANDS, 1:250,000, USGS, 1951

47. Comparison with Nautical Charts

8863 1:300,000
8864 1:300,000

"Items to be Applied to Nautical Charts Immediately"
None

"Items to be Carried Forward"
None

Submitted by

Clarence Misfeldt

Approved by

Clarence Misfeldt
Cartographer (Photo.)

Louis Levin
Louis Levin
Supervisory Cartographer
9-Lens Stereo Mapping Unit

GEOGRAPHIC NAMES

Survey No. T-8560

Name on Survey	On Chart No. On previous survey No. On U. S. quadrangle Maps From local information On local Maps P. O. Guide or Map Rand McNally Atlas U. S. Light List										
	A	B	C	D	E	F	G	H	K		
<u>Bering Sea</u>										1	
<u>Tuman Point</u>										2	
										3	
										4	
										5	
										6	
										7	
										8	
										9	
										10	
										11	
										12	
										13	
										14	
										15	
										16	
										17	
										18	
										19	
										20	
										21	
										22	
										23	
										24	
										25	
										26	
										27	

Names approved
3-1-57 L. Heck.

GEOGRAPHIC NAMES

Survey No. T-8561

GEOGRAPHIC NAMES											
Survey No. T-8561											
Name on Survey											
	A	B	C	D	E	F	G	H	K		
Anvil Peak	T-8560										1
Bering Sea											2
Fenner Lake											3
Northeast Point											4
North Head											5
Perret Ridge											6
Petrel Bank											7
Petrel Point											8
Pochnoi Point											9
Lakeshore Cone											10
											11
											12
											13
											14
											15
											16
											17
											18
											19
											20
											21
											22
											23
											24
											25
											26
											27
											28

M 234

GEOGRAPHIC NAMES

Survey No.

T-8562

Name on Survey

	A	B	C	D	E	F	G	H	K	
										1
										2
										3
BERING SEA										4
MOUNT CERBERUS										5
SOUTHWEST KNOB										6
THREEQUARTER CONE										7
										8
										9
										10
										11
										12
										13
										14
										15
										16
										17
										18
										19
										20
										21
										22
										23
										24
										25
										26
										27

Names approved
3-1-57 L. Heck

GEOGRAPHIC NAMES
Survey No. T-8563

GEOGRAPHIC NAMES		Survey No. T-8563									
Name on Survey											
	A	B	C	D	E	F	G	H	K		
Anchitka Pass											1
Fenner Creek											2
Fenner Lake											3
Mount Cerberus											4
Ragged Top											5
Sugarloaf Head											6
Sugarloaf Knob											7
Sugarloaf Peak											8
											9
											10
											11
											12
											13
											14
											15
											16
											17
											18
											19
											20
											21
											22
											23
											24
											25
											26
											27
											28
											29
											30
											31
											32
											33
											34
											35
											36
											37
											38
											39
											40
											41
											42
											43
											44
											45
											46
											47
											48
											49
											50
											51
											52
											53
											54
											55
											56
											57
											58
											59
											60
											61
											62
											63
											64
											65
											66
											67
											68
											69
											70
											71
											72
											73
											74
											75
											76
											77
											78
											79
											80
											81
											82
											83
											84
											85
											86
											87
											88
											89
											90
											91
											92
											93
											94
											95
											96
											97
											98
											99
											100

Names approved

3-1-57. L. Heck

Review Report
Topographic Maps T-8560 thru T-8563
March 1957

62. Comparison with Registered Topographic Surveys

T-6963 1:30,000 1935 (by U. S. Navy)

This survey (with an assumed scale of 1:30,000) compiled by the U. S. Hydrographic Office from 5-lens photography is in good agreement with T-8560 thru T-8563 in shoreline and general expression of relief. The more recent surveys with adequate control and complete detailing are to supercede the above-listed survey for nautical charting purposes.

63. Comparison with Maps of Other Agencies

Semisopochnoi Island Sheets 1, 2, 3 and 4 1:25,000
War Dept., Corps of Engineers, U. S. Army, 1943
Rat Islands, 1:250,000 U.S. Geological Survey, 1951

Except for the lack of detailing of off-shore and fore-shore features and disagreement of others, there is, generally, good agreement in presentation of shoreline and relief. There is also a difference in datum (U. S. Army Quads based on local datum).

64. Comparison with Contemporary Hydrographic Surveys

H-7726 1:20,000 1949
H-7727 1:20,000 1949
H-7650 1:80,000 1949

These hydrographic surveys have not been verified and are without shoreline. Positions of soundings and depth curves will accommodate shoreline of subject topographic surveys well. A few minor differences in position of fore-shore rocks exist, however, the addition of shoreline onto the hydrographic surveys will resolve these minor disagreements.

65. Comparison with Nautical Charts


8863 1:300,000 1951 corrected to 52 1/14
8864 1:300,000 1951 " to 52 9/29

66. Adequacy of Results and Future Surveys


Except for control field inspection was confined to shoreline, and fore-shore and off-shore features. Shoreline inspection, accomplished in 1949 with U. S. Navy


photography of 1935 to approximate scale of 1:30,000, is not complete but appeared adequate. Lack of complete inspection may have resulted in minor errors in office interpretation. Other than there, no deficiencies in accuracy and adequacy were indicated.

Reviewed by:


Joseph C. Streifler

APPROVED:


Chief, Review & Drafting Sec. Chief, Nautical Chart Branch,
Photogrammetry Div. Charts Division


Chief, Photogrammetry Division


Chief, Coastal Surveys

History of Hydrographic Information for T-8560 thru
T-8563

Hydrography was added to the map manuscript in accordance with AMS Technical Instructions.

Depth curves and soundings are in fathoms at mean lower low water and originate with the following unverified Hydrographic Surveys:

7726,	1:20,000,	1949
7727,	1:20,000,	1949
7650,	1:80,000,	1949

Hydrography was compiled in Photogrammetry Review and verified by Nautical Charts in March 1957.

J. J. Streifler

Summary to Accompany Topographic Maps T-8560 thru T-8563

T-8560 thru T-8563 represents a portion of Project 24050 (Ph-6034 - Ph-34). These four surveys cover all of SEMISOPOCHNOI ISLAND, one of the group comprising Rat Islands of the Aleutian Islands.

Subject topographic surveys were shoreline-inspected in 1949 from U. S. Navy Photography of 1935 at approximate scale of 1:30,000, and compiled in the Washington Office in 1957 from 1953 Nine-Lens Photography by the Reading Plotter.

After addition of hydrographic information, the maps will be published by the Army Map Service as standard topographic quadrangles at the scale of 1:25,000 and replace a previous publication of 1943.

A photographic positive copy (CRONAR) at manuscript scale and the Descriptive Report, as well as a cloth-backed lithographic print in colors after final printing by AMS will be registered and filed in the Bureau Archives.