TP-00035(2)

NOAA FORM 76-35

U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SURVEY

DESCRIPTIVE REPORT

Type of Survey CHART TOPOGRAPHY
Job No. CM-7408 Map No. TP-00035(2)
Classification No.: Final. Edition No. Second
LOCALITY
State
Snake River, Lower Granite General Locality Dam and Reservoir
Locality Lower Granite Dam
Locally
19 74 TO 1977
REGISTRY IN ARCHIVES
DATE :
DATE

☆ U.S. GOVERNMENT PRINTING OFFICE: 1974-762-901

NOAA FORM 76-36A U. S. DEPARTMENT OF COMMERCE (3-72) NATIONAL OCEANIC AND ATMOSPHERIC ADMIN.	TYPE OF SURVEY SURVEY	TP- 00035(2)
ALL SOLING AND ATMOSPHERIC ADMIN.	ORIGINAL MAPEDIT	TON NO. (2)
		10N NO. (2)
DESCRIPTIVE REPORT - DATA RECORD		ss Final
	A REVISED (partial) JOB	PHCM-7408
PHOTOGRAMMETRIC OFFICE	LAST PRECEEDING MAP ED	ITION
	TYPE OF SURVEY JOB	PH- 7001
Coastal Mapping Division, Norfolk, VA	ORIGINAL MAPCLA	ss <u>Final</u>
	RESURVEY SURVEY	
Jeffrey G. Carlen	REVISED 19_690	19_70
I. INSTRUCTIONS DATED		
1. OFFICE	2. FIELD	
Aerotriangulation 9/23/74	June 5, 1974	
Pirls Black Data		
Compilation 1/23/75		
II. DATUMS		
1. HORIZONTAL: X 1927 NORTH AMERICAN	OTHER (Specify)	
I HOMEZON AL.	National Geodetic Vertica	Datum 1929
MEAN HIGH-WATER	OTHER (Specity)	
2. VERTICAL: MEAN LOW-WATER MEAN LOWER LOW-WATER		
MEAN SEA LEVEL		
3. MAP PROJECTION	4. GRID(S)	
38'00"	STATE ZONE	
Mercator central Paralle: 46025130"	Washington	outh
5. SCALE	STATE ZONE	
1:10,000 at central parallel III. HISTORY OF OFFICE OPERATIONS	Military and the second second	
OPERATIONS		
1. AEROTRIANGULATION BY	M. McGinley	1/31/75
METHOD: Wild STK-1 LANDMARKS AND AIDS BY	M. McGinley	1/31/75
2. CONTROL AND BRIDGE POINTS PLOTTED BY	R. Robertson	1/24/75
METHOD: Calcomp CHECKED BY	R. Robertson	1/24/75
3. STEREOSCOPIC INSTRUMENT PLANIMETRY BY	L. O. Neterer, Jr.	Sept 1976
COMPILATION CHECKED BY	J. Byrd	Sept 1976
INSTRUMENT: Wild B-8 CONFURS BY SCALE: 1:5,000 CHECKED BY	L. O. Neterer, Jr.	Sept 1976
4. MANUSCRIPT DELINEATION PLANIMETRY BY	J. Byrd D. Butler	Sept 1976 Oct 1976
CHECKED BY	J. Byrd	Dec 1976
CONTOURS BY	D. Butler	Oct 1976
METHOD: Smoothdrafted CHECKED BY	J. Byrd	12/6/76
scale: 1:10,000 at HYDRO SUPPORT DATA BY	NA	
central parallel CHECKED BY	NA .	
5. OFFICE INSPECTION PRIOR TO FIELD EDIT BY	J. Byrd	12/6/76
6. APPLICATION OF FIELD EDIT DATA	D. Butler F. Margiotta	Nov 1977 Jan 1978
7. COMPILATION SECTION REVIEW BY	F. Margiotta	Jan 1978 Jan 1978
8. FINAL REVIEW BY	A. L. Shands	Apr 1979
9. DATA FORWARDED TO PHOTOGRAMMETRIC BRANCH BY	A. L. Shands	Jul 1979
10. DATA EXAMINED IN PHOTOGRAMMETRIC BRANCH BY	E. L. Rolle	July 1979
11. MAP REGISTERED - COASTAL SURVEY SECTION BY	F. L. DAUGHERTY	DEC 1979
NOAA FORM 76-36 A SUPERSEDES FORM C&GS 181 SERIES	# U.S. G.P.O. 1972-76	

NO.	AA	FORM	76-36B

U. S. DEPARTMENT OF COMMERCE NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION NATIONAL OCEAN SURVEY

. COMPILATION PHOTO	DGRAPHY		1 15			The street of		
CAMERA(S)			TYPE	S OF PHOTOGRAPHY	1.3	TIME DE	EEDENCE	
Wild RC-8 "		J''		LEGEND		TIME REFERENCE		
TIDE STAGE REFERENCE		N.A.	(C) COLOR			ZONE		XSTANDARD
REFERENCE STATION	N RECORDS	N.A.	(P) <u>PA</u>	NCHROMATIC	MEE	Pacific	AST	ANDAR
TIDE CONTROLLED F	PHOTOGRAPHY	N.A.	(I) INF	FRARED		120th		YLIGH
NUMBER AND TY	YPE	DATE	TIME	E SCALE			OF TIDE	
747(0) 5760 5	57/0	6/10/7/	07.0					
74E(C) 5762 - 5		6/13/74 4/21/75	07:2	THE RESERVE OF THE PARTY OF THE		OTT. TIL		
*W 76-6 (P) 59			44.0	1:12,0		OTE: Tid pplicable	es are r	No. of Street
*W 75 3(P) 14-1	16	2/15/75	11:3	1:12,0		roject.	LO LIIIS	
REMARKS								
* Used only	y for gra	ohic	PACOTES.	at Engineers	Phytog	raphy - 1		
delineat: 2. SOURCE OF MEAN HE	ion of fi	eld edit it	ems. C.	irps of Engine	ers phi	oto 8 to phy		
The sourc	ce of the :10,000 sc	pool shore	line (e ation p	levation 738 :	ft.) is	the abov	e	
The sourc listed 1:	ce of the :10,000 sc	pool shore ale compila	line (e	levation 738 :	ft.) is	the abov	e	
listed 1:	:10,000 sc	ale compila	ation p	hotography.	Et.) is	the abov	e	
listed 1:	:10,000 sc	ale compila	ation p	hotography.	Et.) is	the abov	e	
listed 1: 3. SOURCE OF MEAN LO Not appli	DW-WATER OR	MEAN LOWER LO	OW-WATER I	hotography.)
listed 1: 3. SOURCE OF MEAN LO Not appli	DW-WATER OR	MEAN LOWER LO	OW-WATER I	hotography.		rammetric surve		
listed 1: 3. SOURCE OF MEAN LO Not appli 4. CONTEMPORARY HYD SURVEY NUMBER DA	DW-WATER OR icable to	MEAN LOWER LO	OW-WATER I	hotography.	for photog:	rammetric surve	oy information RVEY COPY 2-0034	
listed 1: 3. SOURCE OF MEAN LO Not appli SURVEY NUMBER DA SURVEY NUMBER DA SORTH	DW-WATER OR icable to	MEAN LOWER LO	OW-WATER I	hotography.	for photog:	rammetric surve	ey information	USED
listed 1: 3. SOURCE OF MEAN LO Not appli 4. CONTEMPORARY HYD SURVEY NUMBER DA 5. FINAL JUNCTIONS NORTH No Survey	DW-WATER OR icable to DROGRAPHIC S	MEAN LOWER LO	OW-WATER I	hotography. LINE: Irveys that are sources SURVEY NUMBER	for photog:	rammetric surve	ey information	USED
Not appli CONTEMPORARY HYD CURVEY NUMBER C. FINAL JUNCTIONS CORTH No Survey	DW-WATER OR icable to DROGRAPHIC S	wean Lower List on Survey Cop	OW-WATER I	hotography. LINE: SURVEY NUMBER SOUTH	for photog: DATE(S	rammetric surve	oy information RVEY COPY 2-0034 1-7001 PH-7001	USED

(3-72)

(3-72)		TP-00035	(2)	NIC AND ATMOSPHER	MENT OF COMMERCE RIC ADMINISTRATION NAL OCEAN SURVEY
I W CIE D DESE		HISTORY OF FIELD			
I. X FIELD INSPE		ERATION	EDIT OPERATION		DATE
					22.5
1. CHIEF OF FIELD	PARTY		R. B. 1	Melby	Sept-Dec174
		RECOVERED BY	<u>None</u>		
2. HORIZONTAL CO	NTROL	ESTABLISHED BY	None		-
		PRE-MARKED OR IDENTIFIED BY	None	Ma 11	Sept-Dec 174
3. VERTICAL CONT	'BOI	RECOVERED BY	R. B.		Sept-Dec '74
3. VERTICAL CONT	NOL	PRE-MARKED OR IDENTIFIED BY	R. B.		Sept-Dec '74
			R. B. None	me_rby	Bept-Dec 74
4. LANDMARKS AND		ECOVERED (Triangulation Stations) BY	None		<u> </u>
AIDS TO NAVIGA		LOCATED (Field Methods) BY	None	· · · · · · · · · · · · · · · · · · ·	-
		TYPE OF INVESTIGATION	None		
5. GEOGRAPHIC NA	MFS	X COMPLETE	ļ		
INVESTIGATION		SPECIFIC NAMES ONLY			
		NO INVESTIGATION	R. B.	Me1by	Sept-Dec'74
6. PHOTO INSPECT	ION	CLARIFICATION OF DETAILS BY	None		
7. BOUNDARIES AN		SURVEYED OR IDENTIFIED BY	NA		
II. SOURCE DATA					<u> </u>
1. HORIZONTAL CO	NTROL IDE	NTIFIED	2. VERTICAL CON	TROL IDENTIFIED	
None			<u> </u>		
PHOTO NUMBER		STATION NAME	PHOTO NUMBER	STATION DI	ESIGNATION
			74E(C)5761	V-27-04	
			74E(C)5762		
			74E(C)5762	V-27-02	
			74E(C)5763	V-27-01	
			142(0)3703		
3. PHOTO NUMBERS	5 (Clarificat	ion of details)			
None					
	AIDS TO N	AVIGATION IDENTIFIED			
None					
PHOTO NUMBER		OBJECT NAME	PHOTO NUMBER	OBJEC.	T NAME
			1 1		
			j J		
5. GEOGRAPHIC NA	MES:	X REPORT NONE	6. BOUNDARY AN	D LIMITS: REP	ORT MONE
7. SUPPLEMENTAL	MAPS AND	PLANS			
None					
	ECORDS (Sk	etch books, etc. DO NOT list data submit	ted to the Geodesy D	ivision)	
	,			•	
None					
					ĺ
			_		ļ


NOAA FORM 76-36C (3-72)	TP_00035(AND ATMOSPHERIC	INT OF COMMERCE C ADMINISTRATION AL OCEAN SURVEY
	TP-00035(HISTORY OF FIELD	ÓPERATIONS		
I. TIELD INSPECTION	DPERATION X FIEL	D EDIT OPERATION		
	OPERATION	NAM	WE	DATE
I. CHIEF OF FIELD PART	Y	R. Melby		Sept 1977
	RECOVERED BY	None		Sept 197
2. HORIZONTAL CONTROL		None	· 	
	PRE-MARKED OR IDENTIFIED BY	None		
	RECOVERED BY	None		
3, VERTICAL CONTROL	ESTABLISHED BY	None _		
	PRE-MARKED OR IDENTIFIED BY	None		
	RECOVERED (Triangulation Stations) BY	None		
4. LANDMARKS AND	LOCATED (Field Methods) BY	None		
AIDS TO NAVIGATION	IDENTIFIED BY	None		
	TYPE OF INVESTIGATION			
5. GEOGRAPHIC NAMES	COMPLETE BY			
INVESTIGATION	SPECIFIC NAMES ONLY			1
	NO INVESTIGATION			
6. PHOTO INSPECTION	CLARIFICATION OF DETAILS BY	R. Melby		Sept 197
7. BOUNDARIES AND LIMIT	SURVEYED OR IDENTIFIED BY	None		
II. SOURCE DATA		IA WERTICK CONTE	201 10511715150	
1. HORIZONTAL CONTROL	DENTIFIED	2. VERTICAL CONTE	ROL IDENTIFIED	
None	· · · · · · · · · · · · · · · · · · ·	None	<u> </u>	
PHOTO NUMBER	STATION NAME	PHOTO NUMBER	STATION DES	GNATION
3. PHOTO NUMBERS (Clari	·			
$W75-6(P)\sim59$ and				
4. LANDMARKS AND AIDS	TO NAVIGATION IDENTIFIED			
37				•
None		T		
PHOTO NUMBER	OBJECT NAME	PHOTO NUMBER	OBJECT	NAME
		1		
•	•]		
				
5. GEOGRAPHIC NAMES:	REPORT X NONE	6. BOUNDARY AND L	IMITS: E REPO	RT I NONE
7. SUPPLEMENTAL MAPS	AND PLANS	- .		
None				
8. OTHER FIELD RECORDS	5 (Sketch books, etc. DO NOT list data submi	tted to the Geodesy Divid	eion)	
1 field edit	ozalid			
1 field_edit	report	i 1		

5

NOAA FORM 76-36D (3-72) U. S. DEPARTMENT OF COMMERCE NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION

RECORD OF SURVEY USE

I. MANUSC	RIPT COPIES	SCHOOL ACCES							
	со	MPILATIO	N STAGES				DATE MAN	USCRI	PT FORWARDED
	DATA COMPILED	DA	TE	RE	MARKS		MARINE CH	ARTS	HYDRO SUPPORT
	ation complete g field edit	Oct 1	.976	Class II	I Manusc	ript	4/4/77	7	Field Edit 8/4/77
	edit applied. ation complete.	Nov 1	1977	Class I	Manuscri	pt	2/2/7	8	
Final	Review	Apr	1979	Fir	nal		Jul 1	979	
II. LANDM	ARKS AND AIDS TO NAVIGA	TION N	None						
1. REP	ORTS TO MARINE CHART D	VISION, N	AUTICAL	DATA BRANCH					
NUMBER	CHART LETTER NUMBER ASSIGNED	FORWA				REMA	ARKS		
3. 🔲	REPORT TO MARINE CHART REPORT TO AERONAUTICA RAL RECORDS CENTER DAT	L CHART						DED:	
2 3	BRIDGING PHOTOGRAPHS; CONTROL STATION IDENTI SOURCE DATA (except for G ACCOUNT FOR EXCEPTION DATA TO FEDERAL RECOR	FICATION eographic i	CARDS; Names Rep		567 SUBMIT	TED BY		TIES.	
IV. SURVE	Y EDITIONS (This section s				edition is re				
SECOND	TP-00035	(2)	CM-7	7408				RES	URVEY
EDITION	6/13/74 2/15/75 4/2	1/75	9/7		□n.	□m.	MAPCLAS	s Jv.	VIINAL
THIRD	TPDATE OF PHOTOGRAPH	(3) P	H				YPE OF SUR	RES	URVEY
	SURVEY NUMBER				□n.		□iv. [Jv.	FINAL
FOURTH	TP	_ (4) P	H -				YPE OF SUR	RESC	DRVÉY
EDITION	DATE OF PHOTOGRAPH	TY DA	TE OF FIE	LD EDIT	□n.	□	MAP CLAS		DFINAL



SUMMARY TO ACCOMPANY MAPS TP-00035(2) AND TP-00827 THROUGH TP-00835

This summary covers all of Project CM-7408 which consist of ten chart topography maps. They cover the area of the Lower Granite Dam Reservior from the Lower Granite Dam southeastward to the town of Lewiston, Idaho, and from there south to just below Asotin, Washington. The area of the reservoir is bounded by a steep walled basaltic canyon, except at the southern end.

Maps in this project are to serve as the basis for construction of a small craft chart of the area. The maps are all ruled on the Mercator projection system. Maps TP-00827 through TP-00835 have lat. 46°25'30" as the central parallel and Map TP-00035(2) has lat. 46°38'00" as its central parallel. As can be expected, there is a significant difference in the scales of Maps TP-00035(2) and TP-00827, which joins it. See diagram, page 5 of this Descriptive Report.

Map TP-00035 (2) was added to this project just prior to the bridging function. All bridging was done at the Washington Science Center using the STK-1.

The photographs used for compilation were flown on three separate occasions. The first was taken with color film by the National Ocean Survey in June, 1974. This was followed with two sets taken by the Corp of Engineers using black and white film in February, 1975 and April, 1975. The April photographs were flown after the reservoir was flooded.

A bridge was run only on the color photography. Control for setting models of the black and white photography was obtained by identifying points common to that photography from the B-8 models of the color photographs.

All maps were compiled at the Atlantic Marine Center using the B-8 stereoplotter and graphic methods. The B-8 stereoplotter was used to obtain all elevations and contours, as well as the bulk of the planimetric features. Some map features, recommeded for charting by the field editor, were identified on the 1975 U.S. Corps of Engineers photography. These features were applied to the map bases using graphic methods. In areas where control was sparse, the field edited map features were labeled (PA) for position approximate. Field edit was done in the Fall of 1977. All field edit items were applied to the maps at the Atlantic Marine Center.

All maps were final reviewed at the Atlantic Marine Center during the Spring of 1979. The original base maps and all applicable data was forwarded to the Washington Science Center for reproduction and final registration.

FIELD INSPECTION REPORT

Project CM-7408

Map Manuscripts T-00827 through TP-00835

September - December 1974

FIELD INSPECTION REPORT

Project CM-7408.

Map Manuscripts T-00827 through TP-00835

September - December 1974

General

The area contained in this report commences at the vicinity of the Lower Granite Dam, on the Snake River and upstream along the Snake River to the vicinity of the town of Asotin, and upstream along the Clearwater River, from its confluence with the Snake River to a point about 5 miles upstream.

Except in the area of the cities of Lewiston and Clarkston, the rivers flow through steep walled, basaltic canyons.

The Camas Prairie Railroad serves the area along the Snake River from the Lower Granite Dam to the city of Lewiston, Idaho, then along the south shore of the Clearwater River. There is little industry along the rivers, except in the Lewiston-Clarkston area.

Horizontal Control

- 1. Four supplemental control stations were established by the field party.
- 2. All horizontal control stations required by the Project Instructions for aero-triangulation were recovered and paneled for aerial photography. Control Station Identification Form 152 were submitted to the Rockville, Maryland, office on June 19, 1974.

Vertical Control

All bench marks necessary to establish the required photo-elevation points were recovered and NOAA Form 76-89 will be submitted for each mark searched for.

Critical Features

The pool area was inspected for critical features and possible obstructions to navigation. At the time the field party was determining the photo elevations, Corps of Engineers contractors were removing possible rocks, knobs, etc., and "dressing"slopes. Dredging and quarrying were in progress in the bottom of the Clearwater River on the downstream side of the Lewiston-North Lewiston Highway Bridge (see photo 74E 5921). Shoreline changes were in progress from Clarkston to Asotin on the Snake River, also between Clarkston and the mouth of Alpowa Creek. The Corps of Engineers, Walla Walla

District should be consulted as to the extent and profiling of the changes. Two contractors bridges, one upstream of the Lower Granite Dam and one downstream of the railroad bridge over the Clearwater River, were being removed. A highway bridge over the Snake River is under construction (see photo 74E 5877).

Leveling

The elevations of the preselected photo-elevation points were determined by trigonometric leveling, utilizing the Wild T-1 and T-2 theodolites. Where the terrain or distances involved were not conducive to trigleveling with the theodolite and stadio rod, the distances were measured with a RANGER III, Laser, distance measuring instrument. Two distances to each vertical point were observed, and non-reciprocal vertical angles were measured with a Wild T-2 theodolite, 2 D/R with a 10-second rejection limit. The distances were recorded in the field record book in meters to 3 decimal places. Pressure altitude, temperature, instrument and mirror constants were dialed into the RANGER III's system. This, in effect, is a closed loop observation, but the foresights and backsights were unbalanced. Therefore, Form 29D, Computations of Elevations for Non-Reciprocal Observations, was used; the difference in elevations of the long lines and the RANGER III distances were treated as two foresights.

The use of the RANGER III allowed the packing unit to carry only a retrodirective prism, a radio, telescoping tripod, photos, etc., as most of the photo-elevation points were on the near vertical slopes of the canyon walls, requiring back-packing up the steep slopes and bluffs to reach the preselected points. Otherwise, it would have required backpacking a tellurometer unit. The backpacking was a rigorous experience, but only the time factor in climbing slowed the field progress. The weather was favorable, the majority of the time cool and clear.

Bottom Characteristics

Bottom characteristics were indicated on the field photographs. Most of the river bottom is either rocky or boulder/stone/gravel sediments.

Photography

The photographs furnished the field unit were of good quality as to resolution and contrast.

Geographic Names

Geographic names will be the subject of a separate report.

Field Edit

Field edit will be the subject of a separate report at a later date, after the field edit has been accomplished.

Aids to Navigation

At the time the photo party was determining the photo-vertical points, employees of the Coast Guard were observed erecting the pedestals and towers for fixed aids to navigation. None of the images of the aids appear on the existing field photography.

RECOMMENDATIONS

It is recommended during the 1975 field season that the pool area be rephotographed to correct the shoreline changes and to permit the location of the aids to navigation by photogrammetric methods if so desired.

Respectfully submitted,

Rold B. Melly 1/9/75

Robert B. Melby, CPM103

cc: CPM1

PHOTOGRAMMETRIC PLOT REPORT

Job CM-7408

Snake River

Lower Granite Pool

Washington-Idaho

January 1975

21. Area Covered

This project covers the Snake River from Lower Granite Dam to just south of Asotin, Idaho, and a portion of the Clearwater River to just east of Lewiston, Idaho. Included are ten T-sheets (TP-00827 thru TP-00835 and TP-00035). T-sheet TP-00035 was generated at the request of the Rockville Review Section.

Sheets TP-00827 thru TP-00835 were plotted with 1:10,000-scale Mercator projections - central parallel 46°25'30"N. Sheet TP-00035 was plotted with 1:10,000-scale Mercator projections-central parallel 46°38'00"N. All sheets have the Washington State Grid (south zone) intersections plotted at 5,000-foot intervals. Sheets TP-00832 thru TP-00835 also have the Idaho State Grid (west zone) intersections plotted at 5,000-foot intervals.

22. Method

A total of twenty-one strips of color photography were bridged on the Wild STK-1 in order to obtain pass-point positions and elevations to be used during compilation. Three strips of 1:30,000-scale photography (strips 1,2, and 3) were bridged in order to obtain horizontal tie point positions for use in adjusting the other eighteen strips of 1:10,000-scale photography (strips 4 thru 21).

Strip 1 was adjusted on five field-identified triangulation stations and sixteen vertical points with six horizontal tie points and eight vertical points as checks. Strip 2 was adjusted on four field-identified triangulation stations and ten vertical points with one additional triangulation station and eight horizontal tie points as checks. Strip 3 was adjusted on three field-identified triangulation stations and seven vertical points with seven horizontal tie points as checks. Strip 4 was adjusted on four horizontal tie points and eight field-identified vertical points with four horizontal and one vertical tie point as checks. Strip 5 was adjusted on three horizontal tie points and eight field-identified vertical points with seven horizontal and four vertical tie points as checks. Strip 6 was adjusted on four horizontal tie points and twelve field-identified vertical points with eleven horizontal and six vertical points as checks. Strip 7 was adjusted on four horizontal tie points and hine fieldidentified vertical points with twelve horizontal and six vertical tie points as checks. Strip 8 was adjusted on five horizontal

tie points and eight field-identified vertical points with ten horizontal and five vertical tie points as checks. Strip 9 was adjusted on four horizontal tie points and ten field-identified vertical points with eleven horizontal and five vertical tie points as checks. Strip 10 was adjusted on three horizontal tie points and seven field-identified vertical points with nine horizontal and four vertical tie points as checks. Strip 11 was adjusted on five horizontal tie points and six field-identified vertical points with seven horizontal and three vertical tie points as checks. Strip 12 was adjusted on three horizontal tie points; six field-identified vertical points; and one vertical tie point with one additional field-identified vertical point; nine horizontal and five vertical tie points as checks. Strip 13 was adjusted on one field-identified triangulation station; five horizontal tie points; and nine field-identified vertical points with three additional field-identified vertical points; nine horizontal and three vertical tie points as checks. Strip 14 was adjusted on one field-identified triangulation station; three horizontal tie points; seven field-identified vertical points; and one vertical tie point with twelve horizontal and six vertical tie points as checks. Strip 15 was adjusted on seven horizontal tie points; seven field-identified vertical points; and one vertical tie point with eight horizontal and seven vertical tie points as checks. Strip 16 was adjusted on three horizontal tie points and eight field-identified vertical points with one additional field-identified triangulation station; twelve horizontal and eight vertical tie points as checks. Strip 17 was adjusted on three horizontal tie points; seven field-identified vertical points; and one vertical tie point with eight horizontal tie points; one additional field-identified vertical point; and four vertical tie points as checks. Strip 18 was adjusted on three horizontal tie points and seven field-identified vertical points with five horizontal and two vertical tie points as checks. Strip 19 was adjusted on five horizontal tie points and ten field-identified vertical points with eight horizontal tie points; one additional field-identified vertical point; and three vertical tie points as checks. Strip 20 was adjusted on three horizontal tie points and six field-identified vertical points with seven horizontal tie points; two additional field-identified vertical points; and four vertical tie points as checks. Strip 21 was adjusted on three horizontal tie points and eight field-identified vertical points with five horizontal and two vertical tie points as checks.

All adjustments were performed on the IBM 6600. All sheets were ruled and plotted on the Calcomp.

23. Adequacy of Control

All horizontal and vertical control utilized in the adjustments held within National Map Accuracy.

24. Supplemental Data

Vertical control for bridging the three 1:30,000-scale strips only was obtained from local USGS quadrangles.

25. Photography


Photography was adequate as to overlap, definition, and coverage.

Submitted by:


Michael L. McGinley


Approved by:

John D. Perrow, Jr. Chief, Aerotriangulation Section



JOB CM-7408 SNAKE RIVER WASHINGTON - IDAHO





NDAA FORM 76-41 (6-75)		DESCRIPTIV	DESCRIPTIVE REPORT CONTROL RECORD		U.S. DEPARTMENT OF COMMERCE NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION	
MAP NO. TP-00035(2)	JOB NO. CM-7408	8	GEODETIC DATUM NA 1927	Costal, Mapping [II Division, AMC	
STATION NAME	SOURCE OF FORMATION (Index)	AEROTRI- ANGULATION POINT NUMBER	coordinates in Feet STATE Washington ZONE South	GEOGRAPHIC POSITION \$\phi LATITUDE\$ \$\lambda LONGITUDE\$	REMARKS	
	GP vol 1 pg. 1116 zone 2 n225		2,760,290.49			
ALMOIA, 1945	BK 905 56825		514,006.72	~ +		
			y= y=	φ		
			χ=	Ф		
			y=	γ		
,	,		-χ	-0-		
,			y=	γ		
2			<i>-</i> χ	•		
			<i>y=</i>	γ		
			=χ	Ð		
			<i>y=</i>	γ		
			=X	•		
			y=	γ		
			χ=	-6-		
			ηπ	γ		
			χ.,	ф		
			y=	γ		
			=X	ф		
				۲		
compured By J. Roderick		DATE 10/18/76	ED BY F. P	. Margiotta	DATE 10/18/76	
LISTED BY		DATE	LISTING CHECKED BY		DATE	
HAND PLOTTING BY		DATE	HAND PLOTTING CHECKED BY		DATE	
		SUPERSEDES N	SUPERSEDES NOAA FORM 76-41, 2-71 EDITION WHICH IS OBSOLETE.	H IS OBSOLETE.		
			-			

COMPILATION REPORT

TP-00035(2)

31. DELINEATION:

Delineation was done from two sets of photographs. The first set was flown in June, 1974 with color film. It was bridged by the Rockville Office. The second set was flown by the Corps of Engineers in February, 1975 using black and white film. No bridge was run on it.

Control for the second set of photographs was established in the B-8 models of the first set. Details which had been altered by construction since the first photography were revised.

32. CONTROL

See the Photogrammetric Plot Report dated Jan. 31, 1975, and the Field Inspection Report dated Sept. - Dec., 1974, for horizontal and vertical control.

33. SUPPLEMENTAL DATA

None.

34. CONTOURS AND DRAINAGE

Contours at 3, 6, and 10ft. intervals decreasing from the 738 ft. pool line, and drainage was delineated of the photographs. See Compilation Instructions dated Jan. 23, 1975, item 9. 04. 1 Contours (Depth Curves)

35. SHORELINE AND ALONGSHORE DETAILS

The pool line at 738 ft. (NGVD) and details alongshore were delineated by office interpretation of the photographs.

36. OFFSHORE DETAILS

Critical features, such as rocks, boulders, knobs, and hilltops, thought to be possible dangers to navigation were compiled by office interpretation and referred to the field editor for verification.

TP-00035

37. LANDMARKS AND AIDS

None.

38. CONTROL FOR FUTURE SURVEYS

None.

39. JUNCTIONS

See the Form 76-36b, item #5 concerning junctions.

40. HORIZONTAL AND VERTICAL ACCURACY

Refer to the Photogrammetric Plot Report, dated Jan., 1975 for horizontal accuracy. Vertical control established by field methods and the subsequent bridging vertical control were adequate for the model leveling process.

46. COMPARISON WITH EXISTING MAPS

A comparison was made with U.S. Geological Survey Quadrangle Map Almota, Washington, scale 1:24,000, dated 1964.

47. COMPARISON WITH NAUTICAL CHARTS

Comparison was made with chart No. 18547, scale 1:20,000, 3rd edition, dated May 8, 1976.

The Lower Granite Lock and Dam is now compiled as structurally complete, but the area impounded immediately above the dam has been flooded to the 738 ft. level and is substantually changed from that of the chart.

TP-00035

ITEMS TO BE APPLIED TO NAUTICAL CHARTS IMMEDIATELY

None.

ITEMS TO BE CARRIED FORWARD

None.

Submitted by:

David P. Butler

Cartographic Technician Date: Oct. 20, 1976

Approved:

Albert C. Rauck. Jr.
Albert C. Rauck, Jr.

Chief, Coastal Mapping Section

April 30, 1979

GEOGRAPHIC NAMES

FINAL NAME SHEET

CM-7408 (Snake River, Lower Granite Dam, Washington, Idaho)

TP-00035 (2)

Camas Prairie (RR)

Lower Granite Dam

Lower Granite Lake

Offield Landing

Snake River

Approved by:

Chas. E. Harrington Chief Geographer - C3x5

NOAA FORM 75-74 (7-75)				U.S. DEPARTMENT OF COMMERCE
	PHO		RIC OFFICE REVIEW 0 = 00035(2)	NATIONAL OCEAN SURVEY
1. PROJECTION AND GRIDS	2. TITLE		3. MANUSCRIPT NUMBERS	4. MANUSCRIPT SIZE
				1 11/11/07/01/11
JLB	FM		FM	FM
CONTROL STATIONS				
5. HORIZONTAL CONTROL ST THIRD-ORDER OR HIGHER	ATIONS OF ACCURACY	6. RECOVER AS OF LESS TH (Topographic	BLE HORIZONTAL STATIONS AN THIRD-ORDER ACCURACY cetations)	7. PHOTO HYDRO STATIONS
ILB 8. BENCH MARKS	9. PLOTTING	OF SEVEANT	NA 10. PHOTOGRAMMETRIC	NA 11. DETAIL POINTS
G BENCH MARKS	FIXES	OF SEXTAIN	PLOT REPORT	THE DETAIL POINTS
NA	NA	\	JLB	JLB
ALONGSHORE AREAS (Nautica			1 * 4	
12. SHORELINE	13. LOW-WATE	RLINE	14. ROCKS, SHOALS, ETC.	15, BRIDGES
JLB	N7.		JLB	JLB
16. AIDS TO NAVIGATION	17. LANDMARI	<u> </u>	18. OTHER ALONGSHORE PHYSICAL FEATURES	19. OTHER ALONGSHORE CULTURAL FEATURES
			PHYSICAL FEATURES	CULTURAL FEATURES
льв	JLB		JLB	JLB
PHYSICAL FEATURES 20. WATER FEATURES		21. NATHRAL	GROUND COVER	22. PLANETABLE CONTOURS
201 WATER FEATORES		211 NATORAL	GROUND COVER	22. PLANE ABLE CONTOURS
JLB			NA	NA
23. STEREOSCOPIC INSTRUMENT CONTOURS	24. CONTOUR	S IN GENERAL	25. SPOT ELEVATIONS	26, OTHER PHYSICAL FEATURES
TI D	JLI	2	JLB	JLB
JLB CULTURAL FEATURES	1 7 7 11		J JBD	1 010
27. ROADS	28. BUILDING	S	29. RAILROADS	30. OTHER CULTURAL FEATURES
JLB	JLB		JLB	JLB
BOUNDARIES			1.00	
31. BOUNDARY LINES	mits of Pho vision Lim	otography	32, PUBLIC LAND LINES	NA
	Vision Lim	ıcs		INA
MISCELLANEOUS 33. GEOGRAPHIC NAMES		34. JUNCTION		35. LEGIBILITY OF THE
		<u> </u>	See Addn. to Comp.	MANUSCRIPT
j1b		Report an	d Plot Report	JLB
36. DISCREPANCY OVERLAY	37. DESCRIPT	IVE REPORT	38. FIELD INSPECTION PHOTOGRAPHS	39, FORMS
JLB	JLB		JВ	JLB
40, REVIEWER But			SUPERVISOR, REVIEW SECTION	
M. P. J.		12/6/76	Albert C. Rauck	
Jim Byrd 41. REMARKS (See attached she		12/0//0	1 Mibere of Rauek	, -
FIELD COMPLETION ADDITION		TIONS TO THE M	IANUSCRIPT	
	s fumished by th	ne field complet		to the manuscript. The manu-
··	D Butler		SUPERVISOR C. O	Daugh O.
7. Marguel			1 22-	
Reviewer F. Mankiot 43. REMARKS	ta	11/11/78	Albert C. Rauck	, Jr.
Sec Form 76-3	16C, items	#3 and #8.		
				•

FIELD EDIT REPORT

Project CM-7408

Lower Granite Reservoir, Snake River Idaho, Washington

September 1977

2. Areal Field Inspection:

The project area is a section of the Snake River that is impounded by the Lower Granite Dam, forming a navigable pool and the lands adjacent to the pool.

The river passes through a steep canyon with numerous basaltic bluffs. The tops of the bluffs give way to open, rolling prairies which in a large part are cultivated grain fields.

Except for the area near the mouth of the Clearwater River where the cities of Lewiston, Idaho and Clarkston, Washington are located the area is sparsely populated.

The area is traversed by a line of the Camas Prairie Railroad, along the north and east shore of the Snake River and the Clearwater River. Two highway bridges and one railroad bridge are found in the area. One highway bridge in the vicinity of Clarkston, Washington is under construction.

Horizontal Control:

Horizontal control requirements consisted on paneling of preselected triangulation stations, necessary for aerial photography. The panels were the conventional, white opaque polyethylene material, cut to conform to the specifications for the premarking of control stations. All of the stations paneled were bureau triangulation stations. The establishment of new norizontal control stations was not required for photohorizontal control.

Form 152, Control Station Identification cards were submitted for each station paneled. All of the paneled stations were in open areas and no difficulty should be encountered due to trees or shadows.

4. <u>Vertical Control</u>:

Vertical control consisted of the determination by the usual field methods of the elevations of preselected, photogrammetric vertical control points. These points are indicated on the field photographs with the prefix "V" and a numbering system utilizing the last two digits of the numbered "TP" sheet (quadrangle) and consecutive numbers. A sketch of the feature appears on the reverse side of the photograph.

All leveling was based on bench marks established by the Coast and Geodetic Survey and the Corps of Engineers.

5. Contours and Drainage:

Contours only applicable for the office compilation of depth curves for underwater topography, based on the field determination of preselected photogrammetric vertical control points are required for the project.

7. Alongshore Features:

Alongshore features in the form of small boat launching ramps, floats, piers, bridges, pumping stations and power transmission lines have been indicated on the field photography.

8. Offshore Features:

Several features in the form of rocks were found along the shoreline. They have been indicated on the field photography. Several concrete bridge piers are found in the channel of the Snake River, near the mouth of the Clearwater River. The piers have been in place for four years and no progress on the bridge construction is evident, although local sources indicate the bridge construction may begin in the near future.

9. Landmarks and Aids to Navigation:

All aids to navigation were located by the field party. The majority of the fixed aids to navigation were photo-identified on the prints furnished by the U.S. Corps of Engineers. Several of the fixed aids to navigation were determined by ground survey methods.

三直要说话,这个人会被""。

Several landmarks for charts were located by the field party either by photo-identification or ground survey methods.

There are numerous skeleton steel, power transmission towers in the area and they are of landmark value. But, except for instances where they are the ends of overhead cable crossings, it is difficult to isolate and identify a particular tower from offshore.

The area is unusual as few salient landmark objects are visible from offshore.

All landmarks and fixed aids to navigation have been listed on Form 76-40.

13. Geographic Names:

Geographic names are the subject of a separate report. The report is dated January 1975.

14. Special Reports:

The method of leveling used by the field party was the conventional trignometric leveling with the Wild TIA theodolite and stadia rod. Due to the steepness of the canyon walls it was necessary to observe vertical angles across the river to avoid exceeding the 10° limit as imposed by the project instructions. Due to the distance involved, the RANGER III laser system was used with good results. A double determination or a closed loop leveling method was employed to obtain a check elevation.

The entire shoreline was field edited (inspected) from a small boat.

15. Small Craft Facilities Investigation:

The small craft investigation was conducted during the month of September 1977. All the facilities were visited and the pertinent information has been entered on Form 77-3.

Respectfully submitted,

Robert B. Melby

Chief, PMC Photo Party

REVIEW REPORT TP-00035(2) CHART COMPILATION

April 23, 1979

61. GENERAL STATEMENT:

See Summary, page 6 of this Descriptive Report.

Configuration of the concrete ramp and float at Offield Landing was revised during final review. The ramp and float were recommended for charting by the field editor.

There is a significant scale difference between this map and TP-00827 to the east, caused by the fact that this map was ruled on a Mercator Projection having Lat. $46^{\circ}38'00''$ as its central parallel. Map TP-00827 was ruled on a Mercator Projection having Lat. $46^{\circ}25'30''$ as its central parallel. Precautions were taken during compilation to assure a satisfactory tie.

Compilation of this map includes only the Lower Granite Dam and its immediate vicinity. This map is a revision of Map TP-00035 of project PH-7001.

62. COMPARISON WITH REGISTERED TOPOGRAPHIC MAPS:

Not applicable.

63. COMPARISON WITH MAPS OF OTHER AGENCIES:

Not applicable.

64. COMPARISON WITH CONTEMPORARY HYDROGRAPHIC SURVEYS:

Hydrography for this area consist of contours and spot elevations delineated from aerial photography taken prior to fielding of the dam. They are displayed on this Chart Topography Map.

65. COMPARISON WITH NAUTICAL CHARTS:

This project is to serve as the basis for construction of a new chart covering the project area. At this writing that chart is not in publication. This area has not been previously charted.

66. ADEQUACY OF RESULTS AND FUTURE SURVEYS:

This map was compiled in compliance with the project instructions. The method employed for the application of field edit (See Summary, page 6) was neither prohibited nor recommended by the instructions.

Submitted by:

A. L. Shands

Final Reviewer

9.2. Shank

Approved for forwarding:

Bell & Barne

Chief, Photogrammetric Branch, AMC

Approved:

Chief, Photogrammetric Branch

Chief, Photogrammetry Division

RECORD OF APPLICATION TO CHARTS

FILE WITH DESCRIPTIVE REPORT OF SURVEY NO. TP-00035(2)

INSTRUCTIONS

A basic hydrographic or topographic survey supersedes all information of like nature on the uncorrected chart.

1. Letter all information.

2. In "Remarks" column cross out words that do not apply.

3. Give reasons for deviations, if any, from recommendations made under "Comparison with Charts" in the Revi

CHART	DATE	CARTOGRAPHER	REMARKS
18548	1-21-80	R. a. Lillis	Full Part Before After Verification Review Inspection Signed Via
		1-23-80 RCS	Drawing No.
			Full Part Before After Verification Review Inspection Signed Via
			Drawing No.
			Full Part Before After Verification Review Inspection Signed Via
			Drawing No.
			Full Part Before After Verification Review Inspection Signed Via
			Drawing No.
			Full Part Before After Verification Review Inspection Signed Via
			Drawing No.
			Full Part Before After Verification Review Inspection Signed Via
			Drawing No.
			Full Part Before After Verification Review Inspection Signed Via
			Drawing No.
			Full Part Before After Verification Review Inspection Signed Via
			Drawing No.
			Full Part Before After Verification Review Inspection Signed Via
			Drawing No.
			Full Part Before After Verification Review Inspection Signed Via
			Drawing No.