Form 504 Rev. Dec, 1933

DEPARTMENT OF COMMERCE
U.S. COAST AND GEODETIC SURVEY
R. S. PATTON, DIRECTOR

DESCRIPTIVE REPORT

Topographic

Hydrographic)

Sheet No. 5342

State Maryland

LOCALITY

Chesapeake Bay

Project No.:HT-175

193 5

CHIEF OF PARTY

Jr. H.&G. E.

U. S. GOVERNMENT PRINTING OFFICE: 1984

Applied to New Comp. Chart 545 June 29-1938. Chas. Or Bush for Applied to New Comp. of Chart 549 May 23 1939 Chas R. Bush?

DEPARTMENT OF COMMERCE U.S. COAST AND GEODETIC SURVEY

TOPOGRAPHIC TITLE SHEET

The Topographic Sheet should be accompanied by this form, filled in as completely as possible, when the sheet is forwarded to the Office.

Field No. 5342

REGISTER NO.

State Maryland
General locality Chesapeake Bay Sledds Pt to Stony Pt
Locality Patapsco River, Markey Creek, Stony-Creek & Reck-Gree Date of Photographs April 28 & May 18 1934 Scale 1:10,000 Date of Example December 3, 1934
Scale 1:10,000 Date of Entrey December 3,, 19.34
Reviewed and recommended for approval Chief of party Lieut. (j.g.) J.C. Partington, March 18, 1935
Photographs plotted by S.M. Stoler, December 3, 1934
Inked by A.V. Merkel March 6, 1935
Heights in feet aboveto ground to tops of trees
Contour, Approximate contour, Form line intervalfeet
Instructions dated March 14, 1934 , 19
Compilation of agrial photographs: Remarks: Nos. 537-555; 576-585; 696-708.

on

SHEET, FIELD NO. 5342, REG. NO. 7-5342 537-555 PHOTOS, NO. 576-585 696-708

DATE OF PHOTOGRAPHS April 28, 1934 May 18, 1934 11:20 A.M. to 1:00 P.M. 9:45 A.M. to 1:50 P.M.

9:4	19 A.M. to 1:50 P.M.		DATE
	BY	FROM	TO
ROUGH RADIAL PLOT	S.M. Stoler	8- 6-34	8-16-34
SCALE FACTOR (1.034)	S.M. Stoler	8-14-34	8-16-34
SCALE FACTOR CHECKED	ReD. Cross	8-17-34	8-17-34
PROJECTION	W. Seager	8-14-34	8-14-34
PROJECTION CHECKED	R.D. Cross	8-14-34	8-14-34
CONTROL PLOTTED	J.W. Seager	8-14-34	8-14-34
CONTROL CHECKED	D. J. Batte	8-15-34	8-15-34
TOPOGRAPHY TRANSFERRED	S.M. Stoler	12- 5-34	12- 6-34
TOPOGRAPHY CHECKED	R.D. Cross	12- 6-34	12- 6-34
SMOOTH RADIAL LINE PLOT	S.M. Stoler	11-22-34	12- 3-34
RADIAL LINE PLOT CHECKED	R.D. Cross	12- 4-34	12- 4-34
DETAIL INKED	A.V. Merkel	12-21-34	3- 6-35
			10

AREA OF DETAIL INKED 23.37 Sq. Statute Miles (Land Area)

AREA OF DETAIL INKED .02 Sq. Statute Miles (Shoals in Water Area)

LENGTH OF SHORELINE (more than 200 m. from nearest opposite shore) 21.6 Statute Miles

LENGTH OF SHORELINE (rivers and sloughs less than 200 m. wide) 14.4 Statute Miles

LENGTH OF STREETS, ROADS, TRAILS, R.R., etc. 1/2.5 Statute Miles

GENERAL LOCATION Maryland, Chesapeake Bay Sledds Pt to Stony Point LOCATION Patapsco River, Marley Greek, Steny

DATUM North American 1927

Latitude 39° 09' 31.488" = 971.0 m. STATION: Solly 1933 Longitude 76° 34' 03.815" = 91.6 m.

Field Computations

PROJECTION DIAGRAM

SHEET NO. 5342

Scale = 1:10,000

Scale Factor = 1.034

Distances multiplied by Scale Factor are given in Red.

76°_35'		34 [†]	₁ 33 *	1321	31 <i>'</i>	76°	301	ė
i	(4465.0)	(2976.7)	(1488.3)					13'
	4318.2	2878.8	1439.4					
				(5739•5)			,	
				5550.8				
121	(14,66.0)	(2977•3)	(1488.6)					121
+=	4319.2	2879.4	1439.7					
				(3826.4)				
•				3700.6				
			(2) (2)	9,00.0				
111	<u>(4467.1)</u>	(2978.0)	(1/189.1)				<u> </u>	11'
	4320.2	2880.1	1440.1					
				(1913.2)				
				1850.3				
708201	(2،86بلا)	(2978.7)	(1489.4)				30°	10'
39°10'	4321.3	2880.8	1440.4					
,	,,,			(1913.2)				
				1850.3				
<i>i</i>		/ >	(2) (2)	10,000				ا 99
o 💆	(4469.2)	(2979•5)	(1489.8) 1440.8				-	U
	4322.3	2881.5	T\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	•				
				(3826.4)				
				3700.6				
081	(4470.3)	(2980.2)	(1490.1)					081
	4323.3	2882.2	1/41.1					
· .	(J. 19.14)			(5739•5)				
				1				
05.		,	(2) 1 >	5550.8				071
07 *	(4471.3)	(2980,8)	(1490.4)				 	71
	4324.3	2882.8	1441.4	70*	311	76°	 30 '	
76° 35	7	34*	33'	321	Dayout by Checked by	J.W.S.	50.	

SHEET NO. 5342

SCALE FACTOR COMPUTATIONS

Photos 571-585

Station	<u>to</u>	Station	Measured Distance	Computed Distance	Scale Factor Meas./Comp.
Quarantine 1915 r'34*		Sledds (U.S.E.) 1915*	1965	1897	1.036
Quarantine 1915 r'34*		Stone 1915	2491	2402	1.037
Quarantine 1915 r •34*		F.S. Royster 1915	3059	2953	1.036
Quarantine 1915 r'34*		Brooklyn Church, spire 1915	55 3 5	5324	1.040
Quarantine 1915 r'34		U.S. Ordinance Plant, tank 1933 r'34 *	3948	3826	1.032
U.S. Ordin Plant, tan 1933 r'34*	k	Filbert 1933	2239	2 176	1.029
U.S. Ordin Plant, tan 1933 r'34*	ık	Brooklyn Church, spire 1915	391 0	37 89	1.032
U.S. Ordin Plant, tar 1933 r'34:	ık	F.S. Royster 1919	5 4544	51415	1.030
F.S. Royst 1915 r'34	er	Brocklyn Church, spire 1915	3490	3352	1.041
F.S. Royst 1915 r'34	er	Sledds (U.S.E.) 1915*	2536	2450	1.035
Prudential Co.'s stac 1915		Sledds (U.S.E.) 1915*	2060	1 987	1.037
Sugar (U.S 1916	S.E.)	Quarantine 1915 r'34 *	2325	2245	1.036
Dome 1915	*	Brooklyn Church, spire 1915	523 5	5041	1.038
		Α.		la Feator	₌ 1 .035

Average Scale Factor = 1.035

Average scale factor computed for entire flight but only part of this flight (576-585) falls on the tracing area of the sheet.

Triangulation stations marked (*) fall on this sheet.

Actual scale factor used for sheet was 1.034 in order to correspond with adjoining sheets.

Computed by S.M.S. 8/16/34 Checked by R.D.C.

SHEET NO. 5342 CONTROL DATA

Station	_	orth _	American	Datum <u>m.</u>	1927 Datum m.	x Scale Factor
Armistead 1915 r'34* (N.A. 1927 Datum)	3 9 76	1 2 32	35.226 00.003	;	(764.0) 1086.3 (1439.6) 0.1	(790.0) 1123.2 (山88.5) 0.1
Base Monument, north (U.S.E.) 1915	3 9	12	34.591	1066.8	(794.6) 1055.8 (1360.4)	(821,6) 1091,7 (14,06,6) 82,1
Brewerton Channel	76 39	3 2 1 2	03.11 ₁ 2 28.031	75•4	79•4 (965•9) 864•4	(1019 _• 年) 893 _• 8
Front Range 1934 * (N.A. 1927 Datum)	76	31	58 . 56 7	;	(345.5) (345.5)	(35,6) 以53 . 2 (357 . 2)
Brewerton Chammel Rear Range 1934 * (N.A. 1927 Datum)	39 76	1 2 33	48.796 07.483		1504.8 (1259.9) 179.6	1556.0 (1302.7) 185.7
Dome 1915	39		28.953	892.9	(968°.4) 881°.9 (339°.9)	(1001.3) 911.9 (351.4)
1	76	33	3 45.668	1095.7	1099.7	1137'.1
Fort Carroll Light House 1915 r'34* (N.A. 1927 Datum)	39 76	12 31	51.921 12.731		(249.3) 1601.1 (1174.1) 305.5	(257 • 7) 1655 • 5 (1172 • 6) 315 • 9
Quarantine 1915 r 34 (N.A. 1927 Datum)*	39 76	13 33	02.044 04.365		(1787•3) 63•0 (1335•7) 104•7	(1848.0) 65.1 (1381.1) 108.3
Sledds (U.S.E.) 1915	3 9 76	13 34	96.664 بالله	204.9 553.3	(1656.4) 193.9 (882.0) 557.3	(1712.7) 200.5 (912.0) 576.2
Solly 1933* (N.A. 1927 Datum)	39	09	31 . 488)))•)	(879•3) 971•0 (1349•2)	(909.2) 1004.0 (1395.1)
(2,111)	76	34	03.815		91.6	94•7
Stony 1934 * (N.A. 1927 Datum)	39 76	10 30	19.849 195.444		(1238.2) 612.1 (379.4) 1061.0	(1280.3) 632.9 (392.3) 1097.1

SHEET NO: 5342 CONTROL DATA

-	Station	•	North	American	Datum m.	1927 Datum <u>m.</u>	x Scale Factor
ţ.	Sugar (U.S.E.) 1916	3 9	13	15.667	483.1	(1378.1) 472.1 (566.9)	(1425.0) 488.2 (586.2)
		76	34	36.203	بلـ 868		902.1
	Swan 1934* (N.A. 1927 Datum)	3 9 76	11 31	19.227 56.906		(1257.4) 592.9 (74.3) 1365.8	(1300.1) 613.1 (76.8) 1412.2
	Tank, U.S. Indust- rial Alcohol Co.	3 9	13	08.396	258.9	(1602.4) 247.9 (11.2)	(1656.9) 256.3 (11.6)
	1933 r'34	76	34	59.368	1424.2	1,28.2	1476.8
	U.S. Alcohol Co., stack 1933* (N.A. 1927 Datum)	39 76	13 35	09•237 01•023		(1565.l ₁) 28l ₁ .9 (1l ₁ 1l ₁ .9) 2l ₁ .5	(1618.6) 294.5 (1463.0) 25.3
	U.S. Ordinance Plant, tank 1933 r'34* (N.A. 1927 Datum)	,39 76	1 2 3 5	19.00 33.53		(1264.4) 585.9 (635.2) 804.6	(1307.4) 605.8 (656.8) 832.0
	U.S. Quarantine Station, tank 1933 r'34* (N.A. 1927 Datum)	39 76	12 33	52 .13 6 02 . 686		(242.5) 1607.8 (1375.3) 64.5	(250.7) 1662.5 (比22.1) 66.7

^(*) Computed directly on N.A. 1927 Datum

⁽t) Falls without the limits of the compilation as shown.

6

DESCRIPTIVE REPORT

To Accompany

PHOTO COMPILATION SHEET NO. 5342

Chesapeake Bay: Patapsco River, Marley Creek, Stony Creek,

& Rock Creek

Instructions dated March 14, 1934

1. GENERAL INFORMATION: *

- (a) Title. Refer to Title Sheet.
- (b) Statistics. Refer to Statistics Sheet.
- (c) No general report covering this area is available. The area is bounded on the north by the Patapsco River, on the east by the 76° 30' 00" meridian, on the south by approximately the 39° 06' 45" parallel, and on the west by the 76° 35' 00" meridian.

This section is thickly settled along the shores of the rivers and creeks and along the highways. There are only a few cultivated fields and orchards, the rest of the area being covered by trees.

(d) The following photographs were used in plotting this sheet:

Photo Numbers	Flight Strip Location	Date Time	Stage of Tide
5 3 7 to 555	North and south be- tween the 76° 32' 00" and the 76° 33' 00" meridians		AM High 5:52 AM Low12:43 PM PM
576 to 585	North and south be- 4 tween the 76° 34' 00" and the 76° 35' 00" meridians	-28-34 11:20 to 1:00	
696 to 708	North and south be- tween the 76° 34' 00" and the 76° 35' 00" meridians	5-18-34 9:45 to 1:50	

2. CONTROL: *

(a) Sources:

The triangulation stations shown on the celluloid furnished sufficient control for plotting the sheet. established by These triangulation stations were obtained from the progress sketches of the following Chiefs of Parties:

DESCRIPTIVE REPORT

SHEET NO. 5342

Lieut. (j.g.) J.C. Partington Patapsco River 1934
Lieut. John A. Bond Baltimore Harbor 1934
Lieut. Roland D. Horne Project No. G-113 1933

Also several stations were obtained from the publication "Triangulation in maryland".

The stations obtained from the progress sketch of Lieut.

John A. Bond, 1934 and those obtained from Triangulation in
Maryland were on North American Datum and were adjusted to
North American 1927 Datum by applying the following correction
furnished by the Washington Office: From the forward latitude
position subtract eleven meters and to the forward longitude
position add four meters.

(b) Errors:

The field party pricked a flagpole for the triangulation station "Base Monument North (U.S.E.) 1915". This is in error as another field inspection party recovered the triangulation station at a later date and found it to be a concrete monument having a copper nail with a cross mark for a point. This station is plotted on the celluloid but was not used in running the radial plot.

(c) Discrepancies:

No discrepancy in the position of any station was found in running the plot.

3. COMPILATION: *

(a) Method:

The usual radial line method was used to determine the position of all radial points.

(b) Adjustment of plot:

No serious difficulty was encountered in running the plot and no adjustment of plot was necessary. Most of the territory is covered by overlapping flights which give an additional check upon the accuracy of the points. There is very little control for the southern half of this sheet but the points should be very accurately located judging from the intersections obtained by the radial plot.

(c) Interpretation:

Pictures 543 to 551 inclusive are badly distorted due to tilt and it was very difficult to trace detail from them. The distortion made it difficult to identify houses and docks along Rock Creek. At points where the draftsman was in doubt a field inspection was made in order to clear up the difficulty and it is believed that the compilation is correct in this area.

DESCRIPTIVE REPORT

SHEET NO. 5342

(d) Information from other sources:

There are three bridges over navigable streams shown on this compilation. On the following page is the information on these bridges obtained from the U.S. Engineers Department at Baltimore, Md. on January 26, 1935. The information for the bridge over Stony Creek is contained in the publication "List of Bridges over Navigable Waters of the United States - 1927". The data on the other two bridges is not contained in the above mentioned publication.

All other information was obtained directly from the photographs.

(e) Conflicting Names:

The name Solly appears on the U.S. Coast and Geodetic Survey Charts. This name is spelled Solley on the U.S. Geological Survey, Relay Quadrangle. The name is spelled locally as Solley.

Additional Names:

It is recommended that the following names be added to the U.S. Coast and Geodetic Survey Charts. These are established local names:

Orchard Beach
Sunset Beach
Cottage Beach
Fairhaven
Lipins Corner
Lake Waterford
Marley Neck
Mountain Road
Annapolis Blvd.
U.S. Army Ordinance Depot
Fort Armistead

Riviera Beach (This name is erroneously spelled Rivera Beach on a recent Maryland Geological Survey Map).

4. COMPARISON WITH OTHER SURVEYS:

(a) Attention is called to the secondary road that crosses the southern boundary line of the sheet 100 meters east of the 76°31'00" meridian. This road was traced in error and has been corrected on this compilation. However, there is a short section of the road which continues into compilation 5343 and this should also be corrected in order to obtain a satisfactory junction. Compilation 5343 is now in the Washington Office and it is suggested that the correction be handled by that office. Other junctions are satisfactory.

(b) The latest topographic sheet that we have of this area, Topographic Sheet Register No.T-2286, compiled by the U.S. Coast and Geodetic Survey was completed in the year 1897. So many changes have occurred in the area since 1897 that a comparison of detail will be of no value. In general, the creeks and rivers check very closely but the changes are so numerous that the accuracy of this compilation cannot be checked by comparison with the topographic sheet. It is recommended that this compilation be accepted as correct.

Stony Creek bridge is listed as being 3.0 miles above mouth of Creek. This figure is incorrect and the figure given above of 1.0 mile above mouth is approximately correct. N.B.

* The probable error of position given here as 0.5 millimeter on the scale of this compilation is believed to be foo small a value especially in the area of this compilation east of 76° 31.5 where the compilation has not been satisfactorily photographed A more preasonable estimate of the maximum error of position would be from testent millimeters.

LA.M.

B.g. goves

DESCRIPTIVE REPORT

SHEET NO. 5342

5. LANDMARKS:

- (a) No additional landmarks or recoverable objects were recommended in this area by the field party.
- (b) On Chart No. 545, there are two landmarks shown which do not exist. There locations are:

Name Location		Lati	tude	Long	itude
No name	Stahl Pt., Curtis Creek	39°	11.9'	76°	34.81
Stack 40 ft.	Thomas Pt., Curtis Creek	3 9°	11.51	76°	34•7'

On March 14, 1935 the Commanding Officer of the Ordinance Depot, Cartis Bay, was interviewed and he advises that these two landmarks are no longer in existence. It is recommended that they be removed from the charts.

6. RECOMMENDATIONS FOR FURTHER SURVEYS: *

- (a) The compilation is believed to have a probable error of 3 meters in position of well defined detail of importance for charting and of 5 meters for other data. (See opposite page.)
- (b) The width of roads has been exaggerated where necessary in order to procure well defined lines when the sheet is reproduced.

Only houses located near the shore line have been shown on the compilation.

7. RECOVERABLE OBJECTS: *

There is no available record of any described topographic stations in this area and no additional objects were recommended by the field party. Landmarks which are already on the charts or which have already been described by other parties are located on the compilation and copy of Form No. 524 is enclosed herewith.

8. CABLE AREAS:

Chart No. 545 shows three cable areas which should be located on this sheet. Since no accurate data of the positions of these areas are available in this office, these areas are not shown on the photo compilation.

(*) N.B. The paragraphs (numbers and letters) listed refer to those shown on pages 22 and 23 of Notes on Compilation of Planimetric Line Maps.

DESCRIPTIVE REPORT

SHEET NO: 5424

9. MILITARY RESERVATIONS:

On March 14, 1935 the Commanding Officer, Ordinance Depot. Curtis Creek was interviewed in regard to showing detail within the limits of the U.S. Army Ordinance Depot. The Commanding Officer, Major Everett Collins, advised that no detail should be shown on the photo compilations or charts of this area.

In accordance with the Director's letter of April 4, 1934 and in compliance with the above request, this area has been left

The only topography shown is the high water line and features outside of the high water line.

The present charts show the detail in this area. It is recommended that this detail be taken off the present charts.

Respectfully submitted.

Jr. H. & G.K.

Chief of Party

DEPARTMENT OF COMMERCE

U.S. COAST AND GEODETIC SURVEY

LANDMARKS FOR CHARTS

				1	Balt	imoro, M	d.			_		
							Harc	h 19		. 10	93	5
DIRECTOR, U.S. COAST AND GE	ODETIC	Sub	IVEY:	•		- ·				,·	,,	
The following determine description given below, and a the prominence of the been checked from the control of t	should hese	i be d obj i	charted: ects	nent, (can b	e readily d	listinguis	shed from				3
	<u> </u>						<u>Porti</u>	neton_	Chiej	f of Par	ty. ===	=
	-	·		POSI			T	METHOD				
DESCRIPTION		LAT	TUDE	<u> </u>	LONG	SITUDE	DATUM	METHOD OF DETER- MINATION	AFF	HARTS	כ	
Omit Not conspicuo	°	<u>'</u>	D.M. METERS	\- <u>-</u>		D.P. METERS	87.	Radial	 			
PANK 90 Latin 277 (1951)	39	12	1183	76	35	147	N. A. 1927	Plot	545		1	X
TANK 50	3 9	12	444	76	35	69	N.A. 1927	Radial Plot	545,	549	1	- }
CHY 150	39	12	1682	76	型	298	N.A. 1927	Redial Plot	545.	549	,	. 1
PANK 75	39	11	1834	76	刄	126	1927	Plot	545.	549	1	
FLAG TOWER	39	11	1777	76	34	224	N.A. 1927	Radial Plot	545		/	r
COP Letter 277 (1938)	39	11	1734	76	34	134	N.A. 1927	Radial Plot	545.	54:9		, ,
SILO (A Dome)	39	12	881.9	76	33	1099.7	N.A. 1927	Priang.	545.	51.9	1	V
TANK SO (AU.S. Curren- tine Sterion, tank	3 9	12	1607.8	76	33	64.5	N.A. 1927	Prieng.	545.	51.9		
PLAG 30	3 9	12	1106	76	32	128	H.A. 1927	Radial Plot	545		_/	
<u> </u>				 			,,	,	2			
<u>) </u>	C	bart	ed Landr	ark s	- T	ne e nti	nuance	of which	is re	CONTRA	and:	eđ.
			Position	c co	e l od	by J.W.	S					
						d by R.I						
	 		1								—	
	ļ											

A list of objects carefully selected because of their value as landmarks as determined from seaward, together with individual descriptions, must be furnished in a special report on this form, and a copy of such report must be attached by the Chief of Party to his descriptive report.

The selection, determination, and description of these points are an important factor in the value of the chart. Landmarks selected at appropriate intervals can be clearly charted. However, when none is outstanding, a group of two or three objects may by their interrelationship provide positive indentification. A group so selected should be indicated.

The description of each object should be short, but such as will clearly identify it; for example, a standpipe, elevated tank, gas tank, church spire, tall stack, red chimney, radio mast, etc. Assign numerals to landmarks to indicate: (1) Offshore, (2) inshore, (3) harbor, 1, 2, 3 would be a mark useful on all charts. Generally, flagstaffs and like objects are not sufficiently permanent to chart. permanent to chart. U.S. GOVERNMENT PRINTING OFFICE: 1984 23379

March 19

DIRECTOR, U.S. COAST AND GEODETIC SURVEY:

DEPARTMENT OF COMMERCE

U.S. COAST AND GEODETIC SURVEY

LANDMARKS FOR CHARTS

The following determined objects are prominent, can be readily distinguished from seaward from the

TO BE REMOVED FROM CHARTS Baltimore, Md.

					J	.C. Part	ington		Chief of Party			
		POSITION										
DESCRIPTION	LATIT		TUDE	-	LONG	ITUDE	DATUM	METHOD OF DETER- MINATION	CHARTS AFFECTED			
	0	1	D.M. METERS	0	٠,	D.P. METERS	DATUM					
ACK 40 (Thomas Pt., Curtis Creek)	39	11	-5	_76	34	6			545			
Name (Stahl Pt., Curtis Creek)	39	11	9	76	弘	.8			51.5			
Non-ex	stent	Le	ndmarks	· To	ъе	removed	from ch	arts.				
<u> </u>			-			<u> </u>						
<u> </u>	ļ											
							<u> </u>					
							<u> </u>		·. 			
4												
_								•				
					· 							
						 	 					

A list of objects carefully selected because of their value as landmarks as determined from seaward, together with individual descriptions, must be furnished in a special report on this form, and a copy of such report must be attached by the

Chief of Party to his descriptive report.

The selection, determination, and description of these points are an important factor in the value of the chart. Landmarks selected at appropriate intervals can be clearly charted. However, when none is outstanding, a group of two or three objects may by their interrelationship provide positive indentification. A group so selected should be indicated.

The description of each object should be short, but such as will clearly identify it; for example, a standpipe, elevated tank, gas tank, church spire, tall stack, red chimney, radio mast, etc. Assign numerals to landmarks to indicate: (1) Offshore, (2) inshore, (3) harbor, 1, 2, 3 would be a mark useful on all charts. Generally, flagstaffs and like objects are not sufficiently permanent to chart. U. S. GOVERNMENT PRINTING OFFICE: 1934 25379

DEPARTMENT OF COMMERCE

U.S. COAST AND GEODETIC SURVEY

LANDMARKS FOR CHARTS

Baltimore, Md.

•							Decembe	r 28		, 193 🕹	+
DIRECTOR, U.S. COAST AND GEO	DETIC	Sur	EY:			•			•		
The following determined	objec	cts a	re promin	ent, c	an b	e readily d	listi n guis	hed from s	seaward	from the	ş.
lescription given below, and sl	nouna	be c	nartea:			٠		•			
					J.	C. Parti	ngton		Chief o	of Party.	
		POS						-			:
DESCRIPTION	LATITUDE		TUDE .		LONG	SITUDE		METHOD OF DETER- MINATION	CH/ AFFE	ARTS	
	0	,	D.M. METERS	۰	•	D.P. METERS	DATUM M				
Brewerton Channel Front Range Light	3 9	12	864.4	76	31	1405.4	N.A. 1927	Triang.	77, 5L	/ 15 ,5 49,	,12
Brewerton Channel Rear Range Light	3 9	12	(341.5) 150 4.8	76	33	179.6	N.A. 1927	Triang.	77, 5L	549,	,1 2
Fort Carroll Lighthouse	39	12	1601.1	76	31	305.5	N.A. 1927	Triang.	77, 5L	<u>, 5</u> 49,	, 12
					-						
Excerpt from	repo	rt :	ubmitted	und	er (date of	December	28, 19	34		
after oc	mple	tion	ndof Tris	ngul	ati	n Schem	, Pata	sco Riv	ər		
1934.									 		
			-								
		•									
· ·											
							<u> </u>		<u> </u>		

A list of objects carefully selected because of their value as landmarks as determined from seaward, together with individual descriptions, must be furnished in a special report on this form, and a copy of such report must be attached by the

Chief of Party to his descriptive report.

The selection, determination, and description of these points are an important factor in the value of the chart. Landmarks selected at appropriate intervals can be clearly charted. However, when none is outstanding, a group of two or three objects may by their interrelationship provide positive indentification. A group so selected should be indicated.

The description of each object should be short, but such as will clearly identify it; for example, a standpipe, elevated tank, gas tank, church spire, tall stack, red chimney, radio mast, etc. Assign numerals to landmarks to indicate: (1) Offshore, (2) inshore, (3) harbor, 1, 2, 3 would be a mark useful on all charts. Generally, flagstaffs and like objects are not sufficiently permanent to chart permanent to chart. U.S. GOVERNMENT PRINTING OFFICE: 1984 25379

Survey No. 1 - 5342

Chart No. 77, 545, 549, 1226

Diagram No. 77

Approved by the Division of Geographic Names, Department of Interior. *\footnote{\text{Referred to the Division of Geographic Names, Department of Interior.}} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geographic Names, Department of Interior.} \text{Referred to the Division of Geogr

Status	Name on Survey	Name on Chart	New Names in local use	Names assigned by Field	Location
	Solley man ?	do. ch. 1226 (correct s	pelling on ch	549) 500 page	8
	Orchard Beach		~		16
	Sunset Beach		1		
	Cottage Beach?		1		
	Fairhoven Beach.	<u> </u>	. /		
*	Lipins Cornerx		~		
	Rivera Beach	- 44	1		
	Take Waterford		1	Waterford	Lane
	Marley Neck		V	-	
	Armiger.	do ch. 549, 1226			
	Jacobsville	do - 549, 1226		- "	
	Leading Point?	549, 545			
	Sledds Point	549, 545			
	Curtis Creek	549, 545			
	Ferry Point	549, 545		*	
	Marley Creek	549,			
, Miller	Tanyard Core	549,			
	Fort Corroll	549, 545		21	
	Howkins Point.	549, 545			
	Thomas Cove.	549, 545			
	Patopsco River	549 545			
	Thomas Pt.	549,545			(M-136)
		2			(m-13b)

GEOGRAPHIC NAMES

Date. April 8,1935.

Survey	No. 7-5342	

Chart No. 77,545,549, 1226

Diagram No. 77.

Approved by the Division of Geographic Names, Department of Interior. *\foating Referred to the Division of Geographic Names, Department of Interior. R

Under investigation. Q

Status	Name on Survey	Name on Chart	New Names in local use	Names assigned by Field	Location
	Goose Neck	549.			
	Cox Creek	549, 1226			
	Stony Point	549, 1226			
	Stony Creek	549, 1226			
	Back Cove	549, 1226			
	Nobbs Creek	549 /226			
	-Constitution-Cove	549.			
	Beehive Core	549			
	Sloop Cove	549			
	Long Cove	549 /226			
	Eli Cove	549 /226			.,,
÷	Rock Creek	549 1226			
	Tor Cove	549 /226			
	Curtis Bay ?	549 1220	, <u> </u>	1	
	Mountain Road				
- +	Annapolis Blvd				
<u> </u>	Cabin Branch	549 545, 1220	<u>د</u>		· · · · · · · · · · · · · · · · · · ·
	Walnut Point ?	549, 545, 1226	P		
	Stuhl Point	549 545, 1226	× .		
	Furnace Creek	549 1226	Deta.	and name a	d to
,	Big Burley	549 122	6 adjoin	ag sheet.	n 121/35.
· · · · · · · · · · · · · · · · · · ·	Arundel Cove.	549,545, 1226		10 /22/3	/21/35. 5 (4-1
	Sway Creeky.	549, 545. 1226		K.T.A	

REVIEW OF AIR PHOTO COMPILATION NO. T-5342

Comparison with Previous Topographic Surveys.

T-220 (1845) Scale 1:20,000.

T-220 covers the south shore of the Patapsco River from Bodkin Point to Ferry Point. Changes of culture and shoreline since the time of T-220 are large. T-220 is superseded by this compilation over the common area.

T-983 (1865) Scale 1:10,000.

T-983 covers the south shore of the Patapsco River from the Light St. Bridge to Swan Creek. Changes of culture and shoreline since 1865 are large. Except for the contours which are shown on T-983, T-983 is superseded by the compilation over the common area.

T-2269 (1898) Scale 1:10,000.

T-2269 covers the Patapsco River from Curtis Creek to Gwynns Falls. Only a small portion of T-2269 is common to the compilation between Sledds Point and Leading Point. This portion has changed considerably since 1898 and is superseded by this compilation.

T-2286 (1898) Scale 1:20,000.

T-2286 is the most recent complete plane table survey made in this area. It covers the Chesapeake Bay and Patapsco River from Gibson Island to Curtis Creek. Shoreline differences between T-2286 and this compilation, changes since the time of T-2286 are given as follows:

At mouth of Rock Creek:

Latitude 39° 09'.5 60 meters maximum Longitude 76° 30'

At Orchard Beach 0 to 50 meters
At Goose Neck 0 to 40 meters
Between Thomas Cove and Hawkins Pt. 0 to 30 meters

Other changes since the time T-2286 was made are new roads, beach improvements, and real estate developments. Except for the contours shown on T-2286, T-2286 is superseded by this compilation.

T-4065a (1924) Scale 1:10,000.

T-4065a covers the Patapsco River in Baltimore Harbor. No shoreline is shown on T-4065a over the area covered by this compilation, except a portion of Gurtis Creek shoreline. T-4065a is superseded by this compilation over the common area.

Comparison with the Charts.

Chart No. 545.

New landmarks and landmarks recommended for deletion are given at the back of this Descriptive Report. Landmark "SILO" on this chart corresponds to triangulation station Dome, 1915.

The wreck shown on this chart in latitude 39° 12'.9, longitude 76° 33'.85 has been transferred to the compilation from H-4371 (1924). It could not be identified on the photographs but its existence has not been disproved.

The submerged rock on chart 545 on Thomas—Cove and the submerged wreck south of Hawkins Point could not be identified on the photographs but are not disproved. These are not shown on this compilation.

Chart No. 549.

The discussion for Chart 545 given above also applies for Chart No. 549. In addition there is a submerged wreck shown on chart 549 at the mouth of Rock Creek which could not be identified on the photographs but is not disproved and not shown on this compilation.

Chart No. 1226.

The submerged wreck shown on this chart between Sledds Point and Leading Point has been transferred to the compilation from H-4371 (1924). It could not be identified on the photos and its existence has not been disproved.

The submerged rock in Themas Cove and the submerged wrecks, one South of Hawkins Point, the other at the mouth of Rock Creek, could not be identified on the photographs. This detail is not shown on the compilation, although in all probability it is still in existence. Changes to be made to these charts as a result of this compilation are discussed under the comparison with previous Topographic Surveys.

There are no new hydrographic surveys or any graphic control surveys of this area.

Remarks.

The projection of this compilation was tested roughly by checking long diagonals and found satisfactory.

The heights of bluffs as given below were estimated by the field inspection party. They are not shown on the compilation as they do not apply to a specific location.

In Rock Creek	10	to	30	feet
In Stony Creek	15	to	3 0	feet
In Nabbs Creek	10	to	25	feet
At Stony Point			10	feet
At Orchard Beach			30	feet
In Cox Creek	10	to	15	feet
At Hawkins Point			30	feet
At Leading Point			15	feet
At Walnut Point			15	feet
In Curtis Creek	5	to	20	feet.

July 18, 1935.

Leonard A. McGann,

Bg gones

Chief of Party: A.C. Partington

Compiled by: A.V. Merke/

Project: HT 175

Instructions dated: March 14, 1934

- 1. The charts of this area have been examined and topographic information necessary to bring the charts up to date is shown on this compilation. (Par. 16a, b,c,d,e,g and i; 26; and 64)
- -2. Change in position, or non-existence of wharfs, lights, and other topographic detail of particular importance to navigation which affect the chart, is discussed in the descriptive report. (Par. 26; and 66 g,n)
 - 3. Ground surveys by plane table, sextant, or theodolite have been used to supplement the photographic plot where necessary to obtain complete information, and all such surveys are discussed in the descriptive report. (Par. 65; and 66 d,e)

 No ground surveys wade to cover the area of this compilation.
- 4. Blue-prints and maps from other sources which were transmitted by the field party contain sufficient control for their application to the charts. (Par. 28)

 No blue-prints or maps transmitted.
- 5. Differences between this compilation and contemporary plane, table and hydrographic surveys have been examined and rectified in the field before forwarding the compilations to the office and are discussed in the descriptive report.

 Compared with Topographic Sheet T-2286 made in 1897
- 6. The control and adjustment of the photo plot are discussed in the descriptive report. Unusual or large adjustments are discussed in detail and limits of the area affected are stated. (Par. 12b; 44; and 66 c,h,i)
- 7. High water line on marshy and mangrove coast is clear and adequate for chart compilation. (Par. 16a, 43, and 44)

NOTE: Strike out paragraphs, words or phrases not applicable and modify those requiring it. Paragraph numbers refer to those in the Topographic Manual. Refer also to the pamphlet "Notes on the Compilation of Planimetric Line Maps from Five Lens Air Photographs."

- 8. The representation of low water lines, reefs, coral reefs and recks, and legends pertaining to them is satisfactory. (Par. 36, 37, 38, 39, 40, 41)
- 9. Recoverable objects have been located and described on Form 524 in accordance with circular 30, 1933, circular letter of March 3, 1933, and circular 31, 1934. (Par. 29, 30, and 57)

 Descriptions of stations filed with this Compilation See review at back for detail.
- 10. A list of landmarks was furnished on Form 567 and instructions in the Director's letter of July 16, 1934, Landmarks for Charts, complied with. (Par. 16d, e; and 60).

 Duplicate attached to descriptive report.
- 11. All bridges shown on the compilation are accompanied by a note stating whether fixed or draw, clearance, and width of draw if a draw bridge. Additional information of importance to navigation is given in the descriptive report. (Par. 16c)
- 12. Geographic names are shown on the overlay tracing. The accepted local usage of new names has been determined and they are listed in the report, together with a general statement as to source of information and a specific statement when advisable. Complete discussion of place names differing from the charts and from the U.S.G.S. Quadrangles is given in the descriptive report together with reasons for recommendations made. (Par. 64, and 66k)
- 13. The geographic datum of the compilation is North American 1927 and the reference station is correctly noted. Datum station is unadjusted.
- 14. Junctions with adjoining compilations have been examined and are in agreement. (Par. 66j)
- 15. The drafting is satisfactory and particular attention has been given the following:
 - 1. Standard symbols authorized by the Board of Surveys and Maps have been used throughout except as noted in the report.
 - 2. The degrees and minutes of Latitude and Longi- tude are correctly marked.

- 3. All station points are exactly marked by fine black dots.
- 4. Closely spaced lines are drawn sharp and clear for printing.
- Topographic symbols for similar features are of v uniform weight.
- 6. All drawing has been retouched where partially rubbed off.
- 7. Buildings are drawn with clear straight lines and square corners where such is the case on the ground.

(Par. 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 48)

- 16. No additional surveying is recommended at this time.
- 17. Remarks:

18. Examined and approved;

19. Remarks after review in office:

Reviewed in office by:

Examained and approved:

Chief, Section of Field Records

Chief, Division of Charts

Chief, Section of Field Work

Chief, Division of Hydrography

and Topography.