Diag'd. on Diag. Cht. No. 6157 (Insert)

Form 504

U. S. COAST AND GEODETIC SURVEY

DEPARTMENT OF COMMERCE

DESCRIPTIVE **REPORT**

Planimetric Air Photographic

Type of Survey Shoreline.

8849 to

Field No. Ph-2 (45) Office No. 8852 Inc. (Area of the first Radial Plot)

LOCALITY

State Washington

General locality Franklin D. Roosevelt Lake

Locality Coulee Dam

N944-147

CHIEF OF PARTY

J.T.Jarman

LIBRARY & ARCHIVES

July 12, 1949 DATE

DATA RECORD

T-8849

Quadrangle (II): WILBUR, WASH. (USE)

Project No. (II): Ph-2(45)

30 minute 1:125000

Field Office: Coulee Dam, Wash. Chief of Party: J.T. Jarman

Compilation Office: Portland, Ore.Chief of Party: R. A. Earle

Instructions dated (II III):4-3-47 PL Supplemental, 15 May, 1917

Division of Copy filed in Descriptive Photogrammotry Office Files.

Completed survey received in office: / Mar. 1948

Reported to Nautical Chart Section:

Reviewed: 29 Oct. 1948 Applied to chart No.

Redrafting Completed: -

Registered: 24 June 1949

Published: See "Remarks" p. 3

Compilation Scale: 1:10000

Published Scale:

Scale Factor (III): None

Normal Pool Elevation,

Geographic Datum (III): N.A.1927

Datum Plane (III): Mean Sea Level

(128851' USG\$65,1429)

Reference Station (III): GRANITE (USER), 1934 r 1947

Lat.: 47° 57' 16.643" (514.1m) Long.: 118° 55' 47.751" (990.7m) Adjusted x Unad justed

State Plane Coordinates (VI): Washington, North Zone

X = 2, 466, 366.98

Y = 353, 983.75

(0.205)

Military Grid Zone (VI)

PHOTOGRAPHS (III)

Number	Date	Time	Scale	Water Level Stage_of_Tide
Nine lens 17368 to 17371 17442 to 17444 17447 to 17450	8-21-46 ³ 8-22-46 8-22-46	11:55P.S.T. 10:59P.S.T. 11:21P.S.T.	1:10000	1289.65 above M.S.L. 1289.65 above M.S.L. 1289.65 above M.S.L.
U.S.Army Single lens 32-2 to 38-2-493 65-1 to 71-1-493	1944 1944	Unknown Unknown	1:20,000	Unknown Unknown

Tide from (III): None

Mean Range: None

None Spring Range:

Camera: (Kind or source) U.S.C.&G.S., 9 lens, focal length 8.2% inches

U.S.Army, Single lens, focal length 8.25 inches

Field Inspection by: J.T. Jarman

date:

date: Summer 1947

Interior, John Winniford Shoreline, John Lajoye

5-20-47 date: 6-6-47

Field Edit by: None date:

Date of Mean High-Water Line Location (III): 8-22-46

Projection and Grids ruled by (III) Washington Office date: July 1947

checked by: Washington Office date: July 1947

J.L.Harris Control plotted by: date: July 10, 1947

Control checked by: F.H.Elrod date: July 14, 1947

Radial Plot by: J.L.Harris & J.E.Deal date: July 26, 1947

R.A.Davidson date: Sept. 24, 1947 Detailed by:

Reviewed in compilation office by: ... R. H. Barron date: Sept. 30; 1947

Elevations on Field Edit Sheet checked by: Not applicable date:

STATISTICS (III)

Iand Area (Sq. Statute Miles): 33 sq. mi. (Complete detail along shoreline) (Skeleton detail interior

Shoreline (More than 200 meters to opposite shore): 26.4

Shoreline (Less than 200 meters to opposite shore): None

Number of Recoverable Topographic Stations established: 1

Number of Temporary Hydrographic Stations located by radial plot: 89

Leveling (to control contours) - miles:

Roman numerals indicate whether the item is to be entered by, (II) Field Party, (III) Compilation Party, or, (VI) the Washington Office.

When entering names of personnel on this record give the surname and initials (not initials only).

Romarks: Thee shoreline maps have an enumeral amount of interior highways delineated.

At present only 3 copies of each map manuserift have been printed: a mounted therman for registration in ihr Archiver; and two on chart faper for the files.

Extra copies may be issued to the several small towns in the mapped area for distribution to interested local inhabitants.

DATA RECORD

T-8850

Quadrangle (II): WILBUR, WASH. (U.S.S.)

Project No. (II): Fh-2(45)

30 Minute 1:125,000

Field Office: Coulee Dam, Wash. Chief of Party: J. T. Jarman

Compilation Office: Portland. Ore. Chief of Party: R. A. Earle

Instructions dated (II III): 4/3/47

Completed survey received in office: / Nov. 1948

Reported to Nautical Chart Section:

Reviewed: 2 Nov. 1948

Applied to chart No.

Redrafting Completed:

Registered: 24 June 1949

Published:

Compilation Scale: 1:10000

Published Scale:

Scale Factor (III): None

Normal Pool Elevation, 1290' above USBR.19 Datum Plane (III): Mean Sea Level

Geographic Datum (III): N. A. 1927

(1200.5 ± 1, USG 2 65, 1929)

Reference Station (III): PLUM, (USBR) 1934 - 1947

Let.: 47° 54' 31.040" (958.7m) Long.: 118° 49' 01.709" (35.5m) Adjusted x

Unadjusted

State Plane Coordinates (VI): Washington, North Zone

X = 2, 494, 435.80

Y = 3 37, 913. 44

Military Grid Zone (VI)

PHOTOGRAPHS (III)

Number	Date	Time	Scale	Water Level
<pre>9 Lens 17371 to 17374 17438 to 17441 17451 & 17452</pre>	8-21-46 8-22-46 8-22-46	11:57P.S.T. 10:57P.S.T. 11:24P.S.T.	1:10000	1289.65 above M.S.L. 1289.65 above M.S.L. 1289.65 above M.S.L.
U.S.Army Single lens 73-1 & 74-1 27-2 to 31-2 25-2 to 68-2	1944 1944 1944	Unknown Unknown Unknown	1:20000 1:20000 1:20000	Unknown Unknown Unknown

Tide from (III): None

Mean Range: None

Spring Range:

None

Camera: (Kind or source) U.S.C.&G.S., 9 lens, focal length 8.25 inches
U.S. Army, Single lens, focal length 8.25 inches

Field Inspection by: J. T. Jarman

Interior, John Winniford

date: Summer 1947 date: 5-21-47

Shoreline, John Lajoye

date: 6-18-47

Field Edit by: None

date:

Date of Mean High-Water Line Location (III): 8-22-46

Projection and Grids ruled by (III) Washington Office	date:	July 1947
" " checked by: Washington Office	date:	July 1947
Control plotted by: J. L. Harris	date:	July 1947
Control checked by: Frank Elrod	date:	July 10, 1947
Radial Plot by: J. L. Harris & J. E. Deal	date:	July 28, 1947
Detailed by: Marie Elrod	date:	Sept. 12, 1947
Reviewed in compilation office by: Ree H. Barron	date:	Sept. 29, 1947

Elevations on Field Edit Sheet checked by: None Not applicable

)

date:

W.

STATISTICS (III)

Land Area (Sq. Statute Miles): 30 (Complete detail along shoreline) (Skeleton detail interior)

Shoreline (More than 200 meters to opposite shore): 21.0

Shoreline (Less than 200 meters to opposite shore): None

Number of Recoverable Topographic Stations established: 4

Number of Temporary Hydrographic Stations located by radial plot: 52

Leveling (to control contours) - miles:

Roman numerals indicate whether the item is to be entered by, (II) Field Party, (III) Compilation Party, or, (VI) the Washington Office.

When entering names of personnel on this record give the surname and initials (not initials only).

Remarks:

\$

DATA RECORD

T-8851

Quadrangle (II): WILBUR, WASH. (USE)

Project No. (II):

Ph-2(45)

30 minute 1:125.000

Field Office: Coulee Dam, Wash. Chief of Party: J.T.Jarman

Compilation Office: Portland. Ore. Chief of Party: R. A. Earle

Instructions dated (II III): 4-3-47

Completed survey received in office: / Mar. 1948

Reported to Nautical Chart Section:

Reviewed: 15 Nov. 1941 Applied to chart No. ____ Date:

Redrafting Completed:

Registered: 24 June, 1949

Published: ----

Compilation Scale: 1:10,000

Published Scale:

Scale Factor (III): None

Geographic Datum (III): N.A. 1927

Normal Pool Elevation,
1290' above USBR 1937

Datum Plane (III): Mean Sea Level
(1288.5 t' USCR 65,1029)

Reference Station (III): DEVILS CANYON, U.S.B.R., 1934 r 1947

Lat.: 47° 53' 50.995" (1575.0m) Long.:118° 43' 28.847" (599.2m) Adjusted x Unad justed

State Plane Coordinates (VI): Washington, North Zone

X = 2,5/7,2/6.02

Y = 334,465.06

(p205)

Military Grid Zone (VI)

PHOTOGRAPHS (III)

Number	Date	Time	Scale	Stage of Tide
9 lens 17375 to 17377 17434 to 17438 17453 to 17456	8-21-46 8-22-46 8-22-46	11:59P.S.T. 10:55P.S.T. 11:27P.S.T.	1:10000 1:10000	1289.65 above M.S.L. 1289.65 above M.S.L. 1289.65 above M.S.L.
17498 to 17500	8-22-46	12:40P.S.T.	1:10000	1289.65 above M.S.L.
U.S.Army Single lens				
27-1 to 80-1	1944	Unknown	1:20000	Unknown
22-2 to 26-2	1944	Unknown	1:20000	Unknown
70-2 to 76-2	1944	Unkn <i>o</i> vn	1:20000	Unknown

Tide from (III): None

Mean Range: None Spring Range: None

Camera: (Kind or source) USC&GS, 9 lens, focal length 8.25 inches U.S. Army, Single lens, focal length 8.25 inches

J. T. Jarman Summer 1947 Field Inspection by: date:

Interior-John Winniford

5-23-47 6-26-47 Shoreline-John Lajoye

Field Edit by: None date:

Date of Mean High-Water Line Location (III): 8-22-46

Projection and Grids ruled by (III) Washington Office date: July 1947

checked by: Washington Office date: July 1947

date: July 15, 1947 Control plotted by: Frank Elrod

Control checked by: date: July 16, 1947 James L. Harris

date: July 28, 1947 Radial Plot by: James L. Harris & J. E. Deal

date: Oct. 8, 1947 Detailed by: Marie Elrod

Reviewed in compilation office by: Ree H. Barron date: Oct. 13, 1947

Elevations on Field Edit Sheet checked by: None

date:

STATISTICS (III)

Land Area (Sq. Statute Miles): 38 (Complete detail along shoreline) (Skeleton detail interior

Shoreline (More than 200 meters to opposite shore): 33.0 statute miles

Shoreline (Less than 200 meters to opposite shore): None

Number of Recoverable Topographic Stations established: 4

Number of Temporary Hydrographic Stations located by radial plot: 55

Leveling (to control contours) - miles:

Roman numerals indicate whether the item is to be entered by, (II) Field Party, (III) Compilation Party, or, (VI) the Washington Office.

When entering names of personnel on this record give the surname and initials (not initials only).

Remarks:

DATA RECORD

T-8852

Wilbur, Wash. Keller, Wash. Quadrangle (II):

Project No. (II): Ph-2(45)

30 minute 1:125000

Field Office: Coulee Dam, Wash.

Chief of Party:

J. T. Jarman

Compilation Office: Portland, Ore. Chief of Party: R. A. Earle

Instructions dated (II III): 4-3-47

Copy filed in Descriptive

Report No. T (VI)

Photogramme try Office Files

Completed survey received in office: / Mar. 1948

Reported to Nautical Chart Section:

Reviewed: 19 Nov. 1948 Applied to chart No. _____ Date:

Redrafting Completed:

Registered: 24 June, 1949

Published:

Compilation Scale: 1:10000

Published Scale:

Scale Factor (III): None

Geographic Datum (III): N. A. 1927

Datum Plane (III): Mean Sea Level
(1288.5 ± USC165.1929)

Reference Station (III): STUD(USER) 1936-1947

Lat.: 48° 00' 05.384" (166.3m) Long.: 118° 41' 20.995" (435.2m) Adjusted x Unadjusted

State Plane Coordinates (VI): Washington, North Zone

X = 2,524,868.04 Y = 372,626,35

(p 210)

Military Grid Zone (VI)

PROTOGRAPHS (III)

Number	Date	Time	Scale	Stage=of=Fide
9 lens 17494 to 17498	8-22-46	12:38P.S.T.	1:10000	1289.65 above M.S.L.
U.S.Army Single lens 26-1 to 28-1	1944	Unkn ov m	1:20000	Unknown

Tide from (III): None

Mean Range: None

Spring Range:

None

Camera: (Kind or source) USC&GS 9 lens, focal length 8.25 inches

U.S.Army, Single lens, focal length 8.25 inches

Field Inspection by: J.T.Jarman

date: Summer 1947

Interior, John Winniford

May 29, 1947 June 30, 1947

Shoreline, John Lajoye

. _ .

Field Edit by: None

date:

date:

Date of Mean High-Water Line Location (III): 8-22-46

Projection and Grids ruled by (III) Washington Office date: July 1947

" " " checked by: " " date: July 1947

Control plotted by: Frank Elrod date: July 14, 1947

Control checked by: James L. Harris date: July 15, 1947

Radial Plot by: J.L.Harris & J.E.Deal date: July 28, 1947

Detailed by: Carita Wiebe date: Sept. 29, 1947

Reviewed in compilation office by: Ree H. Barron date: Oct. 9, 1947

Elevations on Field Edit Sheet checked by: None

STATISTICS (III)

(Complete detail along shoreline)

Iand Area (Sq. Statute Miles): 10 (Skeletom detail over portion of)
(Interior area)

Shoreline (More than 200 meters to opposite shore): 15.0

Shoreline (Less than 200 meters to opposite shore): None

Number of Recoverable Topographic Stations established: 2

Number of Temporary Hydrographic Stations located by radial plot: 42

Leveling (to control contours) - miles:

Roman numerals indicate whether the item is to be entered by, (II) Field Party, (III) Compilation Party, or, (VI) the Washington Office.

When entering names of personnel on this record give the surname and initials (not initials only).

Remarks:

MAP T. 8849		PROJECT NO. Fn-2(42)	CT NO.	777	- N+7.	SCALE OF MAP	- MAP	700,011	SCALE FACTOR	ביייים אר
STATION	SOURCE OF INFORMATION	DATUM	LATITU	DE OR V-C	LATITUDE OR V-COORDINATE LONGITUDE OR x-COORDINATE	DISTANCE FRO	DISTANCE FROM GRID IN FEET, OR PROJECTION LINE IN METERS	DATUM	N.A. 1927 - DATUM DISTANCE FROM GRID OR PROJECTION LINE IN WETERS	REMARKS -PACOR PRINKER -ROM GEND DR. REDECTION LIN
	(INDEX)					FORWARD	(BACK)		FORWARD (BACK)	-FORWARD (BACK)
EAST AXIS, 1933	G 6760 USBB	4	047	57.1	27.002"	834.0	(1019.2)			Used in Radial
11947	1036	1927	118	58	15.615	324.0	(920.8)			Plot
GRANITE, 1934	a:	#	°27	571	16,643"	514.1	(1339.1)			2
			318	55	127.72	4. 066	(254.1)			
-LONE PINE, 1934	G 6760 IISBR	н	64	571	58,959"	1821.0	(32.2)	-		=
	1037		118	52	26.437	7*875	(696.2)			
SPRING CANYON.	G 6760	=	470	551	16.656"	7.719	(1338.7)			=
1933 11947	1036		118	57	09.563	198.5	(1047.2)			
BASALT, 1933	u	и	470	551	52.417"	1619.0	(234.2)			=
F 1947			118	53	76,989	7.576	(270.0)	l·		
CERAND COULEE	2000	E	6 ² / ₂	551	25.705"	6*664	(1059.2)			=
1934 r1936 cuery	, K		118	59	06.190	190.8	(1054.8)			
OGBORNÉ O 1026	USBR Field	=	470	571	49.428"	1 526.6	(326.6)			#
1000 CO	Data		118	59	13.534	280.7	(964.0)			
FIDDLE CREEK	G 5299	Ħ	470	581	15.946"	492.5	(1360.7)			L
(USBR), 1934 riggy	587		119	00	47.733	0*066	(254.4)	I		
/C.P. #8 (HPOOK ± 7/ 70)	13 to 12	=	°77	571	"899 * 00	20.6	(1832.5)			1
USBR, 1934 - 1947	Comp.		118	55	27,659	573.9	(671.1)			
C.P. #19	=	-	7.7	561	48.863"	1509.2	(344.0)			#
, ,			118	52	07.257	150.6	(1094.5)			
- C.P. #10 - (Tr 261-28 02)	2	=	470	571	20.800"	642.4	(1210.7)			Not used in
USBR 1934 1947	•	:	1180	54.1	19,285	400.1	(8,44.8)			radial plot
C.P. # 12	t	. =	47	57	27.193"	839.9	(1013.2)	26.7.	33 r 1947 & plotted	=
山S照 1934 ** F. Per			1189	53#	11001 70	561 3	(480 4)			

Page 2

STATION	SOURCE OF	DATUM	LATITUDE OR y-COORDINATE	DISTANCE FR	DISTANCE FROM GRID IN FEET.	DATUM	N.A. 1927 - DATUM DISTANCE FROM GRID OR PROJECTION LINE	FACTOR DISTANCE FROM GRID OR PROJECTION LINE
	(INDEX)		LUNGITUDE OR #-COORDINALE	FORWARD	FORWARD (BACK)	NO.	IN METERS FORWARD (BACK)	IN METERS FORWARD (BACK)
C.P. #14	Field	N. A.	47° 57' 38,673"	1194.5	(658.7)			Tot used in
U.S.B.R. 1934 (1977)	comp.	1927	118 52 16,836	349.3	(895.5)			radial plot
C.P. #17 (IR591+63 60)	#	E	470 561 43.544"	1344.9	(508,3)			Pltted for hydro-
1934 - 1947			118 53 02,806	58.2	(1186.9)			graphic use.
C.P. #15 - (TE) COLES 26)	=	=	470 561 20,927"	7,979	(1206,8)			£
1934 71947			118 54 48,098	998.3	(247.0)			
C.P. #7	. =	E	47° 56' 19.896"	614.5	(1238.7)			=
1934 1007			118 58 18,145	376,6	(868,7)			
AT DHA	G 6760	=	47° 58' 00.844	26.1	(1827.1)			=
USBR) 1933 71992	1036		118 58 29,827	618.7	(625.9)			
C.P. #4		-	E 103,940.05				1934 Grand Coulee	(Not recovered
ULIVATO7.50)			N 93,988.38				Grid Datum	plotted to estab-
9# 'd '0			E 108,460.80				Origin Alp hin 1933	USBR reservation)
(UL158+03.03			N 93,263.21				-	E
C.P. #3		_	E 95,368,57					=
(UR95+61.68)			N 919,67					
C D ##			E 97,829,23					=
(UR211+64.65)			N 94,846,99					
b# d 0			E 101,775,25					=
(ur2994,6.90)			N 89,271,40			•		
(P #31		_	E 104,271,52					=
(ur331+40.79)			N 87,468.56			****		
C.P. #13			E 110,209,01					=
(TIB 208±1032)			N 88 330 27					

TROPIC NO.
LATITUDE OR V-COORDINATE LONGITUDE OR x-COORDINATE
44.446"
42.034
55.150"
02,363"
31.040"
01.709
25.424"
51.371
28,686"
35.728
55.044"
12,306
51.343"
44.276
02:909"
31.943
23.299#
28.110
07.235#
18,559
54,925
53.741
33,320
02.951

TACTOR DISTANCE PROMORED OF PROMORED IN METERS USBR reservation) in the PORTERNO - - CONCR. plotted to establish boundary (Not recovered Not used in Radial Plot REMARKS None = Ξ. July, 1947 ≂ = Ħ = SCALE FACTOR FROM GRID OR PROJECTION LINE 1934 Grand Coulee Origin Alpha 1933 (BACK) N.A. 1927 - DATUM from DATE.... Kron DISTANCE Grid Datum FORWARD Duplicated Duplicated 7996 Pope CHECKED BY. Carita Wiebe CORRECTION DATUM SCALE OF MAP 1:10,000 OR PROJECTION LINE IN METERS DISTANCE FROM GRID IN FEET, (1183.5)(8.6%) (824.0) (156.7)(129.8) (928.1)(550.4) (874.2) (147.5) (41.8) (843.1) (41.6) (BACK) FORWARD 925.0 61.2 402.7 371.4 903.4 1811.5 1696.4 1114.8 1302.7 1029.1 1203.4 1098.1 LONGITUDE OR x-COORDINATE LATITUDE OR V-COORDINATE 29.950" 58,652" 54.925" 33.320" 42,178" 29.248" 57.987 52.894 July, 1947 53.741 17.889 19.394 02.951 73,897,38 146,953.92 83,419,87 PROJECT NO Ph-2(45) 80,759,70 77,024.65 140,941,19 151,492.97 155,190.20 571 167 541 571 561 55. 551 63 S S 49 87 67 ¢7.0 470 470 7.40 470 470 118 118 118 118 118 118 ഥ Εď 闰 \mathbf{z} 臼 \geq DATE. DATUM N.A. 1927 = ≖ . = E = SOURCE OF COMPUTED BY. J. L. Harris Field (INDEX) Comp. = E ± Ħ = **z** 8850 (UR712 + 44.12) USBR, 1934 (194) USBR, 1934 (114) C.P. #25 USBR. 1934 C. (1942) USBR, 1934 C.19 1/2 USBR, 1934 //// USER, 1934 C/PK ~(UL649.+ 61.45) (41766 + 21.15) (UL520 + 19.80) ~(UR810 + 56.85) (UR874 + 80.33) (UL 710442.26) (UR1063435.08) (UR1114+09,93) (m921+23.32) 1 FT. - 3048006 METER MAP T-STATION 7c. P. 35 C.P. #21 C.P. #24 C.P. #27 VC. P. 26 7C.P. 33

<u>,</u>

Page 2

MAP T. 8851		PROJECT NO. PB-2(45)	ON TO	-H-H	2(45)	SCALE OF MAP		1:10,000	SCALE FACTOR	OR None
STATION	SOURCE OF INFORMATION (INDEX)	DATUM	LATITI	LATITUDE OR v-COOF LONGITUDE OR x-COO	LATITUDE OR V-COORDINATE ONGITUDE OR x-COORDINATE	DISTANCE FRO OR PROJECTION FORWARD	DISTANCE FROM GRID IN FEET. OR PROJECTION LINE IN METERS FORWARD (BACK)	DATUM	N.A. 1927 - DATUM DISTANCE FROM GRID OR PROJECTION LINE IN WETERS FORWARD (BACK)	REMARKS ***********************************
POIL	G 6760 USBR	N.A.	027	571	53.936"	1665.9	(187.3)			Used in Radial
I.S. No. 2, 1935	1049	1927	118	07	11.323	234.9	(1009.8)			Plot
	=	=	470	571	13.681"	422.6	(1730.6)			=
I.S. No. 1, 1935	- 1		118	43	21,365	443.3	(801.6)			
CLARKE	G 6760 ISBR	=	470	551	14.527"	448.7	(1404.5)			#
1934 61847	1032		118	39	16.999"	352.9	(892.8)			
DEVITS CANYON	0949 D	=	470	531	50.995"	1575.0	(278,1)			
- L	1037	-	118	43	28.847	599.2	(647.1)			
PENIX CANYON	0949 0		470	551	00.592"	18.3	(1834.8)			Ħ
	1038		118	37	53.716	1115.3	(130,5)			
(TEP/1 + 18 70)	អី ខេរិស	ŧ	470	571	39.971"	1234.5	(618.6)			=
ത	Comp.		118	41	46.719	969.5	(275.5)			
(m.928 + 07.64)	=	*	470	551	42.473"	1311.8	(541.3)			B
1934			118	42	52.113	1081.8	(163.7)	•		
C.P. #38 - S.P.# (UI)124 + 43.14)	=		470	561	45.348"	1400.6	(452.5)			=
1934			118	391	48.313	1002,6	(242.5)			
C.P. #40 -(1188 + 68.36)	ε	ŧ	470	561	21.123"	652.4	(1200.8)			Úsed in
13			118	38	24.015	7*867	(746.9)		*	Radial Plot
7 C. P. #41 UR1381 + 64.17)	=	=	7.70	551	36.162"	1116.9	(736.3)			Used in Redial
T N			118	41	19.829	9.117	(833.9)			Plot
- HE L	2	=	470	351	16.448"	508.0	(1345.1)			Wed in
- 2			118	38	02,590	53.8	(1191.9)			Radial Plot
C.P.S.P.#3 (SS)	, =	=	470	571	34.430"	1063.4	(789.8)			Used in Radial
			118	41	00,459	9.5	(1235.2)			Plot
IFT. 3048006 NETER COMPUTED BY	Harris	V DA	TE JY	DATE Junes 1947	171	CHE	CHECKED BY. Carita Wiebe	a Wiebe	DATE 17 J	DATE 17 JULY 1947 GPA WAS
										,

Page 2

MAP T.	8851 p	PROJE	PROJECT NO	Ph-2(45)	(45)	SCALE O	SCALE OF MAP 1:10,000	000,01	SCALE FACTOR None	OR None
Z	SOURCE OF INFORMATION (INDEX)	DATUM	LATITUDE	LATITUDE OR "-COORDINATE LONGITUDE OR "-COORDINATE	ORDINATE	DISTANCE FRO OR PROJECTION FORWARD	DISTANCE FROM GRID IN FEET. OR PROJECTION LINE IN METERS FORWARD (BACK)	DATUM	N.A. 1927 - DATUM DISTANCE FROM GRID OR PROJECTION LINE IN METERS FORWARD (BACK)	REMARKS - Prevor despare From the transfer emergence of the properties of the prope
+ %	Field Comp.	N.A. 1927	470	541 3	39.699" 15.638	324.7	(627.0)			Not used in Radial Plot
C.P.S.P. #7(8S) USLP903 + 43.23 USBR, 1936 (AV)		£			45.371" 39.458	1401.3	(451.8)			
de ser										
`										
V ₁							i in			
					į					
27										
I FT = 3048006 METER COMPUTED BY:	J. I. Harris		DATE JULY, 1947	7, 1947		CHEC	СНЕСКЕВ ВҮ: С.	Carita Wiebe		DATE 17 JULY 1947 CON GL

					0				- 5
MAP T- 8852	PRO	PROJECT NO. Ph-2	Ph-2	(45)	SCALE	SCALE OF MAP 1	1:10,000	SCALE FACTOR	OR None
STATION SOURCE OF INFORMATION (INDEX)	DATUM		LATITUDE OR y - (COORDINATE -COORDINATE	DISTANCE FRO OR PROJECTIO	DISTANCE FROM GRID IN FEET, OR PROJECTION LINE IN METERS FORWARD (BACK)	DATUM	N.A. 1927 - DATUM DISTANCE FROM GRID OR PROJECTION LINE IN METERS FORWARD (BACK)	REMARKS PACTOR PRITANCE FROM GING OF PROFESSION-LINE IN METERS FORWARD—— (BAGCK)
HARLINDA, 1936 USBR	A M	087	01.	51,219"	1582.0	(277.2)			Used in Radial
			07	38.564	799.0	(444.1)			Plot
DICE, 1936 G 6760	=	480	100	56,267"	1737.9	(115.3)			п
,		118	39	31.407	620.9	(592.5)			
936	-	87	170	54.580"	1685.8	(167.4)			п
		118	70	22,293"	461.4	(780.4)		N. of mer. 0100	
936	0	780	100	05.384"	166.3	(1686.9)			=
		118	17	20,995	435.2	(808.5)			***
D O V		687		38,001"	1173.7	(679.5)			=
1936 (1947) 1050		118	39	57.979	1200.5	(41.8)			
WATSON, 1936 "	=	480	031	40.099	1238.5	(614.7)			=
r 1047		118	39	19,622	406.3	(836.0)			
(III.SP198 + 58 38) Field	=	480	100	05.233"	161.6	(1691.5)			=
17000	5.	118	41	179.50	117.6	(1126.2)			
	=	E 172	097	.26	6.672	(774.1)	<u></u>	1034 Canad C Inc	Not recovered
USBR 1936			831	86	558.4	(965.6)	nel	Grid Natura	plotted for use by hydrographic
C.P.S.P. #14	=	王 174	654	66	1418,8	(105.2)	ers	100	party
		N 120	978	.62	298.3	(1225.7)			
C.P.S.P #16	=	E 174	589	.22	1398.8	(125.2)	To		
		N 126	691	45	515.6	(1008,4)			
(Treprostrance) "	=	E 175	673.	.32	205.2	(1318.8)	91		=
USBR 1936		TEL N	607	4.2	6.687	(1034.1)	id		
(ITSP/68m15 42) #	=	E 174	352	.70	13267	(197.3)			п
200		N 136	731.	09	527.8	(996.2)	>		
COMPUTED BY LA LA HARRIS	to	DATE	June, 1947	176		снескер ву. Саг	Carita Wiebe	DATE	July, 1947 cm

	_		_	_	-	_	
STATION	SOURCE OF INFORMATION (INDEX)	DATUM	LATITUDE OR y-COORDINATE LONGITUDE OR *-COORDINATE	metus DISTANCE FROM GRID IN FEET. OR PROJECTION LINE IN METERS FORWARD (BACK)	F. DATUM	N.A. 1927 - DATUM DISTANCE FROM GRID OR PROJECTION LINE IN METERS FORWARD (RACK)	FACTOR DISTANCE FROM GRID OR PROJECTION LINE FORWARD (RACK)
P. #9	Field	N	E 173 857.84				ere
(ULSF 024+/1.00) USBR 1936	·dillo	1361	N 108 798.26		-		plotted for use
C.P.S.P #11	п	=	E 173 229.86	984.5 (539.5)			by nyurographic party
		!	N 113 749.34	1142.8 (381.2)			=
C.F.S.P. #13	ı.	=	175		1		, 11
USBR 1936			N 117 974.15				
C.P.S.P. # 15 (U.SP75494.44)	=	=	E 176 058.08		(:		t t
USBR 11936		-	N 122 874,76	876.2 (647.8)			
C.P.S.P. #17	F	·=			 		=
USBR 1936			125				
C.P.S.P. #19	t	¥	E 176 440.08)		=
USBR 1936			N 129 218,69	1285,9 (238,1)			
(TrSP552+83,77)	=	=	第 176 \$19.08	(1061.0))		11
USBB:1926			N 132 989.76	(612.7)			
,							
	•						
3		_ -					
					•		

FIELD INSPECTION REPORT Area of the First Radial Plot Project PH-2(45)

1. Description of the Area:

This report pertains to the area of the first radial plot encompassed by the 4 shoreline surveys numbered 8849 to 8852 inclusive along the Franklin D. Roosevelt lake from Grand Coulee Dam eastward to and including the San Poil River. It should be noted, also, that this report is applicable, in part or in whole, under some of the side headings to the Project as a whole, and should be regarded as the leading report to which the remaining 6 descriptive reports will be referenced. The Project was sub-divided logically into 7 radial plot units to facilitate the field work and the subsequent compilation of the shoreline surveys.

A General Description of the Project Area:

The artificial lake or storage reservoir upstream from the Grand Coulee Dam extends 151 miles up the Columbia River canyon to the Canadian border at which point the elevation determined the height of the Dam; in addition, the reservoir extends 32 miles up the Spokane River, 14 miles up the San Poil River, and 8 miles up the Kettle River. The storage reservoir covers an area of 128 square miles with an estimated total capacity of 10 million acre-feet of water. The Lake averages about 0.8 mile in width with a maximum depth of 400 to 450 feet.

The normal water level of the Lake is 1290 feet above M.S.L. based on the 1937 USER Datum of Leveling; this normal water table extends upstream from the Dam for about 115 miles before any appreciable gradient is noticeable. Since the water level was raised about 300 feet above the old river level, all lands (mostly privately owned) in the river basin above the dam site and below elevation 1310 (referred to as the "Taking Line") were surveyed, appraised, and acquired by the Government for reservoir purposes before the waters were impounded. Chiefly grazing and pasture lands, and cut-over timber sites were affected. The old townsites of Keller and Kettle Falls were imundated. Several highways and railroads were relocated including the removal of numerous indian graves. The "Taking Line" referred to above is a series of short transit-traverse lines run approximately on the 1310-foot contour line.

The drainage basin of the Columbia River above the Grand Coulee covers an area of 74,100 square miles. Among its principal tributaries are the Kootenai, Clark Fork, and Spokane Rivers; the first two rivers join the Columbia 30 miles and 0.5 mile north of the international boundary, respectively; the latter River joins the Lake about 45 miles east of the Dam. The San Poil and the Kettle Rivers are minor tributaries. Its headwaters are in the high mountain snows, lakes, and ice fields of British Columbia.

The Lake meanders through a deep and wide canyon. Between the Spokane River and Grand Coulee Dam, old and rolling granitic mountains are found on the north side of the Lake. On the south side, it is marked by steep perpendicular walls of basalt with lava-plains on top; inland of this

basalt formation is the wheatland belt. North of the Spokene River, the reservoir area is surrounded by low timber-covered mountains with with narrow grass or timber benches adjoining the Lake in many places.

A Description of the First Radial Plot Area:

The Grand Coulee Dam, on the Columbia River, is located at the head of the Grand Coulee, a prehistoric diversion channel which was formed when the flood waters pouring down the Columbia River canyon were blocked by glaciers. The Dam is the largest man-made masonry structure and the highest spillway dam in the world. It is of the straight-gravity type and depends entirely upon its massive weight to resist the pressure of the impounded waters. The length at the crest is 4300 feet, 3000 feet at the base, and 550 feet in height above bedrock. It has a base thickness of 500 feet and tapers to 30 feet at the top. The center section consists of a 1650-foot spillway with a powerhouse and abutment section on each side. Il drum gates at the crest of the spillway and 60 outlet tunnels, 20 each at three different elevations, control the rate of flow and the amount of water held in storage. The Dam is spanned by concrete arch bridges and a highway which extends the entire length of the dam at the top.

To accomodate the Bureau employees two towns were built near the dam site. Coulee Dam, commonly known in the past as "Engineer's Town", was constructed as a permanent town just below the Dam on the west side of the river by the Bureau of Reclamation. The other town was Mason City; It was opposite Coulee Dam on the east side of the river. Built by a contractor, it was originally designed for temporary use to be dismantled when the Dam was completed in 1942; however, the two towns have been consolidated into one town site which now is officially known as Coulee Dam. Grand Coulee is another small municipality located on the heights just north of and above the dam site. A post office and store, 7-8852 and a few buildings mark the new site of Keller at the north end of the San Poil River reservoir.

There are no major U.S. highways in this area. State Highway 4 from Wilbur crosses the Lake at Keller Ferry, which is near the mouth of the San Poil River, and continues northward paralleling the west side of the River. State Highways 2, 2F, 1QA, and 10B all radiate out of Coulee Dam. A few gravel and dirt roads provide limited access to the Lake. There is no passenger railroad line in the vicinity. A spur freight line, the I.D.B.R., runs from the Northern Pacific Railway line at Odair to the dam site, and is operated by the Bureau of Reclamation. The Grand Coulee Navigation Company with headquarters at Davenport, Wn., maintains a daily passenger service on the Lake between Miles, Wn., near the mouth of the Spokane River, and Coulee Dam. An air-taxi is available at Coulee Dam; it is operated by the Amphibicus Aircraft Association.

On the south side of the Lake, the zone adjacent to the water is interspersed with sedimentary pockets and large granite cutcrops. The vegetation consists of sagebrush and greasewood with a scattering of stunted pine trees. Immediately to the south and above this zone is a high lava-flow formation of basalt which parallels the Lake. It is deeply incised by small canyons and valleys, draws and drywashes. Almost throughout the entire length of this formation, the walls of basalt rise vertically or in steep grades for several hundred feet either from the Lake

or just inland as the result of canyon-excavation by glacial and flood waters in the past. From the Lake and to the northward they can be seen as black escarpments. The lava-plains or benches, which have weathered into soil, on top of the layers of basalt are covered with sagebrush and native grass; its topography is rolling. Inland from the basalt formations and extending southward, the area is a large rolling wheat-land plain.

On the north side of the lake, a rugged and rolling range of granitic mountains rises abruptly. Its thin soil supports a growth of small pine, sagebrush, and greasewood. An occasional agricultural plateau or basalt outcrop is found; they stand out as isolated tracts between the lake and the mountains to the north. The massive granite bluffs and ledges, found found along the edge of the shore are very irregular; the terrain is rugged and, in several areas, they are sheer bluffs that loom above the lake. Disintegration by weathering action has deposited rocks and boulders along the shoreline and on the granitic slopes.

Alluvial fans with flat benches on top are found on both sides of and adjacent to the Lake; their banks are generally steep and sloping. In the alluvial areas the soil composition is sand and gravel. The vegetation consists of sagebrush, greasewood, and a few scattered pine trees. Behind the alluvial benches rise the black basalt escarpments or the granitic mountains.

There are numerous coves and inlets found along the lake shore with draws and small canyons extending inland. The well defined drainage pattern that is so evident on the photographs is a remains of an earlier geologic period of heavy rainfall. No drainage should be shown unless noted as such by the field inspector on the field photographs.

The topography of the SamPoil River, which drains from the north, is similar to that on the north side of the Lake; it has little or no relationship to the south side.

The Lake, in addition to providing hydro-electric power for domestic and industrial use, flood control, and irrigation for the Columbia Basin Project, has potential possibilities for the development and use of its navigable waterway.

For additional information refer to side heading 3.

2. Completeness of Field Inspection:

The field inspection for the clarification of details on the photographs, and for the classification and identification of roads, shoreline, buildings, et cetera, has been completed in accordance with the instructions for this Project dated 3 April 1947 with a few modifications that were minor.

Although the instructions made no mention of interior field investigation (except for cultural features visible from the water) for skeleton details such as roads, railroads, landmark buildings, major drainage and other bodies of water such as lakes and ponds, it was found that an inspection of these features, which was done concurrently with the geographic names investigation, was necessary for the following reasons:

- a. The project instructions requested that a complete and thorough field investigation be made to ascertain all the names in local usage. Since the area within the limits of this Project is comparatively undeveloped, it was felt that the natural and cultural features mentioned in the second paragraph would require investigation in the course of ascertaining and identifying new names and names in local usage.
- b. Existing maps were found to be very inadequate with regard to geographic names, topography, and culture. Many of the geographic names dealt with drainage which did not appear on the maps at all. In view of this, the field inspector on geographic names was instructed to identify and note the correct location of the geographic names on the field photographs.
- c. In rural and undeveloped areas, the names of schools, churches, roads, et cetera, are important since in many cases they are locality names or names that are in extensive local usage.

Sundry maps have been obtained to supplement the field work for the project area.

3. Interpretation of the Photographs:

Each type of vegetation, rock formation, and any other characteristic has been classified a sufficient number of times on the photographs so that the photographic detail should be interpreted correctly by the office personnel.

The following information will assist the draftsman in photographic interpretation:

Vegetation:

- a. Pine covered lands the pines are easily recognized by their black conical shapes, and are found well apart on the ground.
- b. Sagebrush lands sagebrush is usually found with native grass in the field, and is identified by a light and mottled tint. It almost gives the appearance of merging with a slightly lighter or darker background. It is very difficult to identify an individual sagebush.
- c. Greasewood the individual greasewood bush can be readily identified as a small dark spot - usually against a light background.
- d. Native grasslands grasslands show as a light grey tint and when mixed with sagebrush, as is often the case, it is very difficult to distiguish between the two.

Rock Formations and Outcrops:

a. Basalt formation - a dark lava-flow found in large horizontal layers. It shows as a fairly uniform black toned area (striated) shading to a dark grey. On the south side of the lake, a single formation of basalt may be traced, in many cases, for a distance

of several miles at an almost constant elevation above the Lake.

- b. Talus slopes where basalt formations have been incised by streams, numerous vertical bluffs will be found. The talus slopes are found below these bluffs and like their parent rock they are dark grey to black in color. They consist of rocks from 6 inches to 2 feet in diameter which have broken away from the main basalt formation and have come to rest in a slide-like area.
- c. Granitic outcrops light colored rocks which have been exposed by the erosive action of streams and weathering. Granitic outcrops range from dark grey to grey; they are of irregular formation, mottled in appearance, and studded with small trees and bushes. There is a complete absence of any large, continuous, horizontal exposure.

Scablands:

a. A lava-plain exposure of basalt sparsely covered with patches of sagebrush and native grass. A typical example of such an area is the high plateau southeast of the town of Grand Coulee.

Other characteristics:

- a. Slide areas along the shore are identified by their light uniform pattern against a darker background.
- b. The shoreline is readily identified by the contrast in color between fast land and water.

Distortions and Displacements:

- a. Because of excessive relief, the distortions and displacements are exaggerated on the photographs.
- b. Any slope facing away from the picture center will tend to be telescoped, and the effect will be exaggerated as the steepness of the grade and/or as the distance from the picture center increases.
- c. Any slope facing toward the picture center will be exaggerated, and the effect will be increased as the slope and/or as the distance from the picture center increases.

4. Horizontal Control:

It was not necessary to establish any additional control. Recovery notes on Form 526 have been prepared for the few USC&GS stations in the area of the first radial plot. The majority of the stations recovered were established by the Bureau of Reclamation.

All the USBR stations that were recovered and identified for the control of the radial plot are of third-order accuracy or better, except for one or two cases. These cases refer to some of their intersection stations, e.g., natural objects such as lone pines, that were classified as of third-oreder accuracy. It is believed that stations of this type should

be classified as topographic stations since they do not fall in the category of well defined objects. A notation on the pricking card was made of the few stations in this category that were recovered and identified on the field photographs.

Original descriptions were obtained from the Bureau of Reclamation for the reservoir boundary control points (these are marked stations) tablished by them along the "Taking Line". For information on the "Taking Line" refer to side heading 1, paragraph 3. These stations were established in accordance with the USC&GS requirements for third-order control. In most cases, they are near the water's edge and about a mile and a half apart. A search was made for most of these stations and a sufficient number of them have been identified to control the plot; thoses that were recovered but not identified were noted on the field photographs to be plotted for hydrographic use. Since these CP stations in this area are on an independent plane coordinate system (1934 Grand Coulee Grid Datum). the geographic positions for them have been computed. North of the Spokane River, these stations are on the Washington North State System of Plane Coordinates. For additional information on these stations refer to "Special Report on Reservoir Boundary Control Points. Project PH-2(45)". Filed in Library & Archives under GTZ 7380.

Recovery notes on Form 526 have been prepared for all USER stations that were recovered or searched for, and in the case of a reservoir boundary control point, a photostat copy of the original USER description will be submitted along with the recovery note.

With this additional control along the lake shores, all the inland USBR control stations were not searched for as specified in item 12 of the instructions for this Project because of the time and expense involved in recovering them. Most of these stations are inacessible by truck and require on an average 3 hours to pack to and from the station; this includes the recovery and identification of it.

Some difficulty was encountered in the field in identifying substitute stations that would be plainly visible on other photographs because of insufficient overlap between photographs or else all the photographs had not been made available for field use. In some instances, it was not possible or practical to identify well defined objects which would not be obscured on some of the overlapping photographs in this area with an irregular and rugged terrain that predominates in high relief. It is believed that more than a sufficient number of stations have been identified to offset the difficulties described above so as to adequately control the radial plot.

5. Vertical Control:

The recovery of vertical control is being accomplished in accordance with the supplemental instructions dated 15 May 1947. Since this phase of the work is independent of the field work on shoreline surveys, it will be the subject of a special report to be submitted at a later date.

Sent 2 0.56.5 Dec. 8, 1947.

6. Contours and Drainage:

No contouring is involved in the project area.

Major drainage was located and classified in the field concurrently with

the geographic names investigation. For additional information see side heading 1, next to the last two paragraphs, and side heading 2, paragraph 2.

7. Shoreline Plane of Reference:

The term "Shoreline Plane of Reference" was used in place of "Mean High-Water Line" as the more appropriate side heading.

The U.S. Bureau of Reclamation maintains a normal water level of 1290 feet above M.S.L. at the dam site. This elevation is based on the 1937 USBR Datum of Leveling which is referred to their fixed elevation of 1123.752 feet for FM Osborne #2 located near the Administration building in Coulee Dam. The USC&GS adjusted elevation for this EM is 1122.327 feet.

This normal water table extends upstream from the Dam to Marcus, a distance of about 115 miles. Between this point and the international boundary, there is a gradient which is gradual at first but increases as the Canadian line is approached.

The photographs were taken when the water level was close to normal. Except for an occasional confirming note and the delineation of the shoreline where it was less well defined, it can be identified as seen on the photographs.

The following are the reservoir elevations at the Dam on the dates and times indicated; there were no great fluctuations at any hour of the day during or between these days:

			8:00AM	4:00 PM	12:00 Midnight
7	August	1946	1289.67	1289.67	1289,60
8	11	**	•59	.59	•60
9	Ħ	Ħ.	•56	•52	•52
21	11	n	.6 8	•63	. 65
22	11	Ħ	.67	•63	•63
27	n .	11	. 60	•67	.70
8	Sept.,	27	•53	.51	•54

U.S. Army single lens photographs (1:20,000), which were obtained from the Bureau of Reclamation, have been submitted to the Portland Photogrammetric Office to facilitate, if necessary, the interpretation of the shoreline in conjunction with the 9-lens photographs along those areas where the shoreline is not well defined because of pronounced displacements due to relief, and distortion. In a few instances, the shoreline inspection party has found it difficult to distinguish the shoreline because of this which resulted from insufficient field photograph coverage.

These photographs were borrowed from the U.S. Bureau of Reclamation and will have to be returned, eventually. Permission was granted by them to use these photographs for any necessary field inspection or office use. The exposures were taken with a camera focal length of 8.25" at an altitude of 13,750' in the year 1944; the exact date is not known, as they were flown secretly by the Army who did not divulge the date.

It is believed that the shoreline has not changed any, except where

slides have occured. A visual comparison of the lake level between the single lens and the 9-lens photographs was made; the lake level seemed to be the same.

8. Low-Water Line:

In general, only the approximate limits of shoal areas were indicated during the shoreline inspection in the field which was supplemented by a close study of any under-water discolorations that were visible on the photographs.

9. Wharves and Shoreline Structures:

There were no wharves or shoreline structures in the area except for several floating docks, boathouses, or booms near the Dam and Keller 7-885/Ferry.

10. Details Offshore from the Shoreline Plane of Reference:

A few offshore rocks have been noted on the photographs. No other offshore obstructions were found.

11. Landmarks and Aids to Navigation:

A selection of the most prominent objects along the shore was made and these were recommended for future charting. In addition, objects of lesser prominence were recommended because of a paucity of landmarks.

A complete investigation of all fixed aids to navigation was made in the field. They were either identified on the photographs if visible or located by sextant fixes and their correct names were verified from the latest edition of the "Light List - Pacific Coast". No discrepancies were found in the Light List with regard to their distinctive markings, et cetera.

One fixed aids to navigation "San Poil Daybeacon 10," was found destroyed. 7-985/
It was noted, also, that the lights and daybeacons in the 1947 edition
of the "Light List - Pacific Coast" were listed under Coulee Lake in the
sections on "Lights and Fog Signals", "Unlighted Buoys And Daybeacons",
and the "Index". This is incorrect as the official name is "Franklin D.
Roosevelt Lake". In accordance with the memorandum instructions, No. 6,
dated 30 December 1946, Mr. Heck of the Division of Charts has been notified of the name discrepancy and the daybeacon which was found destroyed.

All landmarks recommended for charting and fixed aids to navigation have been reported on Form 567 as well as on Form 524. (See 34, Compilation Report)

12. Hydrographic Control:

Photo hydro stations were established in accordance with the instructions for this Project. In areas of overhanging bluffs or cliffs and in areas where there were no identifiable objects on the photographs, photo hydro stations were established by sextant fixes taken to other control stations (photo hydro and triangulation stations in combination) with a check angle taken in each instance.

This practice of locating a photo hydro station by a sextant fix taken

to other photo hydro stations was discontinued in the second radial plot. This is in accordance with the letter on the subject of locating photo hydro stations from the Acting Director dated 9 July 1947.

The photo hydro stations were designated and described briefly on the field photographs in accordance with the instructions. In addition, they have been listed and described, including any sextant fixes, in two sketch books, volumes 1 and 2.

13. Landing Fields and Aeronautical Aids:

A small private seaplane base "The Amphibious Aircraft Association" is located just upstream from the Dam on the east side of the Lake. T-8849 (Only hanges delineated flobeled)

14. Road Classification:

All through or connecting public highways, and roads or major trails leading from such highways which provide access to the Lake, have been classified in accordance with the memorandum instructions, No. 10, dated 14 April 1947. All other roads such as field roads, and temporary logging roads or trails were not classified and should not be shown.

Since this phase of the work was done concurrently with the geographic names investigation, the names and numbers of through roads such as state highways were obtained and noted on the field photographs. Only a few roads are found in this area.

15. Bridges and Cable Crossings:

There is one bridge in the area; it spans the Columbia River just below the Dam.

Name: None

Location: Coulee Dam, Wn.

Owner: Washington State Highway Commission

Kind: Fixed

Number of Spans: 1

Channel Span: - Horizontal clearance - 550 feet

Vertical clearance of lowest part above MIN - Not applicable

MHW - 90 feet

Purpose of Bridge: Highway

Date of Field Measurements: 5/22/47 (Hor. Cl.)

Remarks:

Since the river level in the vicinity of this bridge near and downstream from the site of the Dam is not constant, The vertical clearance was not determined in the field. Mr. George Owens of the Bureau of Reclemation in Coulee Dam was consulted and the average minimum clearance (vertical) was determined from the following data; this clearance is considered to be a better determination than could be obtained by a field measurement:

- a. The elevation at the center of the bridge span is 1061.75 feet above MSL based on the 1937 USER Datum of Leveling. For information on this Datum refer to side heading 7, paragraph 2.
- b. The average maximum elevation of the river level at the bridge is: 971.8 feet above MSL based on the same Datum as in item a. There is an automatic recording gage at the bridge zeroed on this Datum.

c. The average minimum vertical clearance is, therefore, 90 feet.

There were no overhead or submarine cable crossings over navigable waters within the limits of this area.

16. Buildings and Structures:

A complete field investigation was made of all buildings and structures along the waterfront. Inland only those buildings and structures were identified that were visible from the water.

17. Boundary Monuments and Lines:

In accordance with the Acting Director's letter dated 27 June 1947, on the subject "Plotting of Boundary - Roosevelt Lake Reservation", ozalid prints of the USBR Index Maps SP 1, SP 2, and 1 to 5 inclusive have been obtained from the Bureau of Reclamation for the purpose of plotting the boundary limits of the reservoir. The Bureau has indicated plainly in red and supplemented by pertinent notes on the ozalid prints any changes in their original reservoir boundary line or commonly referred to as the "Taking Line". For the symbol used to indicate the original reservoir boundary lines on the index maps refer to the legend shown on Index Map No. 1. Refer to side heading 1, paragraph 3 for additional information.

Since the Bureau of Reclamation's "Taking Line" was surveyed only at an approximate elevation of 1310 feet, the Land Office at a later date determined by surveys the actual 1310-foot contour line along those areas where the "Taking Line" was common to indian reservation lands and the reservoir lands of the Bureau of Reclamation. As a result discrepancies were found which were adjusted out by a Congressional act. The acquisition of additional property, also, has altered the reservoir boundary lines. These new changes in the boundary line have been shown in red as mentioned in the first paragraph.

18. Geographic Names:

The investigation of geographic names for the Project area will be the subject of two special reports. The first report will include 11 shoreline surveys numbered 8849 to 8859 inclusive; the second report will be for the remaining 13 shoreline surveys numbered 8860 to 8872 inclusive.

For additional information refer to side heading 2.

20. Ferries:

One ferry crossing, the Keller Ferry, was investigated and noted on the field photographs. It is state owned and operated on the Lake proper 7-885/ near the mouth of the San Poil River.

21. Field Photographs:

The junctions between field photographs and the legibility of the inked notes as well as for the completeness of the field inspection work have been checked by the field inspectors.

No attempt was made to indicate the limits of each sheet on the photographs.

Not drown on 1.8851

For the photographs used for field and shoreline inspection refer to the Data Record, Form No. T-1.

22. Symbols and Color Scheme:

Standard symbols were used on the field photographs for ground and photogrammetric points. The symbolization on the shoreline inspection work was done in accordance with the "Supplemental Instructions - Shoreline Inspection" dated 18 March 1944. Perennial and intermittent drainage was indicated by conventional symbols.

Red ink was used for shoreline, ground and photogrammetric points (photo hydro stations were noted in blue ink in accordance with item 17 of the Project instructions), culture, and general notes. Blue ink was used for drainage and green for deletions.

Approved by:

T. Jaiman,

Chief of Party

Respectfully submitted:

Charles Honasich Charles Hamavich,

Topographic Engineer

COMPILATION REPORT Map Manuscripts T-8849 to T-8852 Inclusive Area of the 1st Radial Plot Project Ph-2(45)

26. Control

Thirty-nine horizontal control stations were recovered and identified by the field parties for use in controlling the radial plot in the area of these four map manuscripts.

Since the field inspection party was furnished only every other nine lens field photograph, in any flight of photographs, they could not comply with Paragraph 13 of the Instructions dated, 3 April 1947. Therefore, when an attempt was made to prick the objects, selected as substitute stations for horizontal control stations, on the office photographs, much difficulty was encountered. Twelve of the thirty-seven identified stations could only be seen on the photograph on which they had been identified by the field party. Of the remaining twenty-five stations, sixteen were plainly visible on a majority of the photographs on which they appeared, but the remaining nine could be identified with surety on not more than two or three office photographs.

The above difficulties were attributed to the fact that the field party, in most cases, selected bushes and other small objects as substitute stations. While these objects were clear and definite in the center chambers, they could not always be identified in the outer chambers of overlapping photographs. Also, many of the objects selected were eliminated, in the outer chambers of adjoining photographs, due to the large amount of displacement caused by decided relief in the area. These difficulties will not occur in succeeding radial plots for this project; as the field party was notified about the trouble encountered and instructed to select more prominent objects for substitute stations.

Insufficient end lap in line of flights also contributed to the difficulty of identifying control and hydrographic signals. In many places it was impossible to obtain stereoscopic vision when viewing a stereoscopic pair. This meant that the use of the stereoscope was limited when transferring signals from one photograph to another. (See paragraph two of letter 711-rs, dated 23 September 1947, on the subject of photographs.)

All horizontal control stations which were recovered by the field party were plotted on the map manuscripts. As stated in item 4, paragraph 5 not of the "Field Inspection Report-Area of the First Radial Plot," all USBR second order stations were not recovered.

Several USBR triangulation stations which were not recovered have been plotted on the map manuscripts. In these cases the stations were needed to control the F. D. Roosevelt Lake reservation line, which was transferred from index maps to the map manuscripts. (This reservation line was plotted prior to receipt of letter 711-rs dated 7 November 1947 to Lt. Comdr. Jarman, stating that it was to be omitted.)

All horizontal control stations shown on these four map manuscripts are listed on several sheets of Form M-2388-12, which are attached to this descriptive report.

27. Radial Plot:

Radial Plot No.1, Project Ph-2(45), covers the four map manuscripts included in this descriptive report. The photographs were prepared in the following manner:

- (1) Conjugate centers were transferred to overlapping photographs.
- (2) Azimuth and cross azimuth lines were plotted on all photo. graphs.
- (3) All horizontal control stations or substitute stations, which were identified by the field inspection unit, were pricked on all photographs on which they appeared. (See information contained in this descriptive report under Item 26, Control.)
- (4) Well defined pass points, which would be cut in during the running of the radial plot, were then selected and pricked on the office photographs, and radial lines to all points were drawn.

Templets were then made on sheets of clear acetate in accordance with Photogrammetry Instructions No. 11, dated 2-28-47, "Corrections to Radial Directions on Nine Lens Photographs for Radial Plotting." Inks of various colors were used to designate the azimuth and cross azimuth lines, and the radial lines to horizontal control stations, topographic stations, and pass points.

Four polyconic projections, ruled on acetate, were furnished this office, for use as map manuscripts. On these, all horizontal control stations which were recovered and their substitute stations, if they were identified, were plotted. Standard Symbols, listed in Photogrammetry Instructions No. 12 dated 3-17-47, were used to indicate all stations.

After all plotting was completed and checked, the four map manuscripts were placed on the large radial plot table and joined together by matching common meridians and parallels. Clear cellulose tape was used to hold the four sheets together.

The templets were oriented directly on the four joined map manuscripts. As many of the horizontal control stations were doubtfully identified on the photographs; notes pertaining to the accuracy of identification were lettered on each templet near the radials to said control stations. Those templets, which contained several clearly identified and well distributed horizontal control stations and which could be rigidly fixed, were then oriented. The remaining templets were oriented by holding to clearly identified control stations, azimuth lines, cross azimuth lines, and pass points which had been established by orienting the rigidly fixed templets. In this manner we could usually determine which of the horizontal control stations were incorrectly identified on any particular photograph. An attempt was then made to correct the pricking of all doubtful stations. If this was impossible, the station was eliminated from the photograph in question.

Indications of small errors in the location of a few of the U. S. B. R. third-order control stations were evident, however this point could not be determined definitely by radial plot methods. In several cases these stations could not be held rigidly with nearby stations in the second-order scheme, even the identification was positive in each case. In any event the error is not believed to be over two meters.

When the plot was satisfactorily completed and all of the templets were securely fastened to the four joined map manuscripts, it was turned over so that the templets were face down on the radial plot table. The locations of all pass points and photograph centers were carefully pricked and indicated directly on the reverse sides of the four map manuscripts by circles in blue ink.

It is believed that excellent results were obtained in this radial plot and that accurate map manuscripts may be compiled which will be well within the limits of accuracy for the project.

28. Detailing:

These maps were compiled in accordance with instructions for Project Ph-2(45). Features and symbols were shown as indicated in Photogrammetry Instructions No. 10, 12, and 17.

The transforming printer at the Washington Office was not in proper adjustment at the time the photographs were printed and they could not be oriented in their entirety at the compilation table when radially plotting various types of pass points. Enough pass points had, however, been established during the radial plot so that each chamber of each photograph could be separately oriented. For at least two of the chambers on each photograph, it was found necessary to de-center the photograph radially, to or from the chamber being oriented, so that the radials to the pass points and horizontal control stations in the chamber would pass through their positions on the map manuscript.

In order to furnish the hydrographic party with shoreline and photo-hydro signals, detailing was divided into two distinct steps. In the first phase of the work all photo-hydro stations and shoreline pass points were located. Because of difficulties which have arisen on other projects and in order to insure the accuracy of the photo-hydro stations, the located positions were checked by a supervisor and all questionable signals were noted. The shoreline was then detailed from those photographs on which it was clearly visible and on which the bluffs were displaced outward from the center. (It might be stated that there were cases, particularly at the heads of narrow coves, where the photograph coverage was not sufficient to accurately delineate the shoreline and where stereoscop#ic vision could not be obtained. In these doubtful areas the hydrographic party checked the shoreline by running small planetable surveys. If errors were found, the map manuscripts were corrected and notes were lettered nearby designating that part of the shoreline which was located by planetable.) When the above work was completed, prints of the map manuscript were made and forwarded to the hydrographic party.

The second phase of the work, which consisted of interior detailing, was completed after we were certain that sufficient data had been furnished the hydrographic parties in order to complete their surveys.

Because of insufficient photograph coverage interior detailing could not be completed in the following areas:

The northeast part of T-8849
On sheet T-8850 between Latitude 47°-52' and Latitude 47°-53'
The northeast, northwest, and southwest parts of T-8851
On most of the interior area of T-8852

For the compilation of T-8852, only one flight of nine lens photographs, located close to the banks of the San Poil River, was furnished. In addition, there were three U.S. Army single lens 1:20000 photographs in a short flight which crossed the San Poil River near the south limits of this map manuscript. These single lens photographs were used successfully to supplement the nine lens photographs when radially plotting all types of pass points in the southern part of this map manuscript. In the area north of Latitude 480-00', where only nine lens photographs were available, there were places where the angle of intersection of radials, obtained for shoreline pass points and photo hydrographic signals, was weak. The doubtful shoreline pass points and pass points of two radial intersections are shown with green waterproof ink circles on the reverse side of the map manuscript. The doubtful photo-hydro signals have been shown with a question mark (?) after the number. (This map manuscript was detailed prior to the time that instructions for locating photo-hydro signals were revised. On future sheets only those photo-hydro signals which are clearly visible on the photographs and which can be located accurately by the intersection of at least three cuts are shown.)

Whenever possible the stereoscope was used to aid in determining the location of the tops of bluffs along the shoreline. The location of these bluffs could more readily be determined from photographs on which they were displaced away from the water line and the principal point of a photograph. Detail pass points were radially plotted near or along the tops of these bluffs so that they could be compiled as accurately as possible.

In many places it was very difficult to identify sufficient pass points for the compilation of roads. This was particularly true in areas of severe changes in relief and in places where roads wound thru dense woods. Similar conditions caused trouble in compiling the drainage, especially since the use of the stereoscope was very limited in interior areas.

Because of the numerous new roads and many changes in road alignment, it was found easier to compile all through roads, as they appeared on the photographs, rather than to make comparisons with old surveys and quadrangles and compile only the changes as suggested in the instructions for this project.

It is believed that all provisions of Paragraph 32 of the Instructions, relative to drafting, have been applied to the map manuscripts.

29. Supplemental Data:

The following maps or plans, which will be forwarded with the map manuscripts, were used to supplement the photographs:

Black & White Prints--10 each, Index Maps Nos. SP 1, SP 2, and 1

to 6 Inc.. (2 copies of Nos. 5 & 6)

Black & White Prints--Grand Coulee Power Plant, Scale 1 = 60

Grand Coulee Dam, Elevations & Sections

Fire Map, Scale 1 = 400 (Approx.)

Grand Coulee Power Plant, Scale 1 = 30'

Grand Coulee Dam, Vicinity Development,

Scale 1 = 250'

Grand Coulee Dam, Scale 1 = 100'

Town of Coulee Dam & Vicinity, Scale 1 = 600'

Columbia River Reservoir, Scale Unknown

The following map, which was also used, will be forwarded when the project is completed:

Black & White Print---Existing & Relocated Highways and Railroads, Scale 1"= 4 miles

30. Mean High-Water Line: (Lake shoreline at the adopted plane of reference) *

A complete discussion of this feature may be found in Paragraph 7 of the "Field Inspection Report, Area of the First Radial Plot," which is attached to this descriptive report.

The mean high-water line (Lake shoreline at the adopted plane of reference) is shown by a continuous black acid ink line, 008" in thickness, at a plane 1290.0 ft. above Mean Sea Level. There are no marsh areas bordering the shoreline.

31. Low-Water and Shoal Lines:

The field inspection unit did not indicate any low-water lines within the limits of these four map manuscripts.

Approximate shoal lines have been shown by a light, dashed, black acid ink line, as indicated by the field party.

32. Details Offshore from the Mean High-Water Line:

A floating debris net is the only detail offshore from the high-water line within the area of these four map manuscripts. Many rocks, adjacent to the shoreline, have been shown.

33. Wharves and Shoreline Structures:

A small dock, located on the south shore of the F. D. Roosevelt Lake, about two miles east of Coulee Dam, is the only shoreline structure within the area of these four map manuscripts. The dam has been completely detailed in accordance with field inspection data and various plans furnished the compilation office by the field party.

34. Landmarks and Aids to Navigation:

Form 567, recommending the charting as landmarks of the following objects, is attached.

HOUSE (North Gable) T-8850

BARN (South Gable) T-8851

HOUSE GABLE (Downstream) T-8852

BARN GABLE (Southwest) T-8852

Form 567 listing planetable and radially plotted positions of the following non-floating aids to navigation, is attached.

* A-profile of the reservoir water-level, from Brand Couled Dawn & the International Boundary, is attached to the Description Report for the Fifth Radial Plot (T-8863 & T-8865).

See also Sub. No. 38 PINE TREE POINT 1 LIGHT T-8849
SWAWILLA 3 LIGHT T-8850 7-8849
UPPER PLUM FLATS DAYBEACON 5 T-8850
LOWER CAMEL BLUFF DAYBEACON 6 T-8850
CAMEL BLUFF 8 LIGHT T-8851 7
CHINA BLUFF 11 LIGHT T-8851

Form 567, recommending the deletion of the following fixed aid to navigation, is attached.

SANPOIL DAYBEACON 10 T-8851

35. Hydrographic Control:

This office had a great deal of trouble locating the objects which had been pricked as hydrographic signals by the field parties. This was occasioned by the fact that the field men pricked small objects which, while they were definite on one photograph, could not be seen on adjacent photographs. This was usually caused by distortion due to relief. Due to the above conditions this office was forced to reject some signals and question others which could not be identified with certainty on enough photographs to obtain a good radial intersection.

In connection with the above it must be remembered that only every other photograph was furnished to the field parties and that inspection on these sheets was accomplished prior to receipt of letter 7ll-aar, dated June 20, 1947, which stated that future instructions would contain the clause that only well defined relatively permanent objects were to be selected. Because of the difficulty encountered in pricking photo-hydro stations in the area of this plot and in accordance with the above mentioned letter, the field party was requested to select larger objects which they felt would be clearly visible on adjacent photographs. As this was done, it was relatively easy to locate signals in the remaining sheets in this project.

After the hydrography was started the compilation office was informed that the hydrographic party was having difficulty with several of the photo-hydro signals that were believed to be accurately located. At a conference between personnel of the field party and personnel in this office, it was decided to await further investigation by the hydrographic party, of all questionable signals, before making changes on the map manuscript. In accordance therewith, Comdr. Jarman located additional signals and checked the location of many of the photo-hydro signals, during the field season.

On December 18, 1947, Lt. Comdr. Jarman and other personnel of the field party came to the Portland Office for a conference. At this time a thorough study was made of discrepancies and the difficulties encountered, and the following points were noted.

To interpret par. 6, page 19, of this compilation report, which is ambigious as to which photo-hydro stations were retained on, and which were deleted from, the map manuscripts T-8849 to T-8852 inclusive, Mr. Hanavich, who conducted some of the field operations and who is now in the Washington Office, was consulted, and from his explanation it has been concluded that this payagraph must mean that:

- (1) The photo-hydro stations whose positions were verified in the field were retained on the hydrographic sheet.
- (2) The photo-hydro stations whose positions were found in error of were not verified at all were deleted from the hydrographic sheet.
- (3) The stations in the first category were retained on the map manuscripts and those in the second category were deleted.

Actually, many more photo-hydro stations were located on these maps by radial plotting than were necessary for hydrographic control.

Charles Hanavich who was a member of the field centy and

Charles Hanavich, who was a member of the field party and was present at the meeting at the Portland Office on Dec. 18, 1947 (see previous page), was consulted about the paragraph on the opposite page and it was concluded that it must mean:

To aid the reviewer two classes of photo-hydro

To aid the reviewer two classes of photo-hydro stations were eliminated from necessary consideration as a result of the field topographic and hydrographic surveys. These two classes were:

- (1) Photo-hydro stations not used by the hydrographic party because they either could not be found on the ground or they were not needed. These were deleted from the map manuscript, and,
- (2) Certain photo-hydro stations whose compiled positions were verified by independent planetable surveys by Lt. Comdr. Jarman's party. This class was retained on the map manuscript but did not need to be verified during the review.

K.T. Adams 7/5/49

- 1. Most of photo-hydro positions were verified by planetable methods.
- 2. Due to distortion of ozalid prints of the map manuscript, some signals had been incorrectly transferred to boat sheets; thus an apparent error had existed.
- 3. Some small objects which had been pricked far out on the wings of distorted photographs had been misidentified in the compilation office. Similarly there were a few cases where objects were pricked erroneously by the field parties.
- 4. Due to strong winds in the area, many of the marked points, such as rags on bushes, had been lost; and in some cases the signal building party had errected signals over a nearby object, rather than the located photo-hydro position.
- 5. In their effort to locate all signals for the hydrographic party the field parties had pricked some indefinite objects; thus straining the limits of accurate photogrammetric compilation and creating a great deal of confusion. Had all field photographs been available many of the doubtful signals would never have been selected.

In order to avoid confusion during review, the hydrographic party deleted all photo-hydro signals, which had been verified, from the topographic sheets. Similarly all photo-hydro signals which were questionable, or which could not be relocated by the signal building party, were eliminated from the map manuscripts.

d Dee page opposite

A list of the hydrographic signals, shown on these four map manuscripts, is attached to this descriptive report.

36. Landing Fields and Aeronautical Aids:

7-8849

A small private seaplane base, The Amphibious Aircraft Association, is located just upstream from the Dam on the north side of the lake.

37. Geographic Names:

Geographic Names are the subject of a special report, "Investigation of Geographic Names, Sheets 8849 to 8859 inclusive, Project Ph-2(45)," which has been submitted to the Washington Office by the field party.

38. Recoverable Topographic Stations:

Copies of Form 524 are being submitted for all of the stations listed under Item 34, "Landmarks and Aids to Navigation." The following fixed aids to navigation, which were located by the hydrographic party, were plotted on the map manuscripts:

PINE TREE POINT 1 LIGHT 7-8849
SWAWILLA 3 LIGHT 7-8850
UPPER PLUM FLATS DAYBEACON 5 7-8850

39. Junctions:

Complete and satisfactory junctions have been made between all map manuscripts in this radial plot, and between map manuscripts T-8851 and T-8853.

40. F. D. Roosevelt Lake Reservation Lines:

The F. D. Roosevelt Lake reservation line was transferred to the map manuscripts, by use of the vertical projector, from ozalid prints of the U. S. B. R. index maps, on which it had been plotted. This was done by matching meridians and parallels and holding triangulation stations which were common to both the map manuscripts and the index maps. The line has been shown on the reverse side of the map manuscripts in red acid ink.

This reservation line was compiled prior to receipt of Director's letter, 711-rs, dated 7 November 1947, stating that it should be omitted. Due to the fact that this line may be of some use, it was not deleted. It will not, however, be compiled on the remaining map manuscripts in this project.

44. Comparisons with Existing Topographic Surveys:

All existing maps of the area were at a much smaller scale and were made before the waters of the F. D. Roosevelt Lake were impounded. Due to these facts only visual comparisons could be made.

45. Comparisons with Nautical Charts:

There are no nautical charts of the area.

Respectfully submitted,

J. Edward Deal Jr. Photogrammetric Engineer

J. Edward Deal Jo.

Approved after additional comments were added.

Robert A. Earle Chief of Party

Ahtt tark

Form 567 ev. March 1935

DEPARTMENT OF COMMERCE U. S. COAST AND GEODETIC SURVEY

ï

Area of 1st Radial Plot Project Ph 2(45) T-8849 to T8852 Inc.

LANDMARKS FOR CHARTS (Fixed Aids to Navigation)

June

Coulee Dam, Washington

I recommend that the following objects which have (hare not) been inspected from seaward to determine their value as landmarks, £ 8

J. T. Jermen

The positions given have been checked after listing. Junkal

be charted on (deleted from) the charts indicated.

STRIKE OUT ONE

TO BE CHARTED TO BE DELETED

CHARTS AFFECTED Chief of Party. Area not Sharted ŧ t . F OFFSHORE CHAR **ТИЗНОВЕ СИЧВ**Т жувой снукт DATE OF LOCATION 1947 F ¢ * ŧ LOCATION Radial Plot Plene-METHOD tebla 4 . MA 1927 DATUM ŧ F * 6.9 (320.5) 1070.3 D. P. METERS (1158.2)925.0 (12.1)(830,8) 1234.1 LONGITUDE 48 46 6 呂 POSITION 118 118 118 118 ٥ 8 D. M. METERS 842.9 1552.7 22.3 (300.4)(331.2)1521.9 536.4) 316.8 LATITUDE 56 52 53 40 ŭ ٥ 47 47 47 Φ Daybeacon ij Daybeason NAME AND DESCRIPTION T-8849 PINE TOFE DT. 1 Lt T-8650 LOWER CAMEL BLUFF T-8851 CAMEL BILLE B Lt. T-REGO UPPER PLIM MATS Roosevelt Lake T-8650 SWAWILLA 3 Lt. GENERAL Franklin D.

#

£

\$

¢

41

118

56

43

11 Lt

T-8851 CHINA BLUFF

Ż

(401.4) 1451.8

(787.3)488.0 This form shall be prepared in accordance with 1934 Field Memorandum, "LANDMARKS FOR CHARTS." The data should be considered for the charts of the area and not by individual field survey sheets. Information under each column heading should be given.

U. S. GOVERNMENT PRINTING OFFICE

Form 567 Pev. March 1935

DEPARTMENT OF COMMERCE U. S. COAST AND GEODETIC SURVEY

Area of the 1st Radial Plot Profect Ph-2(45)

LANDMARKS FOR CHARTS

STRIKE OUT ONE

TO BE CHARTED TO BE DELETED

T-8849 to T-8852 Inc.

June Weshington Coulse Dam.

1960

I recommend that the following objects which have (have not) been inspected from seaward to determine their value as landmarks, be charted on (deleted from) the charts indicated.

T. Jarman

The positions given have been checked after listing. Jenlial

Area not CHARTS AFFECTED Chief of Party. charted t 8 OFFSHORE CHART TRAND BECKER! ٠, HARBORCHART LOCATION DATE 1947 E 2 LOCATION Radial METHOD Plot 2 t ŧ NA 1927 DATUM ŧ ŧ D. P. METERS 125.5 (310.9) (1118,5 (680:1) (361.6) * 884.4 365.9 LONGITUDE 8 å NOILISON 118 118 118 ٥ 118 D, M. METERS (1327.8)54 1169.0 703.7 (1149.5)(684.0) 1155.8 525.4 LATITUDE 40 59 김 0 48 4 5 T-8852 HOUSE CABLE (Downstream) -T-8852 RAIN GABLE (Southwest) NAME AND DESCRIPTION T-8850 HOUSE (North Cable) T-8851 BARN (South Geble) Roosevelt Lake GENERAL Franklin D.

This form shall be prepared in accordance with 1934 Field Memorandum, "LANDMARKS FOR CHARTS." The data should be considered for the charts of the area and not by individual field survey sheets. Information under each column heading should be given.

U. S. GOVERNMENT PRINTING OFFICE

7	
rm 567 Jarch 1	
For M	·

DEPARTMENT OF COMMERCE U. S. COAST AN GEODETIC SURVEY

Area of 1st Radial Plot Project Ph 2 (45) T+8849 to T-8852 Inc.

LANDMARKS FOR CHARTS (Fixed Aids To Navigation)

June

I recommend that the following objects which have (frace wire) been inspected from seaward to determine their value as landmarks,. Coulee Dam, Washington

T. Jerman

The positions given have been checked after listing.

be charted on (deleted from) the charts indicated.

STRIKE OUT ONE

TO BE CHARTED TO BE DELETED

* Sen Poli Daybeacon 10 * Sen Poli Daybeacon nus been destroyed * This daybeacon has been destroyed * This daybeacon has been destroyed * This daybeacon number destroyed * This daybeacon									, 		in a facility
*This daybearon has been destroyed by erceston.			a	OSITION						TRAH	
*This daybearon has been destroyed by erosion.			ITUDE	LONG	ITUDE		METHOD OF OF				CHARTS FFECTE
•This daybearon has been destroyed by erosion.		0	D. M. METERS	1 1	D. P. METERS	DATUM					
With daybeagon has been destroyed by erceiton.	* San Poil Daybeacon 10	<u>.</u>									
agon has been destroyed											
ageon has been destroyed											
agon has been destroyed				!						<u>. </u>	
arton has been destroyed			-								
akon has been destroyed											
1 1 1 1 1	This daybearon has been des by erosion.	troyed								-	
i				- 							į
1 1 1			!								
1 1 1											
	·	 	<u></u>					,			
						<u> </u>					

This form shall be prepared in accordance with 1934 Field Memorandum, "LANDMARKS FOR CHARTS." The data should be considered for the charts of the area and not by individual field survey sheets. Information under each column heading should be given.

- Hydrographic Signals 8849
- 4901 Extreme west tower, Coulee Dam
- 4902 / Westerly of two middle towers
- Easterly of two middle towers 4903
- 4904 Extreme east tower, Coulee Dam
- 4906 Top of sawdust burner
- 4907 U/S end of traffic island in parking area
- 4908 West of two power poles in cove
- 4909 Lath with red and white cloth in hole in concrete block (d)
- 4910 Whitewashed rock on waterline
- 4911 Orange and red cloth on lath near Guard House (d)
- 4912 White rag on bush
- 4914 Red and white cloth on lath on point
- 4915 U/S gable of Seaplane Hanger
- 4916 White washed point of rock
- 4918 Square white banner on point of sand
- 4920 Whitewashed point of rock
- 4922 Whitewashed rock
- 4923 Inverted orange triangle on lath
- 4924 Whitewashed D/S corner flat granite rock
- 4925 Triangular red banner
- 4926 Point of rock, whitewashed
- 4927 Square aluminum mark on rock face
- 4928 D/S corner pumping station
- 4929 White banner with vertical red stripe
- 4931 Whitewashed rock point
- Whitewashed rock point D/S from Eden Harbor 4932

Page - 2 - Hydrographic Signals - 8849

4933 Whitewashed "X" on rock 4934 Point of rock on north side of Eden Harbor 4935 Whitewashed rock on square point 4936 Point of rock inside Eden Harbor 4937 Trimmed fir marked with white signal cloth 4938 Rag on lone bush on basalt 4939 Whitewashed point of rock Whitewashed point of rock 4941 4942 Whitewashed rock at side of square cut Triangular red banner on rock point 4943 Orange rag on greasewood bush 4945 Whitewashed "X" on rock face, above point 4947 Yellow and white cloth on lath 4948 4949 White rag on greasewood bush Red and white cloth on lath on rock bare 1' 4950 Yellow and white cloth on lath, U/S corner square rock 4952 4953 Whitewashed point of rock 4956 East gable, green roofed house Red and white strips of cloth on lath on low sand point 4957 4959 Orange rag on greasewood bush White rag on greasewood bush 4960 Orange and white strips on lath on rock point 4961 White square banner, orange stripe 4962 4963 Square orange banner on board on rock point 4967 Whitewashed rock point White signal, red stripe, on end of small dock 4968

Page - 3 - Hydrographic Signals - 8849

4918A

White rag on bush

4969	Whitewashed "X" on rock
4971	White rag on bush
4974	Triangular white banner (d)
4975	Whitewashed rock
4976	Square white banner on grass point
4977	Whitewashed triangle on rock
4978	Square red banner on grass point
4979	Orange signal cloth on pine
4981	Whitewashed triangle on rock
4983	White signal on pine
4985	Square orange banner on pine
4986	Orange rag on sage bush, side of path
4987	Base of pine on side of cliff
4989	Large white banner with rec "X" on lone pine (Lendmark fine on ms.) ms
4990	Whitewashed "X" on rock
4994	Red rag on trimmed sage
4996	Orange rag on sage bush
4998	White rag on bush
4904A	Red and yellow cloth on lath in bush
4906A	White flag on bush
4908A	Orange and white cloth on lath in bush on island
4910A	Red rag on greasewood bush
4912A	White signal cloth on end of brush
4914A	Red rag on bush
4916A	Orange and white cloth on lath in trimmed greasewood bush

Page - 4 - Hydrographic Signals - 8849

4920A	Square orange banner on lath
4922A	White banner at end of fence on 5' bank
4924A	Orange and red cloth on lath at path intersection
4926A	Red and white strips on lath
4928A	White rag on greasewood bush
4930A	Orange cloth on greasewood bush on top of 10' bluff
4936A	Orange signal cloth on sage bush
4940A	Orange banner on stake at greasewood bush
4942A	Orange cloth on greasewood
4944A	White rag on greasewood bush

4946A Triangular orange banner on U/S end of log

PROJECT Ph-2(45) Hydrographic Signals - 8850

5001 Yellow strip on lath 5001A Whitewashed point of rock 5002A Square red banner on gravel point. Was 4948A 5003 White rag on greasewood bush 5003A Point of rock between and below whitewash 5005A Orange rag on greasewood. Was 4997 5006 Whitewashed rock 5007 Orange cloth on lath at end of log on point 5007A Red and white strips on lath. 5008 Whitewashed "X" on rock 5009 White cloth on lath on rock point 5009A Whitewashed corner of square rock. Was 4901A 5010 Whitewashed triangle on rock point 5012 Red rag on greasewood 5013 Square red banner on stake White rag on greasewood bush 5015 5018 Orange and white strips on lath at point of grass in slide area 5020 Whitewashed point of high rock 5022A Lone pine White rag on greasewood bush 5023 5024 White cloth on snag on island 5025 Orange cloth on greasewood bush

Page - 2 - Hydrographic Signals - 8850

5026	Orange cloth on greasewood bush
5027	Small square orange banner
5028	Lone pine tree
5029	Red signal cloth on stake in bush
5029A	No description
5034	U/S pine of two
5035	Orange signal cloth on greasewood
5036	U/S granite outcrop of two
5037	Whitewashed rock point
5039	Red and white "X" on stump
5040 .	Small square orange banner at end of bush and fence
5041	D/S gable of old barn on bench
5042	North gable of unpainted house also submitted as landmark NORTH GABLE
5043	Square white banner on rock
5044	Orange and white signal cloth on lath on rock point
5045	Orange flag on south side of gate
5046	Single pine in granite outcrop
5048	Small square orange banner (d)
5049	Orange flag on fence
5050	Orange flag on deciduous tree
5051	U/S gable on farm house
5054	Red and white strips on lath
5056	Orange and white strips on lath on isolated rock
5057	White signal cloth on bush

Page - 3 - Hydrographic Signals - 8850

5058	Base of bushy cedar	
5060	White signal cloth on pine at edge of 15' bluff	
5061	White banner at greasewood bush	
5063	South gable of concrete house	
5064	White banner on rock. Transferred from 8851; was 5102	(d)
5065	Red and white strips on lath in greasewood bush	

HYDROGRAPHIC SIGNALS - T-8851 Project Ph-2(45)

5101A	White flag on greasewood bush (was 5067)
5105	East gable of farm house
5107	Whitewashed rock, Devils Pasture
5109	White rag on bush, end of point
5110	Whitewashed point of rock
5112	Orange banner on rock point, at the D/S end of a log
5113	Square orange banner on point of rock island
5114	White banner on basalt rock
5115	Lone pine (not flagged)
5117	Pine wrapped with orange signal cloth
5118	White signal cloth on Elderberry bush
5119	Red flag on granite point
5120	Orange cloth on greasewood bush
5121	White flag on point
5122	Square white banner in bush
5124	White rag on greasewood bush
5125	White flag on rock point
5126	Orange rag on greasewood bush
5128	Square orange banner (d)
5129	Orange flag on N side of abandoned road at H.W.L.
5132	U/S gable of old barn
5135	Orange cloth on greasewood bush on hillside.
5136	Orange flag at end of greasewood clump
5137	White signal cloth on greasewood bush W side of abandoned road

Page - 2 - Hydrographic Signals - T8851

5138	Red and white strips on lath in greasewood
5139	Red rag on greasewood bush
5140	White banner on fence post (d)
5141	White signal cloth on bush
5142	Lone deciduous tree
5143	Square white banner at road corner
5145	Orange rag on greasewood bush
5146	Orange flag on bush
5147	White rag on bush
5148	White flag on stake in rock
5149	Orange banner at end of fence
5150	Lone pine near C.P.S.P. 3, 1936
51 51	D/S gable of deserted house
5152	Red flag in trimmed bush
5153	D/S gable of abandoned barn
5154	White signal cloth on bush
5155	Orange rag on bush
5156	Lone pine on side of bank
5156A	Square orange banner in greasewood bush
5 15 7	Orange and white strips on stake in bush
5158	White signal cloth on small pine .
5159	White rag on greasewood
5161	Pine on side hill, east of two
5163	Red flag on stake in bush
5164	Orange signal on D/S pine of 3
5165	White flag at end of slide

Page - 3 - Hydrographic Signals - T -8851

Orange flag on pine

5174

5166 White signal cloth on pine at H.W.L.
5168 Orange signal cloth on dead pine at small cove
5170 White signal cloth on pine
5172 Forked pine near C.P. 47

PROJECT Ph-2(45) Hydrographic Signals - 8852

5201	White rag on inshore end of bush
5202	Lone pine in field
5203	Small square red banner (d)
5204	Orange rag on greasewood
5205	White signal cloth on lone pine
5206	Red flag on fence post (d)
5207	Orange signal cloth on pine
5208	White rag on greasewood
5209	White flag on U/S end of log on point
5210	White cloth on pine
5211	White signal cloth on pine at log dump
5212	Orange signal cloth on greasewood
5213.	Orange flag at point of clay spot
5214	Orange signal cloth on pine
5215	White signal on bush
5216	Red flag on fence at H.W.L.
5217 `	Yellow flag on greasewood bush (d)
5218	White cloth on pine
5219	White signal cloth on bush
5220	Orange signal cloth on small pine
5221	Orange signal cloth on trunk of small pine
5222	White flag on small pine
5223	White wrapped pine
5224	U/S gable, white house; green roof

Page - 2 - Hydrographic Signals - 8852

5 2 2 5	Orange cloth on dead top pine
5226	D/S gable of porch roof
5227	End of drain pipe
5228	Base of tallest pine, marked with red strip
5229	Tallest pine marked with red signal cloth
5230	Orange signal cloth on small pine
5231	White strip on pine
5232	White flag on pine at end of fence
52 33 ::	Orange cloth on pine
5234	Lone pine on hillside
5235	
5236	Orange signal cloth on pine at west side of abandoned road
5237	Chimney of house
5238	Apex of "A" frame at log dump
5239	White signal cloth on D/S pine
5240	West gable, unpainted house
5241	Red and white strips on lath on point
52 43	White strip on small pine

	Survey No.T-8849		/~	idissi	15 Mode	Sed in	Mar	\$ / ₃ 8°°	, chai		\$ ⁷ /
	`	6	Char.	of State of	13 Max	Con to the state of	Or oco Med	2. Octide of	Mod Model	J.S. Jani	
	Name on Survey	ZA.	<u></u>	<u>/c</u>	0	E	/ F	`	H	/ K	_
	Columbia River				<u> </u>	_	·	•			
	Douglas County										
	Washington*	(for	title					,			
	Fiddle Creek	-		·							
	Coulee Dam Town			_				<u> </u>			
	Grand Coulee Town	<u> </u>						<u> </u>	<u> </u>		
	Grand Coulee Dam							ļ <u>.</u>		ļ	
	Washington State Highway	10A		_							
	Washington State Highway	10B		,		,					
	Washington State Highway	#2		_	ļ	<u> </u>		 -		-	-
.	Washington State Highway	2F		<u> </u>				-10	-		-
	Delano	•		_		ļ				<u> </u>	\perp
	Grant County	_				ļ		-	- 61		-
	Okanogan County			ļ 			ļ	<u> </u>			:
	Lincoln County							-		<u> </u>	-
	Franklin D. Roosevelt La	ke*						-		ļ	
	Rattlesnake Canyon										
	Eden Harbor							ļ	· ·		-
	Spring Canyon] :
	Seatons Canyon				!			<u> </u>		<u> </u>	-
	Pine Tree Point										:
	Plum Point							 		<u> </u>	
	Community Church										1
•	St. Henrys Church			_	A 0 =	· · · · · · ·	دلحث				1
	Gibbs Bay	*	- Dec	s. of	BGN	6 np	Edm	HUV		,	-
	,	Aj	prove	i name	s unde	rlined	•				2
				10	-29 -4 8	<u>•</u>		<u> </u>		 	1 2



Survey No. 12-8850	į	-mort	of No. of	2 Mags	To or indicated	C CO MON	Guide	And McHall	Print	/ /
Name on Survey	A of	Oract Oract B	Ke / 6	Ser John Co.	E E	Or Les Hot	Guide G	H	'S' K	
W. shington								(USGB	1
Fanklin D. Roosevelt	Lake								*	2
Okenogan County									,	3
Ferry County		<u>.</u>	,	 						4
Lincoln County		<u> </u>					<u> </u>			5
Kaufman Flat			(pe	t Flat	a)				•	6
Coffman Canyon			(ne	ot Cany	on Ca	eek)				7
Neal Flat							ļ			8.
Neal Canyon					<u> </u>	<u> </u>				9
Plum Flats										10
Swawilla Basin			(ne	t Flat	8)			<u> </u>		11
Qui-Qui Creek							. "			12
Sugarloaf Mountain							,	-		13
Swawilla Cove			<u> </u>	armo	uth	aui-	ani	cv-		14
Cayusa Bay	} 1-	1-50				uth				15
- , ,	7			Name	s unde	rline 1/48	in ro	d are Hecu	approv	'ed 16
										17
										18
							i			19
								-		20
·			:				·	[21
										22
	<u>.</u> <u>.</u> .					`.	,			23
,				· 			_ ,			24
	,				-	, 				25
					,			,		26
				T	_		,	. 7		-

Or John Hade 6. Cripe of Wad J.S. Light Lief GEOGRAPHIC NAMES tron to the state Or local Maps Survey No. **1-8851** Name on Survey Ε G USGB Washington Ferry County Lincoln County USGB Franklin D. Roosevelt Lake Colville Indian Reservation State Highway No. 4 Camel Bluff Devils Canyon 9 Kaufman Flat 10 Devils Pasture to next covo upstream Shiff position to south Moonbeam Bay 12 Chine Bluff 13 Keller Ferry 14 USGB Sampoil River Thorn Spring 16 Penix Canyon 17 18 Names underlined in red are approved. 11/15/48 L.Hec L.Heck 19 21 22 23 24 25 26 27

	GEOGRAPHIC NAMES		/	13	Jet No	note /	/	/	Mag	Wilds /	* /
	Survey No. 1- 8852	,	- Nort	or to or	S. Wood	or rotation of	Or loca Made	o dine	And Mc Holl	1. Harry	/ /
~	Name on Survey	10	Cho.	50 Q	14	or Hor	out.	0.	20mg	39/	/
		A	В	/ c	D	E	/ F	G	/ H	K	
	Washington									USGB	1
	Ferry County							1. 1			2
	Franklin D. Roosevelt	lake								USGB	3
	Sanpoil River										4
	State Highway No. 4						1				5
											6.
	Dick Creek						. 1				7
	French Johns Lake					. 4					8
	Manila Creek										9
	Johnson Ridge								V.	N. Y.	10
	J hn Tom C eek		-								11
)	Silver Creek							**			12
	Watson Ridge			10				*	ap		13
	Watson Ridge Keller Gormer la	cati	07)	new	loca	teon	utsi	The second second	ap ore		13
	**************************************	scati	(-1)	new	loca	Names appro	under	The second second	in red		
	**************************************	cati	on)	New	loca		under	ined	in red	are	14
	**************************************	cati)	New	loca		under	ined	in red	are	14
	**************************************	cati)	New	loca		under	ined	in red	are	14 15 16
	**************************************	cati)	New	loca		under	ined	in red	are	14 15 16 17
	**************************************	cati)	new	loca		under	ined	in red	are	14 15 16 17 18
	**************************************	cati)		loca		under	ined	in red	are	14 15 16 17 18
	**************************************	cati)	new	loca		under	ined	in red	are	14 15 16 17 18 19
	**************************************	cati	. n)		loca		under	ined	in red	are	14 15 16 17 18 19 20 21
	**************************************	cati)		loca		under.	ined	in red	are	14 15 16 17 18 19 20 21
>	**************************************	cati)		loca		under.	ined	in red	are	14 15 16 17 18 19 20 21 22 23
	**************************************	cati)		loca		under.	ined	in red	are	14 15 16 17 18 19 20 21 22 23 24
>	**************************************	cati)		loca		under.	ined	in red	are	14 15 16 17 18 19 20 21 22 23 24 25

C

SIVISION OF CHOTCGRAMMETRY Review Report of Shoreline Map Manuscriets T-SCh9 to T-8852 Area of the First Radial Flot, Fn-2(4)

Subject numbers not used in this revisu report have been adequately covered in other parts of the descriptive report.

26 Control

Unrecovered triangulation stations plotted from local coordinates for the nurpose of placing the reservoir boundary have been left on the map renuscript.

Stati is shown with a recovery date indicate that the coordinate positions have been converted from the 1974 Grand Coulee Grid Datum to geographic positions on the NA 1927 datum.

A list of the recovered and the unrecovered at: tions (Form 1-2381-12) is attached to the descriptive report.

Coast and Geodetic Survey triangulation stations (adjusted from U. S. Fureau of Recommation positions) were plotted on the map remuscripts during review, as follows:

T-8849 Center, 1934
Seaton, 1933
T-8551 San Poil, West Base, 1934
San Poil, East Base, 1934
San Poil, 1934
Sage, 1936
Steep SS, 1936
*CPSP No. 8 SS, 1936
T-8852 Dick, 1936
Humn, I.S.
Ram, 1936
Silver, 1936
Lodoen, 1936
*Eadow, 1936

* On page 1072 of Geographic Positions, three stations of this line are listed by number in the following manner: "UISPCP No. 3, SS, 1936". Recovery cards for these stations say that the disks are stamped "CPSP 3 (SS) UISP 1015 + 83.61, 1936" etc. The stations are Control Points, (Columbia River Project), San Poil line, Sub-idiary Stations, Upstream Left, San Poil. Geodesy Division was notified concerning the discrepancy of designations in their listing.

28 Dateiling

Few revisions were made during review. Of these, the most noteworthy were:

- 1. Re-drawing the entire length of the road leading to the reismograph station on the southern side of Franklin D. Soorevelt Lake and east of the city of Grand Coulse.
 - 2. Checking the pricking of hydrographic station No. 88420 and drawing new relials. This placed the station in its proper relative position.
- T-8951 1. Alded "low-bank" delineation to shore from junction with T-8350 to hydrographic station No. 5109, and between stations numbers 5170-70.
 - 2. Re-drawing bluffs at Devils Pasture area and in the area of hydrographic stations numbers 5170-74.
- T-8852 1. Checking the oricking of hydrographic station number 5217 and drawing new radials to place it in its proper relative position.

Several areas of shoreline were located by planetable. These areas were indicated on the map manuscripts by ticks and by notes. The rotes have been removed from the map manuscript, but can be seen by consulting the ozalid prints of the maps, which were rate prior to review.

T-8849 Between Hydrographic statics Nos. 4957-59
T-8850 Between hydrographic stations Nos. 5027-34
> T-8851 Southern shore of Loonbeau Bay
Lead of estuary at 47° 55' 53"/118° 40' 44".

The mans meet the required accuracy with respect to shoreline, townsites, and near-shore highway delineation. Interior drainage and roads are well drawn in general, but are less accurate in withute detail.

<u>Note to Prafting Section</u>: The Reservation Boundary, and the boom for debris across Roosevelt Take near the dam, have been left on the remuscrint, but are not to be included on a re-drafted copy, in the first case, because of supplementary instructions; and in the second case, because the boom is not a stationery feature, but is anchored to bucys.

77 Geographic Hence

Formarate list for each map manuscript (compiled by the Gangraphic Names Section) is attached to this composite descriptive report.

43 Comparison with Previous Topographic and Contemporary Hydrographic Surveys

There are no previous surveys of the area of Ph-2(45) and the hydrographic survey is in progess.

44 Comparison with Existing Quadrangles

PLEM	S.E.	Coulee Ci Wilbur	1:125,	1920
1	S.E.	Keller	1:125,	1920

These are planimetric maps which show the land net, roads, railroads, drainage, county lines and settlement names.

Except for the land net and boundary lines, the present survey supersedes the quadrangles for their common areas.for charting purposes. Reviewed by:

funa J. Sturens
ena T. Stevens
T-8849 29 Oct. 1948
T-8850 2 Nov. 1948
T-8851 15 Nov. 1948
T-8852 19 Nov. 1948

Approved by

K.T. Adams Chief, Division of Photogrammetry

Division of Charts